



Specials

Elastic facade paint: widely applicable on modern and historic buildings

- Ralston PlastDecor

• paint • passion • people

Ralston
COLOUR & COATINGS

PlastDecor

Sometimes it has to be "a little bit more" or the situation demands a special solution because of the working of building materials and the hairline cracks that have arisen because of this. Ralston has an elastic coating for the renovation of cracked facades and concrete. PlastDecor is elastic and works crack covering.



Exterior
Interior

Ralston PlastDecor

- Excellent outdoor durability
- High elasticity
- Very easy to clean
- Low dirt adhesion

Intended Use

Walls and ceilings, on plasterboard, concrete, masonry and plasterwork. Exceptionally suitable as high build, decorative, hairline crack-hiding wall finish (up to 0.3 mm).

Ralston PlastDecor

Theoretical Coverage *	2,5 - 5 m ² /l
Scrub Resistance	Class 1, as per DIN EN 13 300 after 28 days.
Covering Class	Class 1 at economic use of 2,5 - 5 m ² /l as per ISO 6504-3 and DIN EN 13 300
Dust-Free Drying Time **	2
Time To Recoat **	8 - 12
Gloss Level	Satin gloss, approx. 6 G.U. at 85 °
French Emission Label	A+

* Dependent on the application method, the applied wet paint layer thickness and the surface

** Drying time in hours

For more information visit www.ralstoncolour.com

Part of
Royal Van Wijhe Verf

Ralston
COLOUR & COATINGS

Ralston Colour & Coatings B.V.
Postbus 205, 8000 AE Zwolle
Nederland

+31(0)38 - 429 11 00
info@ralstoncolour.com
www.ralstoncolour.com

2019-10