

according to 1907/2006/EC, Article 31

Version number 1.00 Revision: 24.10.2023 Printing date 24.10.2023

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Ralston Uni-Primer W

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

| Dangerous components: | | |
|--|---|-------------|
| EC number: 919-857-5 Reg.nr.: 01-2119463258-33 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066 | >10–≤50% |
| CAS: 14807-96-6 EINECS: 238-877-9 | Talc (Mg3H2(SiO3)4) substance with a Community workplace exposure limit | >10–≤25% |
| CAS: 1317-65-3 EINECS: 215-279-6 | Limestone (calcium carbonate) substance with a Community workplace exposure limit | >2.5–≤10% |
| CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40 | trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | >2.5–≤10% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32 | zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | ≥0.25-<2.5% |
| CAS: 100545-48-0 EC number: 309-629-8 Reg.nr.: 01-2119979085-27 | Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine Skin Sens. 1B, H317; Aquatic Chronic 3, H412 | ≥0.1–<1% |

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

Consult doctor if symptoms persist.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Take off contaminated clothing.

Wash with water and soap.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 3)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Observe instructions for use / storage.

Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight. Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

| Ingredients with limit values that require monitoring at the workplace: | | |
|---|--|--|
| 14807-96-6 Talc (M | 14807-96-6 Talc (Mg3H2(SiO3)4) | |
| WGW (Netherland) | Long-term value: 0.25 mg/m³ respirabel | |
| 1317-65-3 Limestone (calcium carbonate) | | |
| WGW (Netherland) | Long-term value: 10 mg/m³ zie bijl. 3 | |

| DNELs | | | |
|--|---|-------------------|------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| Oral | ral DNEL Systemic; Long term 125 mg/kg bw/24h (Consumers) | | |
| Dermal | DNEL Sys | stemic; Long term | 125 mg/kg bw/24h (Consumers) |
| | | | 208 mg/kg bw/24h (Workers) |
| Inhalative | DNEL Sys | stemic; Long term | 185 mg/m³ (Consumers) |
| | | | 871 mg/m³ (Workers) |
| 100545-48-0 Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | | | |
| Inhalative | alative DNEL Local; Long term 0.83 mg/m³ (Consumers) | | |
| | | | 3.35 mg/m³ (Workers) |

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures: Wash hands before breaks and at the end of work. **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 4)

Hand protection



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR **Eye/face protection**



Tightly sealed goggles

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: White

Odour:Product specificOdour threshold:Not determined.Melting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range 154–193 °C (Hydrocarbons, C9-C11, n-alkanes,

isoalkanes, cyclics, <2% aromatics)

Flammability Flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:35–40 °CDecomposition temperature:Not determined.

pH Mixture is non-soluble (in water).

Viscosity:

Kinematic viscosityNot determined. **Dynamic at 20 °C:**956.42–1,141.3 mPas

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 2 hPa (Hydrocarbons, C9-C11, n-alkanes,

isoalkanes, cyclics, <2% aromatics)

Density and/or relative density

Density at 20 °C:1.18–1.22 g/cm³Relative densityNot determined.Vapour densityNot determined.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 5)

9.2 Other information

Appearance:

Form: Viscous

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC) 35.53 % **Solids content:** 65.6 %

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes

Flammable liquids Flammable liquid and vapour.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Oxidising substances.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

| LD/LC50 values relevant for classification: | | | |
|--|---|-----------------------|--|
| Hydrocar | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| Dermal | LD50 | >5,000 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | >5,000 mg/l (rat) | |
| 1317-65-3 | 1317-65-3 Limestone (calcium carbonate) | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| 7779-90-0 | 7779-90-0 trizinc bis(orthophosphate) | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| 1314-13-2 | 1314-13-2 zinc oxide | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| 100545-48-0 Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | | | |
| Oral | LD50 | >2,000 mg/kg (rat) | |

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 6)

Inhalative LC50/4 h >5.05 mg/l (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity

| Aquatic toxicity: | | | |
|--|---|--|--|
| Hydroca | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | |
| EL0 | 1,000 mg/l /48h (daphnia) | | |
| EL50 | >1,000 mg/l /72h (Pseudokirchneriella subcapitata) | | |
| | 1,000 mg/l /48h (daphnia) | | |
| LL50 | >1,000 mg/l /96h (Oncorhynchus mykiss) | | |
| NOELR | ELR 100 mg/l /72h (Pseudokirchneriella subcapitata) | | |
| 1317-65 | 1317-65-3 Limestone (calcium carbonate) | | |
| EC50 | >1,000 mg/l /48h (daphnia) | | |
| | >200 mg/l /72h (Desmodesmus subspicatus) | | |
| LC50 | >10,000 mg/l /96h (Oncorhynchus mykiss) | | |
| 100545-48-0 Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | | | |
| EL50 | >100 mg/l /72h (Pseudokirchneriella subcapitata) | | |
| | >10 mg/l /48h (daphnia) | | |
| LL50 | >10 mg/l /96h (Oncorhynchus mykiss) | | |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 7)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| Europ | European waste catalogue | | |
|-------|---|--|--|
| HP3 | Flammable | | |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity | | |
| HP14 | Ecotoxic | | |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS

IMDG PAINT, MARINE POLLUTANT

IATA Paint

14.3 Transport hazard class(es)

ADR, IMDG





Class 3 Flammable liquids.

Label 3

IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant:Symbol (fish and tree)Special marking (ADR):Symbol (fish and tree)

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 8)

14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30 EMS Number: F-E, $\underline{\text{S-E}}$

Stowage Category A

14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3
Tunnel restriction code D/E

Remarks: Exempted according to 2.2.3.1.5 (Viscous liquids)

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1263 PAINT, 3, III, ENVIRONMENTALLY

HAZARDOUS

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

Product subcategory: One-pack performance coatings

· Solvent-borne coatings, Limit value: 500 g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements $200\ t$ Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 9)

REGULATION (EU) 2019/1148

| Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of | f |
|--|---|
| licensing under Article 5(3)) | |

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

| Flammable liquids | On basis of test data |
|--|--|
| Specific target organ toxicity (single exposure) | The classification of the mixture is generally based |
| Hazardous to the aquatic environment - long-term | on the calculation method using substance data |
| (chronic) aquatic hazard | according to Regulation (EC) No 1272/2008. |

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3





according to 1907/2006/EC, Article 31

Printing date 24.10.2023 Version number 1.00 Revision: 24.10.2023

Trade name: Ralston Uni-Primer W

(Contd. of page 10)

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard — Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3