

- 
- Ralston Uni-Primer
 - Ralston 4S Wood-Primer

• paint • passion • people

Ralston
COLOUR & COATINGS



Ralston Uni-Primer

Intended Use

As a universal primer on (pre-treated) metal, plastic and wood.



Exterior
Interior



Ralston 4S Wood-Primer

Intended Use

As wood primer, and as undercoat on pre-treated wood, metal and plastic.



Exterior
Interior

Ralston Uni-Primer

Theoretical Coverage *	11,4 m ² /l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	0,5
Tack-Free Time **	3,45
Time To Recoat **	5
Wet Film Thickness	90 Mμ
Dry Film Thickness	35 Mμ
Gloss Level	Matt, approx. 10 G.U. at 60 °

Ralston 4S Wood-Primer

Theoretical Coverage *	14 m ² /l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	1
Tack-Free Time **	3
Time To Recoat **	16
Wet Film Thickness	72 Mμ
Dry Film Thickness	45 Mμ
Gloss Level	Satin gloss, approx. 20 G.U. at 60 °

Part of
Royal Van Wijhe Verf

Ralston
COLOUR & COATINGS

Ralston Colour & Coatings B.V.
Postbus 205, 8000 AE Zwolle
Nederland

+31(0)38 - 429 11 00
info@ralstoncolour.com
www.ralstoncolour.com

2020-01