

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

### 1 Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** Ralston 4S Satin BW

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Paint

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

#### 1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

### 2 Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02

**Signal word** Warning

**Hazard statements**

H226 Flammable liquid and vapour.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 2)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

**Trade name:** Ralston 4S Satin BW

(Contd. of page 1)

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3 Composition/information on ingredients**

**3.2 Mixtures**

<b>Dangerous components:</b>		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336, EUH066	>2.5–≤25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics ⚠ Asp. Tox. 1, H304, EUH066	>2.5–≤10%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) substance with a Community workplace exposure limit	>2.5–≤10%
EC number: 920-114-2 Reg.nr.: 01-2119459347-30	Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics ⚠ Asp. Tox. 1, H304, EUH066	>2.5–≤10%
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg.nr.: 01-2119539582-35	2-methylpentane-2,4-diol ⚠ Repr. 2, H361d; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures**

**4.1 Description of first aid measures**

**General information:**

Take affected persons out into the fresh air.  
Keep warm, position comfortably and cover well.  
Consult doctor if symptoms persist.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Take off contaminated clothing.  
Wash with water and soap.

**After eye contact:**

Rinse opened eye for several minutes under running water.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After swallowing:**

If person is conscious, rinse out mouth.  
Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 2)

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

**Protective equipment:** Wear fully protective suit.

#### Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:** Observe instructions for use / storage.

**Requirements to be met by storerooms and receptacles:** Protect from heat and direct sunlight.

**Information about storage in one common storage facility:** Store away from oxidising agents.

#### Further information about storage conditions:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 4)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 3)

**8 Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**14807-96-6 Talc (Mg3H2(SiO3)4)**

WGW (Netherland)	Long-term value: 0.25 mg/m <sup>3</sup> respirabel
------------------	---

**DNELs**

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)
Dermal	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)
		208 mg/kg bw/24h (Workers)
Inhalative	DNEL Systemic; Long term	185 mg/m <sup>3</sup> (Consumers)
		871 mg/m <sup>3</sup> (Workers)

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:** Wash hands before breaks and at the end of work.

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

**Hand protection**



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye/face protection**



Tightly sealed goggles

**9 Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Physical state**

Fluid

**Colour:**

Different according to colouring

**Odour:**

Product specific

**Odour threshold:**

Not determined.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 4)

<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	154–193 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Flammability</b>	Flammable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	41 °C
<b>Auto-ignition temperature:</b>	233 °C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not determined.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>Dynamic at 20 °C:</b>	1,062.93–1,263.6 mPas
<b>Solubility</b>	
<b>water:</b>	Not miscible or difficult to mix.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	2 hPa (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.15–1.19 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Viscous
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Solvent content:</b>	
<b>VOC (EC)</b>	21.03 %
<b>Solids content:</b>	78.9 %
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Flammable liquids</b>	Flammable liquid and vapour.

### 10 Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability** The product is stable.

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 5)

### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** Oxidising substances.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
<b>Hydrocarbons, C14-C19, isoalkanes, cyclics, &lt;2% aromatics</b>		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,266 mg/l (rat)
<b>107-41-5 2-methylpentane-2,4-diol</b>		
Oral	LD50	3,700 mg/kg (rat)
Dermal	LD50	8,560 mg/kg (rabbit)

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 6)

### 12 Ecological information

#### 12.1 Toxicity

<b>Aquatic toxicity:</b>	
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	
EL0	1,000 mg/l /48h (daphnia)
EL50	>1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL50	>1,000 mg/l /96h (Oncorhynchus mykiss)
NOELR	100 mg/l /72h (Pseudokirchneriella subcapitata)
<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>	
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL0	1,000 mg/l /96h (Oncorhynchus mykiss)
<b>Hydrocarbons, C14-C19, isoalkanes, cyclics, &lt;2% aromatics</b>	
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL0	87,556 mg/l /96h (Oncorhynchus mykiss)
NOELR	1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	5 mg/l /21d (daphnia)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

#### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

#### 12.7 Other adverse effects

#### Additional ecological information:

#### General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

#### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

<b>European waste catalogue</b>	
HP3	Flammable

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 7)

**14 Transport information**

**14.1 UN number or ID number**

ADR, IMDG, IATA UN1263

**14.2 UN proper shipping name**

ADR UN1263 PAINT

IMDG PAINT

IATA Paint

**14.3 Transport hazard class(es)**

ADR, IMDG, IATA



**Class** 3 Flammable liquids.

**Label** 3

**14.4 Packing group**

ADR, IMDG, IATA III

**14.5 Environmental hazards:** Not applicable.

**14.6 Special precautions for user** Warning: Flammable liquids.

**Hazard identification number (Kemler code):** 30

**EMS Number:** F-E,S-E

**Stowage Category** A

**14.7 Maritime transport in bulk according to**

**IMO instruments** Not applicable.

**Transport/Additional information:**

**ADR**

**Limited quantities (LQ)** 5L

**Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**Transport category** 3

**Tunnel restriction code** D/E

**Remarks:** Exempted according to 2.2.3.1.5 (Viscous liquids)

**IMDG**

**Limited quantities (LQ)** 5L

**Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**UN "Model Regulation":**

UN 1263 PAINT, 3, III

(Contd. on page 9)



**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Satin BW

(Contd. of page 8)

**15 Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Directive 2004/42/EC**

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior/exterior trim and cladding paints for wood and metal
- Solvent-borne coatings, Limit value: 300 g/l

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 10)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

**Trade name:** Ralston 4S Satin BW

(Contd. of page 9)

Flammable liquids	On basis of test data
-------------------	-----------------------

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1