



PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 1/1/2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Antifreeze

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
60062 Northbrook, IL - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Reproductive toxicity, Category 2 H361

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07



GHS08

Signal word (CLP) : Warning
Hazardous ingredients : ethylene glycol; diethylene glycol; potassium 2-ethylhexanoate; sodium 2-ethylhexanoate
Hazard statements (CLP) : H302 - Harmful if swallowed.
H361 - Suspected of damaging fertility or the unborn child.
Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective clothing, eye protection, face protection.
P301+P312 - IF SWALLOWED: Call a doctor, a POISON CENTER if you feel unwell.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P330 - Rinse mouth.
P405 - Store locked up.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Other hazards which do not result in classification : No additional information available.

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% by weight	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethylene glycol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1	45 – 50	Acute Tox. 4 (Oral), H302
water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	45 – 50	Not classified
diethylene glycol	(CAS-No.) 111-46-6 (EC-No.) 203-872-2 (EC Index-No.) 603-140-00-6	0.5 – 5	Acute Tox. 4 (Oral), H302
potassium 2-ethylhexanoate	(CAS-No.) 3164-85-0 (EC-No.) 221-625-7	0 – 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361
sodium 2-ethylhexanoate	(CAS-No.) 19766-89-3 (EC-No.) 243-283-8	0 – 5	Repr. 2, H361
denatonium benzoate	(CAS-No.) 3734-33-6 (EC-No.) 223-095-2	30 - 50 ppm	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Rinse immediately with plenty of water (for at least 15 minutes), Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	: Obtain emergency medical attention. Rinse mouth. If the person is fully conscious, make him/her drink two glasses of water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whiskey. For children, give proportionally less liquor, according to weight.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).

4.3. Indication of any immediate medical attention and special treatment needed

A more effective intravenous antidote for physician uses is 4-methylpyrazole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occurred.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry chemical. Foam. Sand. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Product is not flammable or combustible but may burn under fire conditions.
-------------	---

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Direct sunlight. Keep container closed when not in use. Product may become solid at temperatures below -37 °C (-34 °F). Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.
- Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.
- Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethylene glycol (107-21-1)		
EU	Local name	Ethylene glycol
EU	IOEL TWA	52 mg/m ³
EU	IOEL TWA [ppm]	20 ppm
EU	IOEL STEL	104 mg/m ³
EU	IOEL STEL [ppm]	40 ppm
EU	Remark	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	OEL TWA	52 mg/m ³ (La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.)

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylene glycol (107-21-1)		
Belgium	OEL TWA [ppm]	20 ppm (La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.)
Belgium	OEL STEL	104 mg/m ³ (La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.)
Belgium	OEL STEL [ppm]	40 ppm (La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.)
France	VME (OEL TWA)	52 mg/m ³
France	VME (OEL TWA) [ppm]	20 ppm
France	VLE (OEL C/STEL)	104 mg/m ³
France	VLE (OEL C/STEL) [ppm]	40 ppm
Netherlands	MAC-TGG (OEL TWA)	52 mg/m ³ (damp) 10 mg/m ³ (druppels)
Netherlands	MAC-TGG (OEL TWA) [ppm]	20 ppm (damp) 3.9 ppm (druppels)
Netherlands	MAC-15 (OEL STEL)	104 mg/m ³ (damp)
Netherlands	MAC-15 (OEL STEL) [ppm]	40 ppm (damp)
Sweden	NGV (OEL TWA)	25 mg/m ³ Ethlenglykol (ånga och aerosol); Sweden; Level Limit Value (AFS 2015:7)
Sweden	NGV (OEL TWA) [ppm]	10 ppm Ethlenglykol (ånga och aerosol); Sweden; Level Limit Value (AFS 2015:7)
Sweden	KTV (OEL STEL)	104 mg/m ³ Ethlenglykol (ånga och aerosol); Sweden; Short-term value (AFS 2015:7)
Sweden	KTV (OEL STEL) [ppm]	40 ppm Ethlenglykol (ånga och aerosol); Sweden; Short-term value (AFS 2015:7)
United Kingdom	WEL TWA (OEL TWA) [1]	10 mg/m ³ 52 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	20 ppm
United Kingdom	WEL STEL (OEL STEL)	104 mg/m ³
United Kingdom	WEL STEL (OEL STEL) [ppm]	40 ppm
USA - ACGIH	Local name	Ethylene glycol
USA - ACGIH	ACGIH OEL TWA	10 mg/m ³
USA - ACGIH	ACGIH OEL TWA [ppm]	25 ppm (Vapor fraction)
USA - ACGIH	ACGIH OEL STEL	10 mg/m ³ (Inhalable fraction, Aerosol only)
USA - ACGIH	ACGIH OEL STEL [ppm]	50 ppm (Vapor fraction)
USA - ACGIH	Remark (ACGIH)	Upper respiratory tract & eye irritant
USA - ACGIH	Regulatory reference	ACGIH 2021
diethylene glycol (111-46-6)		
Sweden	NGV (OEL TWA)	10 mg/m ³ Dietylenglykol; Sweden; Level limit value; (AFS 2015:7)
Sweden	NGV (OEL TWA) [ppm]	45 ppm Dietylenglykol; Sweden; Level limit value; (AFS 2015:7)
Sweden	KTV (OEL STEL)	20 mg/m ³ Dietylenglykol; Sweden; Short-term value; (AFS 2015:7)

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

diethylene glycol (111-46-6)		
Sweden	KTV (OEL STEL) [ppm]	90 ppm Dietylenglykol; Sweden; Short-term value; (AFS 2015:7)
United Kingdom	WEL TWA (OEL TWA) [1]	101 mg/m³
United Kingdom	WEL TWA (OEL TWA) [2]	23 ppm

8.2. Exposure controls

Appropriate engineering controls:

No additional information available.

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Respiratory protection not required in normal conditions. If exposed to levels above exposure limits wear appropriate respiratory protection.



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Molecular mass	: 62.07 g/mol Ethylene Glycol
Color	: Orange
Odor	: Mild.
Odor threshold	: No data available
pH	: 8 – 9
Relative evaporation rate (butylacetate=1)	: Nil
Melting point	: No data available
Freezing point	: -37 °C (-34 °F)
Boiling point	: 108.3 °C (226.9 °F)
Flash point	: 116 °C (241 °F) [100% Ethylene Glycol] <i>ASTM D56</i>
Auto-ignition temperature	: 400 °C (752 °F) [100% Ethylene Glycol] <i>Literature</i>
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: < 0.1 @ 20 °C
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 1.06
Density	: 1.06 kg/l (8.84 lbs/gal)
Solubility	: Water: Complete
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Explosive limits	: Not applicable

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Extremely high or low temperatures. Keep away from any flames or sparking source.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Alcohols. Aldehydes. Carbon dioxide. Carbon monoxide. Ethers. Fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ATE CLP (oral)	1010.101 mg/kg bodyweight
----------------	---------------------------

denatonium benzoate (3734-33-6)	
LD50 oral rat	584 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Literature study, Dermal)

ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LD50 dermal	> 3500 mg/kg bodyweight (Mouse, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))

diethylene glycol (111-46-6)	
LD50 oral rat	19600 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	11890 mg/kg (Rabbit, Dermal)
LC50 inhalation rat (mg/l)	> 4.6 mg/l/4h (Other, 4 h, Rat, Weight of evidence)

Skin corrosion/irritation : Not classified
pH: 8 – 9

Serious eye damage/irritation : Not classified
pH: 8 – 9

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Chronic aquatic toxicity : Not classified

denatonium benzoate (3734-33-6)	
LC50 fish 1	> 1000 mg/l (96 h, Salmo gairdneri, Literature study)
EC50 Daphnia 1	13 mg/l (48 h, Daphnia magna, Literature study)
ethylene glycol (107-21-1)	
LC50 fish 1	40761 mg/l (96 h, Salmo gairdneri, Static system)
EC50 Daphnia 1	> 10000 mg/l (24 h, Daphnia magna)
EC50 96h algae (1)	6.5 - 13 g/l (Selenastrum capricornutum, Growth)
diethylene glycol (111-46-6)	
LC50 fish 1	> 5000 ppm (24 h, Carassius auratus)
LC50 fish 2	75200 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Experimental value)
EC50 Daphnia 1	> 10000 mg/l (24 h, Daphnia magna)
EC50 Daphnia 2	> 10000 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 96h algae (1)	9362 mg/l (ECOSAR, Algae, QSAR)

12.2. Persistence and degradability

denatonium benzoate (3734-33-6)	
Persistence and degradability	Biodegradability in water: no data available. No (test) data on mobility of the substance available.
ethylene glycol (107-21-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O ₂ /g substance
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance
ThOD	1.29 g O ₂ /g substance
BOD (% of ThOD)	0.36
diethylene glycol (111-46-6)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance
Chemical oxygen demand (COD)	1.51 g O ₂ /g substance
ThOD	1.51 g O ₂ /g substance
BOD (% of ThOD)	0.015

12.3. Bioaccumulative potential

denatonium benzoate (3734-33-6)	
Log Pow	1.78 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
ethylene glycol (107-21-1)	
BCF fish 1	10 (72 h, Leuciscus idus)
BCF other aquatic organisms 1	0.21 - 0.6 (Procambarus sp., Chronic)
BCF other aquatic organisms 2	190 (24 h, Algae)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
diethylene glycol (111-46-6)	
BCF fish 1	100 (Other, 3 day(s), Leuciscus melanotus, Static system, Fresh water, Experimental value)
Log Pow	-1.98 (Calculated, Other)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

denatonium benzoate (3734-33-6)	
Ecology - soil	No (test)data on mobility of the substance available.
ethylene glycol (107-21-1)	
Surface tension	48 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.
diethylene glycol (111-46-6)	
Surface tension	0.0485 N/m
Log Koc	0 (log Koc, SRC PCKOCWIN v1.66, Calculated value)

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

diethylene glycol (111-46-6)	
Ecology - soil	Highly mobile in soil.
12.5. Results of PBT and vPvB assessment	
Component	
ethylene glycol (107-21-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
diethylene glycol (111-46-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
12.6. Other adverse effects	
Additional information	: Avoid release to the environment.
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to an approved waste disposal plant.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	
In accordance with ADR / IMDG / IATA / ADN / RID	
14.1. UN number	
UN-No. (ADR)	: Not regulated
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not regulated
UN-No. (RID)	: Not regulated
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: Not regulated
Proper Shipping Name (IMDG)	: Not regulated by IMDG (in quantites under 5,000 lbs in any one inner package)
Proper Shipping Name (IATA)	: Not regulated by IATA (in quantites under 5,000 lbs in any one inner package)
Proper Shipping Name (ADN)	: Not regulated
Proper Shipping Name (RID)	: Not regulated
14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: Not regulated
IMDG	
Transport hazard class(es) (IMDG)	: Not applicable
IATA	
Transport hazard class(es) (IATA)	: Not applicable
ADN	
Transport hazard class(es) (ADN)	: Not regulated
RID	
Transport hazard class(es) (RID)	: Not regulated
14.4. Packing group	
Packing group (ADR)	: Not regulated
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not regulated
Packing group (RID)	: Not regulated
14.5. Environmental hazards	
Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

- Overland transport

Not regulated

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

15.1.2. National regulations

ECL (South Korea): The intentional ingredients of this product are listed.

EINECS (Europe): The intentional ingredients of this product are listed

DSL (Canada): The intentional ingredients of this product are listed

Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

PEAK Dexcool 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2

SDS EU (REACH Annex II) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.