



PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/12/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant
SDS ID : 115008

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifreeze & Coolant
Recommended use : Contact supplier for more information on uses.

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

Signal word (GHS-US) : None
Hazard statements (GHS-US) : None
Precautionary statements (GHS-US) : None

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
propylene glycol	(CAS-No.) 57-55-6	>= 50	Not classified
water	(CAS-No.) 7732-18-5	<= 50	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Not expected to present a significant hazard under anticipated conditions of normal use.

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation.
- Symptoms/effects after eye contact : May cause slight irritation.
- Symptoms/effects after ingestion : Excessive ingestion may cause central nervous system effects.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Alcohol resistant foam. Dry chemical. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Stable.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
- Methods for cleaning up : Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propylene glycol (57-55-6)

Not applicable

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

water (7732-18-5)

Not applicable

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Face shield. Protective goggles.

Hand protection:

Not required for normal conditions of use

Eye protection:

Chemical goggles or face shield

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Yellow
Odor	: Odorless
Odor threshold	: No data available
pH	: 8.3
Reserve Alkalinity	: No data available
Relative evaporation rate (butylacetate=1)	: Slight
Freezing point	: -34 °C (-28 °F)
Boiling point	: 106 °C (222 °F)
Flash point	: None. Percentage of water is greater than 20%.
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.1 mm Hg
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 1.02
Density	: 1.02 kg/l (8.51 lbs/gal)
Solubility	: Water: Complete
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: Not applicable
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.

9.2. Other information

VOC content : 0 %

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

propylene glycol (57-55-6)	
LD50 oral rat	20000 mg/kg (Rat; Experimental value)
LD50 dermal rat	22500 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	20800 mg/kg (Rabbit; Experimental value)
ATE US (oral)	20000 mg/kg bodyweight
ATE US (dermal)	20800 mg/kg bodyweight

Skin corrosion/irritation : Not classified
pH: 10 - 11

Serious eye damage/irritation : Not classified
pH: 10 - 11

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Contact during a long period may cause light irritation.

Symptoms/effects after eye contact : May cause slight irritation.

Symptoms/effects after ingestion : Excessive ingestion may cause central nervous system effects.

SECTION 12: Ecological information

12.1. Toxicity

propylene glycol (57-55-6)	
LC50 fish 1	51,600.00 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Experimental value)
LC50 fish 2	51,600.00 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss)
ErC50 (algae)	24,200.00 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

propylene glycol (57-55-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil.
Biochemical oxygen demand (BOD)	0.96 - 1.08 g O ₂ /g substance
Chemical oxygen demand (COD)	1.63 g O ₂ /g substance
ThOD	1.69 g O ₂ /g substance

12.3. Bioaccumulative potential

propylene glycol (57-55-6)	
BCF other aquatic organisms 1	0.09
Log Pow	-1.41 - -0.30 (-0.92; Experimental value; -1.07; Experimental value; Equivalent or similar to OECD 107; 20.5 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

propylene glycol (57-55-6)	
Surface tension	71.60 mN/m (21.5 °C, 1.01 g/l, EU Method A.5: Surface tension)
Log Koc	0.46 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : an approved waste disposal plant.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

ADR

Not regulated

Transport by sea

In accordance with IMDG / IMO

Not regulated

Air transport

In accordance with IATA / ICAO

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

EPA TSCA Regulatory Flag

Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed

water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PEAK ECOSHIELD 50/50 Prediluted Antifreeze and Coolant

WHMIS Classification

This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations

California Proposition 65 - This product does not contain any substance(s) known to the state of California to cause cancer, developmental toxicity and/or reproductive toxicity

propylene glycol (57-55-6)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date

: 09/12/2023

Data sources

: Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Full text of H-statements:

NFPA health hazard


: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard

: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI 1

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.