

PEAK
ORIGINAL
EQUIPMENT
TECHNOLOGY®

EUROPEAN VEHICLES

EXTENDED LIFE **PINK**
ANTIFREEZE + COOLANT

DESCRIPTION

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES** is a line of premium coolants specifically designed to match the technology and color requirements of **European** vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - PINK** is an ethylene glycol-based antifreeze/coolant specifically developed for use in any European vehicle requiring a Pink silicate-free organic acid technology (OAT) formulation. It contains high-quality organic acid corrosion inhibitors and is free of borate, nitrite, nitrate, phosphate, silicate and amines chemicals.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - PINK** meets the performance requirements of ASTM D3306 and BS 6580. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 150,000 miles or 5 years.

FEATURES & BENEFITS

- Matches each European vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and BS 6580
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

Use **PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT concentrate** to perform a complete flush/fill or top-off.

Use **PEAK ORIGINAL EQUIPMENT TECHNOLOGY 50/50 PREDILUTED ANTIFREEZE + COOLANT** when just topping off your system.

**A PERFECT MATCH
FOR EVERY VEHICLE**



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

*Using a 15 psig (103 kPa) pressure cap in good condition



*Available in both 50/50 Prediluted
and Concentrate*



ORIGINAL EQUIPMENT TECHNOLOGY

ANTIFREEZE + COOLANT

APPLICATIONS

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for EUROPEAN VEHICLES - PINK is specifically engineered for use in all European vehicles requiring a PINK SILICATE-FREE ORGANIC ACID TECHNOLOGY extended life antifreeze + coolant:

- Audi: 1996-2007
- Fiat/Alfa-Romeo: 2006 and up
- Ferrari: 2010 and up
- Jaguar: 1997 and up
- Land Rover: 1998 and up
- Mini One D, Mini Cooper D: 2007-2011
- Porsche: 1996-2009
- Range Rover: 2006 and up
- Saab/Opel: 2001 and up
- Volvo: 2016 and up
- VW: 1996-2008

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance	Visual	Pink	Pink	Distinctive
pH, (50% vol)	D1287	8.8	8.8	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °C (°F)	D1120	162.8 (325)	108.2 (227)	108 (226) Min
Freezing point, °C (°F)	D1177		-38.8 (-37.8)	-36.4 (-33.5) Max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 Max ¹
Ash content, mass %	D1119	1.91	0.91	5 Max ¹ / 2.5 Max ²
Chloride, ppm	D3634	12	<25	25 Max

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PEP0B3

1 Gallon Bottle 0-74804-06376-9
6/1 Gallon Case 0-74804-16376-6

PEP0B1
55 Gallon Drum
0-74804-07041-5



50/50 PREDILUTED

PEPB53

1 Gallon Bottle 0-74804-06377-6
6/1 Gallon Case 0-74804-16377-3

PEPB51
55 Gallon Drum
0-74804-07031-6

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PEP0B3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PEPB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PEP0B1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PEPB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Original Equipment Technology European PINK Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Original Equipment Technology European PINK Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com



To order, please call
Old World Industries Customer Service at
1-800-323-8755

Manufactured for Old World Industries, LLC, Northbrook, IL 60062 • (800) 289-7234
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2020 Old World Industries, LLC. All Rights Reserved.
PEAK and PEAK ORIGINAL EQUIPMENT TECHNOLOGY are trademarks of Old World Industries, LLC.
06-10-2020