



# 12V DRUM PUMP SYSTEM

Item Number: 23 761 546  
Material Number: 4006430  
Part Number: DEFDP12V

The 12V Drum Pump System provides everything you need to pump diesel exhaust fluid efficiently with a 12V power source.

- Drum Pump System includes 12V axial gear pump, discharge hose, expandable down tube, drum adapters and manual poly nozzle
- Can be manually operated in case of electrical power outage
- Consistent DEF delivery rate each time the manual lever is pumped
- Designed exclusively for use as a drum pump
- 1 Year Limited Liability Warranty\*

## TECHNICAL DATA

Connecting cable, with battery terminal clips and fuse holder, length (ft): 6.6

Drum adapters: S64x5 (American Male Buttress Thread) and G2" (Male BSPP Thread)

Connection suction side: G1" male

Connection discharge side: G1" male

### HYDRAULIC DATA:

Pump design:	axial gear
Delivery rate under free discharge up to (gpm):	9.2
Suction height up to (ft):	8
Discharge height max. (ft):	49
Pumping media:	DEF

### MOTOR DATA:

Voltage (VDC):	12
Power consumption (A):	14
Power (W):	180
Thermal protection:	self-resetting
Duty cycle:	continuous operation
Rotation speed at 0.5 bar counter pressure (rpm):	7500
Type of construction:	IMB 5 (flange mount, no feet)
Protection class:	IP34
Material of pump housing and pump:	PA6 (polyamide 6/nylon 6)
Material motor shaft:	stainless steel 1.402
Dimensions of pump L x W x H (inch):	3.5 x 4.7 x 11.8
Weight with accessories (lb):	9.5

## SPECIAL NOTES

In the case of crystal formation, clean the pump with warm water until all crystals are dissolved.

**IMPORTANT: Priming with hand lever is required before first use and when changing drums.**



## DEFDP12V (MANUAL POLY NOZZLE)

UPC: 0-74804-06471-1  
SCC 14 Bar Code: 1-00-74804-06471-8

## PACKAGING

Packaging:	Carton
Dimensions L x W x H (inch):	15.7 x 15.7 x 8.7
Weight including package (lb):	11.4
Packaging unit:	One per package

## SPECIFICATION

- Axial gear pump with manual lever assembly
- Illuminated on/off switch
- Motor with thermal protection switch, self-resetting
- 6.6 ft cable with battery terminal clips and fuse holder
- DEF discharge hose with 90° female with swivel joint
- Preassembled 13.1 ft. discharge hose with G1" swivel fittings and manual poly nozzle
- Expandable down tube with suction strainer valve
- Drum adapters: (1) S64x5 and (1) G2"

\* See PEAKGuarantee.com for more details

©2025 Old World Industries, LLC. All Rights Reserved. PEAK, PEAK & Mountain Graphic, BlueDEF and BlueDEF & Drop Graphic are trademarks of Old World Industries, LLC.

