



DESCRIPTION

PEAK® DEX-COOL® ANTIFREEZE + COOLANT is a GM-approved premium coolant that can be used in all GM vehicles 1995 and newer. It provides engine protection 10 Years / 150,000 Mile Guaranteed Protection*.

PEAK® DEX-COOL® ANTIFREEZE + COOLANT is a factory-approved technology that contains a well-balanced mix of Organic Acid Technology (OAT) and corrosion inhibitors for complete protection.

FEATURES & BENEFITS

- Designed for use in all GM vehicles 1995 and newer requiring an orange organic acid technology (OAT) coolant
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306, D4985 and GMW3420, GM6277M
- Service life of up to 10 years / 150,000 miles with a complete cooling system flush and fill
- Color coding and application information on the front make it easy to select the correct antifreeze/coolant

Use **PEAK® DEX-COOL® ANTIFREEZE + COOLANT** when topping off your system or when performing a complete flush and fill.

**If properly maintained. See warranty details at PEAKAUTO.com*

FREEZE/BOIL PROTECTION CHART

PROTECTION ^Δ Using a 15 psi (103 kPa) pressure cap		
Coolant/Water Ratio	PROTECTS FROM	
	Freezing Down to	Boiling Up to ^Δ
50/50	-34°F (-37°C)	265°F (129°C)

^ΔUsing a 15 psi (103 kPa) pressure cap

50/50 Prediluted: For optimum performance and corrosion protection, coolant concentration should be maintained at 50% by volume.

Concentrate: For optimum performance coolant concentration should be maintained between 40-60% by volume.

Available in both 50/50 Prediluted and Concentrate

APPLICATIONS

PEAK® DEX-COOL® ANTIFREEZE + COOLANT is engineered for use in all GM vehicles 1995 and newer requiring an orange organic acid technology (OAT) antifreeze coolant:

- Buick
- Cadillac
- Chevy
- GMC
- Oldsmobile
- Pontiac
- Saturn

Properties	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Orange	Orange	Distinctive
pH, 50 vol %	D1287	8.3	8.3	7.5-11.0
Specific gravity	D1122	1.113	1.077	1.110-1.145 ¹ /1.065 min ²
Boiling point ³ , °F (°C)	D1120	325 (162.8)	229 (109)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-37.8 (-38.8)	-34 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PDX0B3

1 Gallon Bottle

0-74804-07843-5

6/1 Gallon Case

0-74804-17843-2



50/50 PREDILUTED

PDXB53

1 Gallon Bottle

0-74804-07844-2

6/1 Gallon Case

0-74804-17844-9

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PDX0B3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,217
PDXB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK® DEX-COOL® ANTIFREEZE + COOLANT can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Disposal Guidance: PEAK® DEX-COOL® ANTIFREEZE + COOLANT contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestion of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

To order, please call Old World Industries Customer Service
at 1-800-323-5440

For Technical Product Support, please call
1-800-477-5847