

SUPERIOR LIFETIME PROTECTION*

PEAK

ANTIFREEZE+COOLANT

**GUARANTEED PROTECTION
10+ YEARS / 300,000+ MILES***

DESCRIPTION

PEAK® Antifreeze + Coolant is specially engineered to deliver guaranteed superior lifetime protection**. Its advanced universal formula contains a proprietary blend of 10X the scale-fighting inhibitors† coupled with robust organic additives to fight against the damaging effects of scale deposits and corrosion. PEAK Antifreeze + Coolant is free of 2-EHA, silicate, nitrite, borate and amines, ensuring maximum cooling system performance for 10+ years/300,000+ miles*. It is compatible for use with any color or type of antifreeze/coolant in the system.

FEATURES & BENEFITS

- Specially formulated to deliver Superior Lifetime Protection** against damaging scale and corrosion
- Contains 10X the scale-fighting inhibitors† to ensure maximum cooling system performance
- Provides more than 2X the warranty coverage for 10+ years/300,000+ miles of service**
- Universal formula is compatible with any color or type of antifreeze/coolant
- Meets the performance requirements of ASTM D3306 and D4985

APPLICATIONS

PEAK® Antifreeze + Coolant is designed for use in all North American, Asian and European passenger cars, SUVs, motorcycles and light/medium duty trucks, regardless of make, model or year.

Best performance is achieved when a complete flush & fill is performed using PEAK Antifreeze + Coolant.

*Lifetime Protection: 10+ years/300,000+ miles lifetime guarantee when a complete cooling system flush and fill is performed and proper cooling system maintenance is followed. Always follow vehicle owner's manual for top off requirements, change intervals and specified maintenance. See peakauto.com for more details.

† Versus legacy PEAK Antifreeze + Coolant technologies.

**10x
MORE
SCALE-FIGHTING
INHIBITORS†**



Old World
Industries, LLC



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
50/50	-34° F (-36° C)	265° F (129° C)
60/40	-62° F (-52° C)	270° F (132° C)

*Using a 15 psig (103 kPa) pressure cap in good condition



**Available in both 50/50 Prediluted
and Full Strength Concentrate**

SUPERIOR LIFETIME PROTECTION™

PEAK®

ANTIFREEZE+COOLANT

10x MORE
SCALE-FIGHTING INHIBITORS¹

PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Yellow	Yellow	Distinctive
Specific gravity	ASTM D1122	1.113	1.077	1.110-1.145 ¹ /1.065 min ²
Boiling point ³ , °F (°C), 50 vol %	ASTM D1120	325 (162.8)	229 (109)	226 (108) min.
pH, 50 vol %	ASTM D1287	8.3 ²	8.3	7.5-11.0
Effect on Automotive Finish	ASTM D1882	No Effect	No Effect	No Effect
Total water, mass %	ASTM D1123	<5	50	5 max ¹
Ash content, mass %	ASTM D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	ASTM D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



FULL STRENGTH

PKPOB3
1 Gallon Bottle
0-74804-07187-0

PKPOB3
6/1 Gallon Case
1-00-74804-07187-7

PKPOB1
55 Gallon Drum
0-74804-07201-3

PKPOB8
275 Gallon Tote
0-74804-07203-7



50/50 PREDILUTED

PKPB53
1 Gallon Bottle
0-74804-07188-7

PKPB53
6/1 Gallon Case
1-00-74804-07188-4

PKPB51
55 Gallon Drum
0-74804-07200-6

PKPB58
275 Gallon Tote
0-74804-07202-0

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PKPOB3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,217
PKPB53	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	58	36	20	2,145
PKPOB1	Drum	55 gal	23.5" dia. x 34.5"	525	4	20	2,157
PKPB51	Drum	55 gal	23.5" dia. x 34.5"	553	4	20	2,269
PKPOB8	Tote	275 gal	40" x 40" x 46"	2,679	1	14	2,679
PKPB58	Tote	275 gal	40" x 40" x 46"	2,503	1	14	2,503

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

To order, please call
Old World Industries Customer Service at
1-800-323-8755



© 2019 Old World Industries, LLC. All Rights Reserved.
PEAK and PEAK 6 Mountain Graphic are trademarks of Old World Industries, LLC.
12-05-19 ARF24529