

The 120V Drum Pump System provides everything you need to pump diesel exhaust fluid efficiently.

- Drum Pump System includes 120V axial gear pump, discharge hose, suction hose, drum adapter coupling and poly manual nozzle
- Can be manually operated in case of electrical power outage
- Designed exclusively for use as a drum pump
- 1 Year Limited Liability Warranty

TECHNICAL DATA

Connecting cable, length (ft):	6.6
Connection container:	G 2" male, drum adapter 64x5
Connection suction side:	hose fitting DN 19
Connection discharge side:	G 1" male
HYDRAULIC DATA:	
Pump design:	axial gear
Delivery rate under free discharge up to (gpm):	13.7
Suction height up to (ft):	6.6
Flow media:	DEF
MOTOR DATA:	
Voltage (V):	120
Frequency (Hz):	60
Power consumption (A):	1.8
Power (W):	320
Thermal protection:	self-resetting
Duty cycle:	continuous operation
Rotation speed at 0.5 bar counter pressure (rpm):	7500
Type of construction:	IMB 5
Protection class:	IP 34
Material of pump housing and pump:	PA 6
Material motor shaft:	stainless steel 1.4021
Dimensions of pump (inch):	3.5 x 4.7 x 11.8
Weight of motor and pump (lb):	3.5



DEFDP120

UPC: 0-74804-06469-8

SCC 14 Bar Code: 1-00-74804-06469-5

PACKAGING

Packaging:	white carton
Dimensions LxWxH (inch):	15.7 x 15.7 x 8.7
Weight including package (lb):	11
Packaging unit:	1.0

SPECIFICATION

- Axial wheel pump with manual pump assembly
- Illuminated on/off switch
- Motor with thermal protection switch, self-resetting
- US plug, 6.6 ft cable
- Drum adapter coupling
- DEF discharge hose with 90° female with swivel joint
- Poly nozzle w/ 13 Ft DEF hose
- DEF suction hose, 5.25 ft, with foot valve
- Drum adapter coupling, for plastic container, connecting thread G 2"

