

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 04/02/2018

<b>SECTION 1: Identific</b>	ation of th <u>e sub</u>	stance/mixture and of the company/undertaking
1.1. Product identifie		
Product form		: Mixture
Product name		: PEAK Original Equipment Technology North American Vehicles Extended Life ORANGE Concentrate Antifreeze and Coolant
		tance or mixture and uses advised against
Use of the substance/mixtur	re	: Antifreeze & Coolant
	pplier of the safety of	lata sheet
Old World Industries, LLC 3100 Sanders Road Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com	A	
1.4. Emergency telep	ohone number	
Emergency number		: 800 424 9300; 00 1 703 527 3887 (International) Chemtrec
<b>SECTION 2: Hazards</b>	identification	
2.1. Classification of	the substance or m	ixture
GHS-US classification		
Acute toxicity (oral),	H302	Harmful if swallowed
Category 4 Reproductive toxicity,	H361	Suspected of damaging fertility or the unborn child
Category 2 Specific target organ toxicity — Repeated exposure, Category 2 Full text of H statements : si	H373 ee section 16	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)
2.2. Label elements		
GHS-US labelling		
Hazard pictograms (GHS-U	S)	HS07 GHS08
Signal word (GHS-US)		: Warning
Hazard statements (GHS-U	S)	<ul> <li>H302 - Harmful if swallowed</li> <li>H361 - Suspected of damaging fertility or the unborn child</li> <li>H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)</li> </ul>
Precautionary statements (GHS-US)		<ul> <li>P201 - Obtain special instructions before use</li> <li>P202 - Do not handle until all safety precautions have been read and understood</li> <li>P260 - Do not breathe mist, spray, vapors</li> <li>P264 - Wash affected areas thoroughly after handling</li> <li>P270 - Do not eat, drink or smoke when using this product</li> <li>P280 - Wear personal protective equipment as required</li> <li>P301+P310 - If swallowed: Immediately call doctor/physician or poison center</li> <li>P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting</li> <li>P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing</li> <li>P308+P313 - If exposed or concerned: Get medical advice/attention</li> <li>P405 - Store locked up</li> <li>P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations</li> </ul>

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

### No additional information available

2.4. Unknown acute toxicity (GHS US)

#### No data available

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
ethylene glycol	(CAS-No.) 107-21-1	90 - 97	Acute Tox. 4 (Oral), H302
diethylene glycol	(CAS-No.) 111-46-6	0.5 - 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
water	(CAS-No.) 7732-18-5	1 - 5	Not classified
potassium 2-ethylhexanoate	(CAS-No.) 3164-85-0	1 - 5	Repr. 2, H361
denatonium benzoate	(CAS-No.) 3734-33-6	30 - 50 ppm	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

OFOTION 4. First sid massing	
SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Remove contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Rinse immediately with plenty of water (for at least 15 minutes), Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	: Obtain emergency medical attention. Rinse mouth. If the person is fully conscious, make him/her drink two glasses of water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whiskey. For children, give proportionally less liquor, according to weight.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/effects	: Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).

#### 4.3. Indication of any immediate medical attention and special treatment needed

A more effective intravenous antidote for physician uses is 4-methylpyrazaole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occured.

SECTION 5: Fire-fighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Carbon dioxide. dry chemical. Foam. Sand. Water fog.	
Unsuitable extinguishing media	: Do not use a heavy water stream. May spread fire.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2.	Special hazards arising from the substance or mixture	
Fire haza	rd	: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.
Reactivity	/	: No dangerous reactions known under normal conditions of use.
5.3.	Special protective equipment and pre	cautions for fire-fighters
Firefightir	ng instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting		: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTI	ON 6: Accidental release meas	sures
6.1.	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For non-emergency personnel	
Emergen	cy procedures	: Evacuate unnecessary personnel.
6.1.2.	For emergency responders	
Protectiv	e equipment	: Equip cleanup crew with proper protection. Use personal protective equipment as required.
Emergen	icy procedures	: Ventilate area.
6.2.	Environmental precautions	
Prevent	entry to sewers and public waters. Notify	authorities if liquid enters sewers or public waters.
6.3.	Methods and material for containme	nt and cleaning up
Methods	for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Store away from other materials.
6.4.	Reference to other sections	

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.	
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.	
7.2. Conditions for safe storage, includir	ng any incompatibilities	
Storage conditions	<ul> <li>Keep only in the original container in a cool, well ventilated place away from : Heat sources.</li> <li>Keep container closed when not in use. Product may become solid at temperatures below -18</li> <li>°C (0 °F). Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.</li> </ul>	
Incompatible products	: Keep away from strong acids, strong bases and oxidizing agents.	
Incompatible materials	: Sources of ignition.	
7.3. Specific end use(s)		

No additional information available

SECTION 8: Exposure controls/personal protection			
8.1. Control parameters			
denatonium benzoate (3734-33-6)			
Not applicable			
ethylene glycol (107-21-1)			
ACGIH	Local name	Ethylene glycol	
ACGIH	ACGIH TWA (mg/m³)	10 mg/m <sup>3</sup>	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)		
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	100 mg/m³ (Ethylene glycol; USA; Momentary value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Upper respiratory tract & eye irritant
diethylene glycol (111-46-6)		
Not applicable		
water (7732-18-5)		
Not applicable		
potassium 2-ethylhexanoate (3164-85-0)		
Not applicable		

#### 8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

#### Hand protection:

Wear protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Respiratory protection:

Respiratory protection not required in normal conditions. If exposed to levels above exposure limits wear appropriate respiratory protection.



#### Other information:

Do not eat, drink or smoke during use.

<b>SECTION 9: Physical and chemical</b>	properties	
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Color	: orange	
Odor	: Mild	
Odor threshold	: No data available	
pH 50% water solution	: 8	
Relative evaporation rate (butylacetate=1)	: Nil	
Freezing point	: -18 °C (0 °F)	
Boiling point	: 158 °C (317 °F)	
Flash point	: 116 °C (241 °F) [100% Ethylene Glycol] ASTM D56	
Auto-ignition temperature	: 400 °C (752 °F) [100% Ethylene Glycol] Literature	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: < 0.1 @ 20 ℃	
Relative vapor density at 20 °C	: No data available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific Gravity	: 1.12
Density	: 1.12 kg/l (9.34 lbs/gal)
Solubility	: Water: Complete
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Explosive limits	: 3.2 - 15.3 vol %
9.2. Other information	
VOC content	: 0%
VOC content	. 0 %
<b>SECTION 10: Stability and reactivity</b>	
10.1. Reactivity	
No dangerous reactions known under normal con	nditions of use.
10.2. Chemical stability	
Stable.	
10.3. Possibility of hazardous reactions	
No dangerous reactions known under normal con	nditions of use.
10.4. Conditions to avoid	
Extremely high or low temperatures. Keep away	from any flames or sparking source.
10.5. Incompatible materials	
Keep away from strong acids, strong bases and	
10.6. Hazardous decomposition products	
Alcohols. Aldehydes. Carbon dioxide. Carbon mo	DNOXIDE. Ethers. Fume.
SECTION 11: Toxicological informat	ion
11.1. Information on toxicological effects	
Acute toxicity	: Oral: Harmful if swallowed.
denatonium benzoate (3734-33-6)	EQ4 mailes (Date Literature at etc.)
LD50 oral rat	584 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Literature study)
ATE US (oral)	584 mg/kg bodyweight
ethylene glycol (107-21-1)	
LD50 oral rat	> 5000 mg/kg (Rat; Literature study)
ATE US (oral)	500 mg/kg bodyweight
diethylene glycol (111-46-6)	
LD50 dermal rabbit	11890 mg/kg (Rabbit)
ATE US (oral)	500 mg/kg bodyweight
ATE US (dermal)	11890 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
ea.eegomony	
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: No additional information available.
denatonium benzoate (3734-33-6)	
LC50 fish 1	> 1,000.00 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	13.00 mg/l (EC50; 48 h; Daphnia magna)
ethylene glycol (107-21-1)	
EC50 Daphnia 1	> 10,000.00 mg/l (EC50; 24 h)
LC50 fish 2	40,761.00 mg/l (LC50; 96 h; Salmo gairdneri)
diethylene glycol (111-46-6)	
LC50 fish 1	> 5,000.00 ppm (LC50; 24 h)
EC50 Daphnia 1	> 10,000.00 mg/l (EC50; 24 h)

#### 12.2. Persistence and degradability

denatonium benzoate (3734-33-6)			
Persistence and degradability	Biodegradability in water: no data available. No (test) data on mobility of the substance available.		
ethylene glycol (107-21-1)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.		
Biochemical oxygen demand (BOD)	0.47 g O <sub>2</sub> /g substance		
Chemical oxygen demand (COD)	1.24 g O <sub>2</sub> /g substance		
ThOD	1.29 g O <sub>2</sub> /g substance		
BOD (% of ThOD)	0.36		
diethylene glycol (111-46-6)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. Photolysis in the air.		
Biochemical oxygen demand (BOD)	0.02 g O <sub>2</sub> /g substance		
Chemical oxygen demand (COD)	1.51 g O <sub>2</sub> /g substance		
ThOD	1.51 g O <sub>2</sub> /g substance		
BOD (% of ThOD)	0.02		

### 12.3. Bioaccumulative potential

denatonium benzoate (3734-33-6)		
Log Pow	1.78 (Estimated value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
ethylene glycol (107-21-1)		
BCF fish 1	10.00 (BCF; 72 h)	
BCF other aquatic organisms 1	0.21 - 0.6 (BCF)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)	
BCF other aquatic organisms 2	190.00 (BCF; 24 h)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
diethylene glycol (111-46-6)	
BCF fish 1	100.00 (BCF; Other; 3 days; Leuciscus melanotus; Static system; Fresh water; Experimental value)
Log Pow	-1.98 (Calculated; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

ethylene glycol (107-21-1)			
Surface tension	0.05 N/m (20 °C)		
diethylene glycol (111-46-6)			
Surface tension	0.05 N/m		
Log Koc	Koc,SRC PCKOCWIN v1.66; 1; Calculated value; log Koc; SRC PCKOCWIN v1.66; 0; Calculated value		
12.5. Other adverse effects			
12.5. Other adverse effects			
Effect on the ozone layer	: No known effect on the ozone layer		
Other information	: Avoid release to the environment.		

SECTION 13: Disposal consideration	15
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials	: Avoid release to the environment.

## **SECTION 14: Transport information**

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : No limit

### **Department of Transportation (DOT)**

In accordance with DOT

Non Bulk (in quantities under 5,000 lbs in any one inner package): Not regulated by the US DOT

#### Bulk (in quantities 5,000 lbs or over in any one inner package):

	1 0,
Transport document description	: UN3082 Environmentally hazardous substances, liquid, n.o.s., 9, III
UN-No.(DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s.
Class (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: G - Identifies PSN requiring a technical name

(49 CFR 173.27)

: 155

## Safety Data Sheet

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
Fransportation of Dangerous Goods	
Refer to current TDG Canada for further Canad	dian regulations
Fransport by sea	
n accordance with IMDG / IMO	
Proper Shipping Name (IMDG)	: Not regulated by IMDG (in quantites under 5,000 lbs in any one inner package)
Air transport	
n accordance with IATA / ICAO	
Proper Shipping Name (IATA)	: Not regulated by IATA (in quantites under 5,000 lbs in any one inner package)
SECTION 15: Regulatory information	
5.1. US Federal regulations	
	American Vehicles Extended Life ORANGE Concentrate Antifreeze and Coolant
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
denatonium benzoate (3734-33-6)	
Listed on the United States TSCA (Toxic Substa	ances Control Act) inventory
ethylene glycol (107-21-1)	
Listed on the United States TCCA (Taula Culture	
Listed on the United States TSCA (Toxic Substa Subject to reporting requirements of United Stat	
Subject to reporting requirements of United Stat	tes SARA Section 313 T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 5000 lb(s)
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ	tes SARA Section 313 T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 5000 lb(s) Immediate (acute) health hazard
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ SARA Section 311/312 Hazard Classes	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard         Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ SARA Section 311/312 Hazard Classes SARA Section 313 - Emission Reporting	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard         Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.         Ethylene glycol is subject to Form R Reporting requirements.
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ SARA Section 311/312 Hazard Classes SARA Section 313 - Emission Reporting diethylene glycol (111-46-6)	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard         Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.         Ethylene glycol is subject to Form R Reporting requirements.
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ SARA Section 311/312 Hazard Classes SARA Section 313 - Emission Reporting diethylene glycol (111-46-6) Listed on the United States TSCA (Toxic Substates	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard         Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.         Ethylene glycol is subject to Form R Reporting requirements.
Subject to reporting requirements of United Stat EPA TSCA Regulatory Flag CERCLA RQ SARA Section 311/312 Hazard Classes SARA Section 313 - Emission Reporting diethylene glycol (111-46-6) Listed on the United States TSCA (Toxic Substates water (7732-18-5)	tes SARA Section 313         T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.         5000 lb(s)         Immediate (acute) health hazard         Delayed (chronic) health hazard         Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.         Ethylene glycol is subject to Form R Reporting requirements.

### 15.2. International regulations

### CANADA

PEAK Original Equipment Technology North American Vehicles Extended Life ORANGE Concentrate Antifreeze and Coolant	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

### **EU-Regulations**

No additional information available

### **National regulations**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### PEAK Original Equipment Technology North American Vehicles Extended Life ORANGE Concentrate Antifreeze and Coolant

DSL (Canada): The intentional ingredients of this product are listed

ECL (South Korea): The intentional ingredients of this product are listed.

EINECS (Europe): The intentional ingredients of this product are listed

ENCS (Japan): The intentional ingredients of this product are listed

#### 15.3. US State regulations

**WARNING** This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ethylene glycol	(107-21-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

### ethylene glycol (107-21-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### diethylene glycol (111-46-6)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

#### **SECTION 16: Other information**

Revision date

: 04/02/2018

Full text of H-statements:

H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
	exposure

#### NFPA health hazard

NFPA fire hazard

NFPA reactivity

- : 1 Materials that, under emergency conditions, can cause significant irritation.
- : 1 Materials that must be preheated before ignition can occur.
- : 0 Material that in themselves are normally stable, even under fire conditions.



Hazard Rating	
Health	2 Moderate Hazard - Temporary or minor injury may occur
Flammability	1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 °F (93 °C). (Class IIIB)
Physical :	0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	B - Safety glasses, Gloves
SDS GHS US (GHS HazCom 2012) OWI	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.