

**PEAK**  
**ORIGINAL**  
**EQUIPMENT**  
**TECHNOLOGY<sup>®</sup>**

**ASIAN VEHICLES**

**EXTENDED LIFE BLUE**  
**ANTIFREEZE + COOLANT**

**DESCRIPTION**

**PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT** for **ASIAN VEHICLES** is a line of premium coolants specifically designed to match the technology and color requirements of **Asian** vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

**PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT** for **ASIAN VEHICLES - BLUE** is an ethylene glycol-based antifreeze/coolant specifically developed for use in any Asian vehicle requiring a Blue phosphate-enhanced organic acid technology (POAT) formulation. It contains high-quality organic acid corrosion inhibitors and is free of borate, nitrite, silicate and amines chemicals.

**PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT** for **ASIAN VEHICLES - BLUE** meets the performance requirements of ASTM D3306 and JIS K2234. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 150,000 miles or 5 years.

**FEATURES & BENEFITS**

- Matches each Asian vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and JIS K2234
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

Use **PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT concentrate** to perform a complete flush/fill or top-off.

Use **PEAK ORIGINAL EQUIPMENT TECHNOLOGY 50/50 PREDILUTED ANTIFREEZE + COOLANT** when just topping off your system.

**A PERFECT MATCH**  
**FOR EVERY VEHICLE**



**FREEZE/BOIL PROTECTION CHART**

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

\*Using a 15 psig (103 kPa) pressure cap in good condition



*Available in both 50/50 Prediluted and Concentrate*



# ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT

## APPLICATIONS

**PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for ASIAN VEHICLES - BLUE** is specifically engineered for use in all Asian vehicles requiring a BLUE PHOSPHATE-ENHANCED OAT extended life antifreeze/coolant:

- Acura: 1990 and up
- Honda: 1990 and up
- Infiniti: 2009 and up
- Mitsubishi: Mirage and Outlander 2001 and up, Raider 2006 and up, Lancer 2012 and up
- Nissan: 2009 and up
- Subaru: 2009 and up
- Suzuki: 2010 and up

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance	Visual	Blue	Blue	Distinctive
pH, (50% vol)	D1287	7.7	7.7	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 <sup>1</sup> / 1.065 min <sup>2</sup>
Boiling point <sup>3</sup> , °C (°F)	D1120	162.8 (325)	109.5 (229.1)	108 (226) Min
Freezing point, °C (°F)	D1177		-37.9 (-36.2)	-36.4 (-33.5) Max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 Max <sup>1</sup>
Ash content, mass %	D1119	1.62	0.82	5 Max <sup>1</sup> / 2.5 Max <sup>2</sup>
Chloride, ppm	D3634	<25	<25	25 Max

<sup>1</sup>For concentrate product only, <sup>2</sup>Prediluted (50/50) only, <sup>3</sup>Unpressurized

## SHIPPING INFORMATION



### CONCENTRATE

**PAB0B3**

**1 Gallon Bottle**  
0-74804-06372-1

**6/1 Gallon Case**  
0-74804-16372-8

**PAB0B1**  
**55 Gallon Drum**  
0-74804-07038-5



### 50/50 PREDILUTED

**PABB53**

**1 Gallon Bottle**  
0-74804-06373-8

**6/1 Gallon Case**  
0-74804-16373-5

**PABB51**  
**55 Gallon Drum**  
0-74804-07028-6

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PAB0B3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PABB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PAB0B1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PABB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

\*\*Includes pallet weight of 50 lbs each

## ADDITIONAL INFORMATION

**Testing Requirements:** For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

**Storage Recommendations:** PEAK Original Equipment Technology Asian BLUE Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

**Safety and Environmental Guidance:** PEAK Original Equipment Technology Asian BLUE Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from [peakauto.com](http://peakauto.com). Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.  
Northbrook, IL 60062 • 800-323-5440

[Peakauto.com](http://Peakauto.com)

Manufactured for Old World Industries, LLC, Northbrook, IL 60062 • (800) 289-7234

MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT

©2020 Old World Industries, LLC. All Rights Reserved.

PEAK and PEAK ORIGINAL EQUIPMENT TECHNOLOGY are trademarks of Old World Industries, LLC.

06-10-2020



To order, please call  
Old World Industries Customer Service at  
**1-800-323-8755**