

The In-line Digital Flow Meter features an easy to read four-digit digital display enclosed in a stainless-steel meter housing allowing, this quality meter to offer precision quantity and measurements.

- Pre-calibrated for DEF
- ISO 22241 compatible
- Durable stainless-steel construction
- Large visible screen
- Rotating screen
- "G" style fittings to leak proof connection
- Easily converts between gallons and liters



## TECHNICAL DATA

Distance in-/out flange (mm):	110
Connection on both ends:	G 1" female
Media:	DEF
Flow capacity min. (l/min):	15
Flow capacity max. (l/min):	100
Permitted liquid temperature max. (°C):	40
Permitted ambient temperature (°C):	-10 / +50
Measuring tolerance (%):	1
Nominal pressure (bar):	15
Burst pressure (bar):	60
Lifetime of battery:	approx. 2 years at 0.5 hours per day (20 °C)

## MATERIALS OF PARTS IN CONTACT WITH LIQUID:

Meter housing:	stainless steel
Turbine:	POM
Seals:	NBR 70
<b>Dimensions LxWxH (inch):</b>	4.33 x 3.35 x 2.17
<b>Weight (lb):</b>	2.12

## PACKAGING

<b>Packaging:</b>	white carton
<b>Dimensions LxWxH (inch):</b>	5.71 x 4.96 x 3.07
<b>Weight including package (lb):</b>	2.31
<b>Packaging unit:</b>	1.0

## DEFMTR

UPC: 0-74804-06474-2

SCC 14 Bar Code: 1-00-74804-06474-9

## SPECIFICATION

- Pre-calibrated for DEF
- ISO 22241 compatible
- Durable stainless-steel construction
- Large visible screen
- Rotating screen
- "G" style fittings to leak proof connection
- Easily converts between gallons and liters
- The display can be adapted to the direction of flow in 90° steps

