

PREMIUM EXTENDED LIFE TECHNOLOGY



ANTIFREEZE + COOLANT

GLOBAL LIFETIME™

FOR USE IN ALL VEHICLES
LIFETIME PROTECTION*

DESCRIPTION

PEAK® Global Lifetime™ Antifreeze + Coolant features an advanced organic acid technology that provides guaranteed lifetime protection for as long as you own your vehicle!* Its specially-engineered formula will provide maximum protection against damaging rust and corrosion in all automobiles, and light/medium and heavy duty trucks worldwide, regardless of make, model, year or original antifreeze color.

FEATURES & BENEFITS

- Provides guaranteed lifetime protection for as long as you own your vehicle when a complete cooling system flush and fill is performed and specified maintenance followed†
- Formulated for use in all American, Asian, and European vehicles
- Features a proprietary non 2-EH formula that is borate, nitrite, amine and silicate-free
- Amber color will not change the current antifreeze color when used for topping off

APPLICATIONS

Engineered for use in all passenger cars, SUVs, motorcycles, and light/medium and heavy duty trucks, regardless of make, model, year or antifreeze/coolant in the system.

*See warranty details at PEAKGuarantee.com



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTS FROM	
	Freezing Down to	Boiling Up to ^Δ
40/60	-13°F [-25°C]	260°F [127°C]
50/50	-34°F [-37°C]	265°F [129°C]
60/40	-62°F [-52°C]	270°F [132°C]

Provides corrosion protection when diluted by volume to a minimum of 33% coolant concentration.

50/50 Prediluted: For optimum performance coolant concentration should be maintained at 50% by volume.

Concentrate: For optimum performance coolant concentration should be maintained between 40-60% by volume.



Available in both 50/50 Prediluted
and Concentrate

PREMIUM EXTENDED LIFE TECHNOLOGY



ANTIFREEZE + COOLANT

PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Amber	Amber	Distinctive
pH, 50 vol %	D1287	8.0-9.1	8.0-9.1	7.5-11.0
Specific gravity	D1122	1.1130	1.077	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °F (°C)	D1120	325 (162.8)	229 (109)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-34 (-36.6)	-34 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PXA0B3

1 Gallon Bottle

0-74804-00407-6

6/1 Gallon Case

1-00-74804-00407-3

PXA0B1

55 Gallon Drum

0-74804-03397-7



50/50 PREDILUTED

PXAB53

1 Gallon Bottle

0-74804-00243-0

6/1 Gallon Case

1-00-74804-00243-7

PXAB51

55 Gallon Drum

0-74804-03351-9

PXABR8

275 Gallon Tote

0-74804-05845-1

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	
PXA0B3	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,082
PXAB53	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	54	36	20	
PXA0B1	Drum	55 Gal	23.5" dia. x 34.5" H	495	4	20	2,277
PXAB51	Drum	55 Gal	23.5" dia. x 34.5" H	520	4	20	
PXABR8	Tote	275 Gal	40" L x 40" W x 46" H	2,503	1	14	

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK® Global Lifetime™ Antifreeze + Coolant can be stored in original container at ambient temperature and limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK® Global Lifetime™ Antifreeze + Coolant is based on virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

To order, please call
Old World Industries Customer Service at
1-800-323-8755

Manufactured for Old World Industries, Northbrook, IL 60062 • (800) 289-7234
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2023 Old World Industries. All Rights Reserved.
PEAK, PEAK G Mountain Graphic and GLOBAL LIFETIME are trademarks of Old World Industries

