

PEAK
ORIGINAL
EQUIPMENT
TECHNOLOGY

EUROPEAN VEHICLES

GREEN
ANTIFREEZE + COOLANT

DESCRIPTION

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES** is a line of premium coolants specifically designed to match the technology and color requirements of **European** vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - GREEN** is an ethylene glycol-based antifreeze/coolant specifically developed for use in any European vehicle requiring a blue silicate-enhanced hybrid organic acid technology (Si-HOAT) formula. It contains high-quality organic and inorganic corrosion inhibitors and is free of nitrite, phosphate and amines chemicals.

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - GREEN** meets the performance requirements of ASTM D3306 and BS 6580. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 150,000 miles or 5 years*.

FEATURES & BENEFITS

- Matches each European vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and BS 6580
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

Use **PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT concentrate** to perform a complete flush/fill or top-off.

Use **PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ 50/50 PREDILUTED ANTIFREEZE + COOLANT** when just topping off your system.

* If properly maintained. See warranty details at PEAKAUTO.com

A PERFECT MATCH FOR EVERY VEHICLE



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
40/60	-13°F (-25°C)	260°F (127°C)
50/50	-34°F (-37°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)

*Using a 15 psig (103 kPa) pressure cap in good condition.

50/50 Prediluted: For optimum performance and corrosion protection, coolant concentration should be maintained at 50% by volume.

Concentrate: For optimum performance coolant concentration should be maintained between 40-60% by volume.



**Available in both 50/50 Prediluted
and Concentrate**



ORIGINAL EQUIPMENT TECHNOLOGY™

ANTIFREEZE + COOLANT

APPLICATIONS

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - GREEN** is specifically engineered for use in all European vehicles requiring a GREEN SILICATE-ENHANCED HYBRID ORGANIC ACID TECHNOLOGY extended life antifreeze + coolant:

• BMW & MINI: 2018- Current

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance	Visual	Green	Green	Distinctive
pH	D1287	8.8 (50% vol)	8.8	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ / 1.065 Min ²
Boiling point ³ , °C (°F)	D1120	162.8 (325)	108.2 (227)	108 (226) Min
Freezing point, °C (°F)	D1177	-	-38.8 (-37.8)	-36.4 (-33.5) Max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 Max ¹
Ash content, mass %	D1119	1.91	0.91	5 Max ¹ / 2.5 Max ²
Chloride, ppm	D3634	<25	<25	25 Max
Shelf Life, Years-Unopened original container	-	3	5	-

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PEGOB3

1 Gallon Bottle
0-74804-08837-3

6/1 Gallon Case
0-74804-18837-0

PEGOB1

55 Gallon Drum
0-74804-08839-7



50/50 PREDILUTED

PEGB53

1 Gallon Bottle
0-74804-08838-0

6/1 Gallon Case
0-74804-18838-7

PEGB51

55 Gallon Drum
0-74804-08840-3

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PEGOB3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PEGB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PEGOB1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PEGB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK® Original Equipment Technology™ European GREEN Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK® Original Equipment Technology™ European GREEN Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestion of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

**To order, please call Old World Industries Customer Service
at 1-800-323-5440**

**For Technical Product Support, please call
1-800-477-5847**



Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

Manufactured for Old World Industries, LLC Northbrook, IL 60062
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2025 Old World Industries, LLC. All Rights Reserved.
PEAK, PEAK & Mountain Graphic, PEAK Original Equipment Technology graphic and
Original Equipment Technology are trademarks of Old World Industries, LLC

05-21-25