

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Id	lentification of the substanc	e/mixture and of the company/undertaking
	identifier	
Product form	: Mix	ture
Product name	: Blue	e Mountain Windshield Wash -20 °F
1.2. Relevar	t identified uses of the substance of	or mixture and uses advised against
Use of the substar	ce/mixture : Wir	ndshield Wash Fluid
1.3. Details	of the supplier of the safety data sh	eet
Old World Industri 4065 Commercial Northbrook, IL 600 T (847) 559-2000 www.oldworldind.c	Ave. 62 - USA	
1.4. Emerge	ncy telephone number	
Emergency number		0) 424-9300; (703) 527 3887 (International) emtrec
SECTION 2: H	azards identification	
2.1. Classifi	cation of the substance or mixture	
GHS-US classific	ation	

GHS-US classification

Flam. Liq. 2	H225	
Acute Tox. 4 (Oral)	H302	
Acute Tox. 3 (Dermal)	H311	
Acute Tox. 4 (Inhalation:dust,mist)	H332	
STOT SE 1	H370	
Full text of H-phrases: see section 16		

2.2. Label elements				
GHS-US labelling				
Hazard pictograms (GHS-US)	: GHS02 GHS06 GHS08			
Signal word (GHS-US)	: Danger			
Hazard statements (GHS-US)	 H225 - Highly flammable liquid and vapor H302+H332 - Harmful if swallowed or if inhaled H311 - Toxic in contact with skin H370 - Causes damage to organs (May cause blindness if swallowed) 			
Precautionary statements (GHS-US)				

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P36 P37(P403 P403 P50	P314 - Get medical advice/attention if you feel unwell P361+P364 - Take off immediately all contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use Foam, Sand, Dry powder, Carbon dioxide to extinguish P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations		
2.3. Other hazards				
No additional information available				
2.4. Unknown acute toxicity (GHS US)				
No data available				
SECTION 3: Composition/information.	on on Ir	ngrealents		
Not applicable				
3.2. Mixture				
Name		Product identifier	% by wt	GHS-US classification
methanol		(CAS No) 67-56-1	< 33	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
SECTION 4: First aid measures				
I.1. Description of first aid measures				
First-aid measures general		er give anything by mouth to an unconscic ce (show the label where possible).	ous person. If yo	u feel unwell, seek medical
irst-aid measures after inhalation	brea	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical advice. Allow the victim to rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.		
First-aid measures after skin contact		Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Remove clothing before washing. Consult a doctor/medical service.		
First-aid measures after eye contact	plen	Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if irritation persists.		
First-aid measures after ingestion		: Obtain emergency medical attention. Rinse mouth. Never give anything by mouth to an unconscious person.		
I.2. Most important symptoms and effe	<mark>cts, bot</mark> h	acute and delayed		
Symptoms/injuries after inhalation		cause irritation of the nose and throat. His ous system depression characterized by h		
Symptoms/injuries after skin contact		onged exposure to skin may cause skin irr redness.	itation experien	ced as burning, dryness, cracking
Symptoms/injuries after eye contact		cause severe irritation.		
Symptoms/injuries after ingestion	blinc	cause nausea, abdominal pain, headache Iness. Severe poisoning can lead to coma	and death.	
Chronic symptoms	rash	CONTINUOUS/REPEATED EXPOSURE/ /inflammation. Headache. Feeling of weal- rbances. Sleeplessness. Gastrointestinal	ness. Disturbed	I tactile sensibility. Visual
I.3. Indication of any immediate medica	al attentio	on and special treatment needed		
This product contains methanol which can caus ormaldehyde. These metabolites can cause me symptoms, their onset may be delayed from 6 to	etabolic a	cidosis, visual disturbances and blindness		
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		powder. Foam. Dry powder. Carbon diox	ide. Sand.	
Insuitable extinguishing media	: Dor	ot use a heavy water stream.		
5.2. Special hazards arising from the su	Ibstance	or mixture		

Fire hazard	: Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or
	may be moved by ventilation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
5.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Special protective equipment for fire fighters	: Wear positive pressure self-contained breathing apparatus (SCBA). Protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves.

SECTION 6: Accidental release measures			
6.1. Personal precautions, pre	Personal precautions, protective equipment and emergency procedures		
General measures	: Remove ignition sources. Use special care to avoid static electric charges. Do not breathe vapor or mist. Wear appropriate respirator when ventilation is inadequate.		
6.1.1. For non-emergency perso	onnel		
Emergency procedures	: Evacuate unnecessary personnel. Keep upwind. Mark the danger area.		
6.1.2. For emergency responde	rs		
Protective equipment	: Equip cleanup crew with proper protection.		
Emergency procedures	: Ventilate area.		
6.2. Environmental precaution	ns		
Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters			

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3.	Methods and material for containment and cleaning up		
For con	tainment	: Contain released substance, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Dilute combustible/toxic gases/vapors with water spray.	
Method	s for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.	

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage				
7.1. Precautions for safe handling				
Additional hazards when processed	: In use, may form flammable vapor-air mixture.			
Precautions for safe handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.			
Hygiene measures	: Wash contaminated clothing before reuse.			
7.2. Conditions for safe storage, includi	ng any incompatibilities			
Technical measures	: Use explosion-proof electrical, lighting, ventilating equipment. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed.			
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources, hot surfaces, open flames, sparks. Keep container closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies.			
Incompatible products	: Keep away from strong acids, strong bases and oxidizing agents.			
Incompatible materials	: Sources of ignition.			
7.3. Specific end use(s)	7.3. Specific end use(s)			

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm (Skin)
ACGIH	ACGIH STEL (ppm)	250 ppm (Skin)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ (Skin)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)		
OSHA	OSHA PEL (TWA) (ppm)	200 ppm (Skin)
3.2. Exposure controls Personal protective equipment		exposure. Gloves. Safety glasses.
	. Avoid all difficeessary e	Aposule. Cloves. Salely glasses.
		D)
land protaction		
Hand protection Eye protection	: Wear protective gloves. : Chemical goggles or sa	
Skin and body protection	: Wear suitable protective	
Respiratory protection		entilation wear respiratory protection. Wear appropriate mask.
Other information	: Do not eat, drink or smo	
SECTION 9: Physical and		
	physical and chemical properties	
Physical state	: Liquid	
Color	: Blue	
Ddor Ddor threshold	: alcohol odor : No data available	
Relative evaporation rate (butyla		atato
Freezing point	: No data available	
Boiling point	: 80 - 83 °C (177 - 181 °F	.)
Flash point	: 33 °C (92 °F))
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
/apor pressure	: 43 mm Hg @ 20 °C	
Relative vapor density at 20 °C	: Heavier than air	
Specific Gravity	: 0.96 @ 20 °C	
Solubility	: Water: Complete	
.og Pow	No data available	
₋og Kow	: No data available	
/iscosity, kinematic	: No data available	
/iscosity, dynamic	: No data available	
Explosive properties	: No data available	
Dxidizing properties	: No data available	
Explosive limits	: 6 - 36 vol %	
0.2. Other information		
/OC content	: < 33.00 %	
SECTION 10: Stability an	nd reactivity	
0.1. Reactivity		
No additional information availab	le	
0.2. Chemical stability		
Stable.		
10.3. Possibility of hazardo	ous reactions	
Hazardous polymerization will no		
10.4. Conditions to avoid	-	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials				
Keep away from strong acids, strong bases and oxidizing agents.				
10.6. Hazardous decomposition products				
Fume. Carbon monoxide. Carbon dioxide.				
SECTION 11: Toxicological informati	011			
11.1. Information on toxicological effects				
Acute toxicity	: Oral: Harmful if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Harmful if inhaled.			
methanol (67-56-1)				
LD50 oral rat	> 5,000.00 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)			
LD50 dermal rabbit	15,800.00 mg/kg (Rabbit; Literature study)			
LC50 inhalation rat (mg/l)	85.00 mg/l/4h (Rat; Literature study)			
LC50 inhalation rat (ppm)	64,000.00 ppm/4h (Rat; Literature study)			
ATE US (dermal)	15,800.00 mg/kg bodyweight			
ATE US (gases)	700.00 ppmv/4h			
ATE US (vapors)	3.00 mg/l/4h			
ATE US (dust,mist)	0.50 mg/l/4h			
Skin corrosion/irritation	: Not classified			
Serious eye damage/irritation	: Not classified			
Respiratory or skin sensitisation	: Not classified			
Germ cell mutagenicity	: Not classified			
Carcinogenicity	: Not classified			
Reproductive toxicity	: Not classified			
Specific target organ toxicity (single exposure)	: Causes damage to organs (May cause blindness if swallowed) .			
Specific target organ toxicity (repeated exposure)	: Not classified			
Aspiration hazard	: Not classified			
Symptoms/injuries after inhalation	: May cause irritation of the nose and throat. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.			
Symptoms/injuries after skin contact	: Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.			
Symptoms/injuries after eye contact	: May cause severe irritation.			
Symptoms/injuries after ingestion	: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.			
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Skin rash/inflammation. Headache. Feeling of weakness. Disturbed tactile sensibility. Visual disturbances. Sleeplessness. Gastrointestinal complaints. Cardiac and blood circulation effects.			

SECTION 12: Ecological information

12.1. Toxicity

methanol (67-56-1)			
LC50 fish 1	15,400.00 mg/l (96 h; Lepomis macrochirus; Lethal)		
EC50 Daphnia 1	> 10,000.00 mg/l (48 h; Daphnia magna; Lethal)		
LC50 fish 2	10,800.00 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 2	24,500.00 mg/l (48 h; Daphnia magna; Locomotor effect)		
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)		
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)		
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)		

Persistence and degradability 12.2.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.50 g O ₂ /g substance
BOD (% of ThOD)	0.80 % ThOD

12.3. Bioaccumulative potential

methanol (67-56-1)		
BCF fish 1	< 10.00 (72 h; Leuciscus idus)	
BCF fish 2 1.00 (72 h; Cyprinus carpio; Blood)		
Log Pow	-0.77 (Experimental value; Other)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

methanol (67-56-1)			
Surface tension	0.02 N/m (20 °C)		
12.5. Other adverse effects			
Effect on ozone layer	: No known effect on the ozone layer		
Effect on global warming	: No known ecological damage caused by this product.		
Other information : Avoid release to the environment.			
SECTION 13: Disposal considerati	ons		
13.1. Waste treatment methods			
Waste disposal recommendations	: Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in		

accordance with local/regional/national/international regulations.

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	
In accordance with DOT	
Transport document description	: UN1993 Flammable liquids, n.o.s. (Methanol), 3, III
UN-No.(DOT)	: 1993
DOT NA no.	: UN1993
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s.

Transport hazard class(es) (DOT) Hazard labels (DOT)

Ste	
3	

: 3 - Flammable liquid

Methanol

DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information	: In inner packaging no more than 5.0 L: Proper Shipping Name: Limited Quantity of Class III Per 49 CFR Part 173.10 (PG III, inner packaging no more than 5.0L).
ADR No additional information available	
Transport by sea UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S. (Methanol)

Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	In Non-Bulk quantities with inner packaging no more than 5.0L: Proper Shipping Name: Dangerous Goods in Limited Class 3 (Windshield Wash Containing Methanol) Packages or pallets must be marked "Dangerous Goods in Limited Quantities of Class 3" Outer Package cannot weigh more than 30 kg.
Air transport	
UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: FLAMMABLE LIQUID, N.O.S. (Methanol)
Class (IATA)	: 3 - Flammable Liquids

Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger
Instruction "passenger" - Limited quantities (ICAO)	: Y309 (Max qty. per package 10L) Special Provision A3

SECTION 15: Regulatory information			
15.1. US Federal regulations			
Blue Mountain Windshield Wash -20 °F			
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed		
SARA Section 302 Threshold Planning Quantity (TPQ)	None		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard		
SARA Section 313 - Emission Reporting	33 % (Methanol CAS # 67-56-1)		
methanol (67-56-1)			
Listed on the United States TSCA (Toxic Substances Control Act) i Listed on United States SARA Section 313	nventory		
RQ (Reportable quantity, section 304 of EPA's 5000 lb(s)			

15.2. International regulations **CANADA**

WHMIS Classification

List of Lists)



Class B Division 2 -Class D Division 1 Flammable Liquid Subdivision A - Very toxic material causing immediate and serious toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP] No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD] Not classified

Blue Mountain Windshield Wash -20 °F DSL (Canada): The intentional ingredients of this product are listed

ECL (South Korea): The intentional ingredients of this product are listed. EINECS (Europe): The intentional ingredients of this product are listed ENCS (Japan): The intentional ingredients of this product are listed

15.3. US State regulations

methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
methanol (67-56-1)				
U.S Massachusetts - Righ U.S New Jersey - Right to U.S Pennsylvania - RTK (Know Hazardous Substance L	ist		

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H332	Harmful if inhaled
H370	Causes damage to organs

NFPA health hazard

NFPA fire hazard

NFPA reactivity

: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating Health Flammability

: 2 Moderate Hazard - Temporary or minor injury may occur

3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 °F (22 °C) and boiling points above 100 °F (37 °C). as well as liquids with flash points between 73 °F (22 °C) and 100 °F (37 °C). (Classes IB & IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

A - Safety glasses

Personal Protection

Physical

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.