

The 12V Drum Pump System provides everything you need to pump diesel exhaust fluid efficiently with a 12V power source.

- 12V Drum Pump System includes 12V axial gear pump, discharge hose, suction hose, drum adapter coupling and poly manual nozzle
- Can be manually operated in case of electrical power outage
- Designed exclusively for use as a drum pump
- 1 Year Limited Liability Warranty
- Efficient DEF delivery rate, per manual pump stroke

## TECHNICAL DATA

**Connecting cable, length (ft):** 6.6  
**Connection container:** G 2" male, drum adapter 64x5  
**Connection suction side:** Hose fitting DN 19  
**Connection discharge side:** G 1" male

### HYDRAULIC DATA:

Pump design:	axial gear
Delivery rate under free discharge up to (gpm):	10
Suction height up to (ft):	8.2
Discharge height max. (ft):	49.2
Pumping media:	DEF

### MOTOR DATA:

Voltage (V):	12 V DC
Power consumption (A):	14
Power (W):	180
Thermal protection:	self-resetting
Duty cycle:	continuous operation
Rotation speed at 0.5 bar counter pressure (rpm):	7500
Type of construction:	IMB 5
Protection class:	IP 34
	PA 6
Material of pump housing and pump:	stainless steel
Material motor shaft:	1.4021

**Dimensions of pump LxWxH (inch):** 3.5 x 4.7 x 11.8  
**Weight with accessories (lb):** 9.9



**DEFDP12V (Manual Poly Nozzle)**

UPC : 0-74804-06471-1  
 SCC 14 Bar Code: 1-00-74804-06471-8

## PACKAGING

<b>Packaging:</b>	white carton
<b>Dimensions LxWxH (inch):</b>	15.7 x 15.7 x 8.7
<b>Weight including package (lb):</b>	11.71
<b>Packaging unit:</b>	1.0

## SPECIFICATION

- Axial wheel pump with manual pump assembly
- Illuminated on/off switch
- Motor with thermal protection switch, self-resetting
- US plug, 6.6 ft cable
- Drum adapter coupling
- Connecting cable with battery terminal clips and fuse holder
- DEF discharge hose with 90° female with swivel joint
- Poly nozzle w/ 13 Ft DEF hose
- DEF suction hose, 5.25 ft, with foot valve
- Drum adapter coupling, for plastic container, connecting thread G 2"

