



PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/01/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Motor Oil

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

Signal word (GHS-US) : None
Hazard statements (GHS-US) : None
Precautionary statements (GHS-US) : P273 - Avoid release to the environment.
P391 - Collect spillage.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification : Avoid prolonged or repeated contact with used motor oil. Used motor oil has been shown to cause skin cancer in laboratory animals.

2.4. Unknown acute toxicity (GHS US)

12.9% of the mixture consists of ingredient (s) of unknown toxicity. (Oral, Dermal) 23.14% of the mixture consists of ingredient (s) of unknown toxicity. (Inhalation: Vapor, Dust)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

This mixture does not contain any substances to be mentioned according to the criteria of section 3.2 of HazCom 2012

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation.
Symptoms/effects after eye contact	: ON CONTINUOUS EXPOSURE/CONTACT: May cause slight irritation.
Symptoms/effects after ingestion	: Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs or even death.

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Alcohol-resistant foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Do not use a heavy water stream. Will float and can be reignited on water surface.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Hazardous combustion products. carbon monoxide. Smoke, sulfur oxides, aldehydes & other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.
Reactivity	: No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Fight fire with normal precautions from a reasonable distance. Under fire conditions, hazardous fumes will be present.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Use appropriate personal protection equipment (PPE).
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product. Plug the leak, cut off the supply. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store near food, foodstuffs, drugs or potable water supplies.
- Incompatible materials : Keep away from strong acids, strong bases and oxidizing agents.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene. Nitrile rubber

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : amber
- Odor : petroleum-like odor
- Odor threshold : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Freezing point : No data available

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: 150 °C (302 °F)
Flash point	: 223 °C (433 °F) [Method used: Cleveland Open Cup]
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.2
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 0.87 - 0.88
Density	: 0.87 - 0.88 kg/l (7.2 - 7.3 lbs/gal)
Solubility	: Water: Negligible
Log Pow	: No data available
Log Kow	: 3.9
Viscosity, kinematic	: 110.4 cSt @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons. Nitrogen containing gases. Aldehydes. Sulfur oxides. Oxides of phosphorus. Hydrogen sulfide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation.
Symptoms/effects after eye contact	: ON CONTINUOUS EXPOSURE/CONTACT: May cause slight irritation.

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs or even death.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No additional information available.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Log Kow	3.90
---------	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer

Effect on global warming : No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Transport by sea

In accordance with IMDG / IMO

Not regulated

Air transport

In accordance with IATA / ICAO

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
SARA Section 311/312 Hazard Classes	Refer to Section 2 for the OSHA hazard classification

15.2. International regulations

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CANADA

PEAK Commercial and Industrial Heavy Duty Diesel Motor Oil SAE 15W-40 Synthetic Blend

WHMIS Classification

This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations

California Proposition 65 - This product does not contain any substance(s) known to the state of California to cause cancer, developmental toxicity and/or reproductive toxicity


SECTION 16: Other information

Revision date : 03/01/2022

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.