

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : PEAK Premium Universal Tractor Hydraulic Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Hydraulic oil

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC 4065 Commercial Ave. Northbrook, IL 60062 - USA T (847) 559-2000

www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)

Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Sens. 1 H317

Full text of H-statements: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction Precautionary statements (GHS-US) : P261 - Avoid breathing mist, spray, vapors

P272 - Contaminated work clothing must not be allowed out of the workplace

P280 - Wear personal protective equipment as required P302+P352 - If on skin: Wash with plenty of soap and water

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/container, in a safe manner, to appropriate waste disposal facility,

in accordance with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the

classification

: Avoid prolonged or repeated contact with used fluid.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

08/14/2015 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	% by wt	GHS-US classification
distillates (petroleum), hydrotreated heavy paraffinic	(CAS No) 64742-54-7	90 - 99	Acute Tox. 3 (Inhalation:vapor), H331 Acute Tox. 4 (Inhalation:vapor), H332
Reaction products of bis(4-methlypentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	(CAS No) -	0.1 - 1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 2, H411

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if

you feel unwell.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse. Wash contaminated clothing before reuse. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Remove

contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or

doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.

Symptoms/injuries after skin contact : Contact during a long period may cause slight irritation.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects.

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable extinguishing media : Do not use a heavy water stream. Will float and can be reignited on water surface.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable. Promotes combustion.

Explosion hazard : Not applicable.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Fight fire with normal precautions

from a reasonable distance. Under fire conditions, hazardous fumes will be present.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Special protective equipment for fire fighters : Protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves).

Wear positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray.

6.1.1. For non-emergency personnel

Protective equipment : Use appropriate personal protection equipment (PPE).

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

08/14/2015 EN (English) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain leaking substance. Plug the leak, cut off the supply. Take up mechanically (sweeping,

shovelling) and collect in suitable container for disposal.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Any proposed use of this product in elevated-temperature processes should be thoroughly

evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Do not store near food, foodstuffs, drugs or potable water

supplies.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PEAK Premium Universal Tractor Hydraulic Oil		
ACGIH	ACGIH TWA (mg/m³)	5.00 mg/m³ Chemical name: Oil mist, mineral
ACGIH	ACGIH STEL (mg/m³)	10.00 mg/m³ Chemical name: Oil mist, mineral
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ Chemical name: Oil mist, mineral
OSHA	Remark (OSHA)	Skin notation

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



Hand protection : Wear suitable gloves resistant to chemical penetration.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

08/14/2015 EN (English) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color : brown

Odor : petroleum-like odor Odor threshold : No data available Relative evaporation rate (butylacetate=1) : No data available Freezing point : No data available Boiling point : No data available

Flash point : 207 °C (404 °F) [Method used: Cleveland Open Cup]

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available

Vapor pressure : < 0.2

Relative vapor density at 20 °C : No data available

Specific Gravity : 0.9

Density : 0.9 kg/l (7.50 lbs/gal)
Solubility : Water: Negligible
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : 91.26 cP

Explosive properties : Not applicable.

Oxidizing properties : No data available

Explosive limits : No data available

9.2. Other information

VOC content : 0.00 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5,000.00 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)	
LD50 dermal rabbit	> 5,000.00 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)	
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h (Rat; Experimental value)	
ATE US (vapors)	3.00 mg/l/4h	

Reaction products of bis(4-methlypentan-2-yl (branched) (-)	dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl
ATE US (oral)	500.00 mg/kg bodyweight

Skin corrosion/irritation : Not classified

08/14/2015 EN (English) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.

Symptoms/injuries after skin contact : Contact during a long period may cause slight irritation.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects.

SECTION 12: Ecological information

12.1. Toxicity

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100.00 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
Threshold limit algae 1	>= 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil.

12.3. Bioaccumulative potential

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No known effect on the ozone layer

Effect on global warming : No known ecological damage caused by this product.

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in

accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good in sense of transport regulations

TDG

Refer to current TDG Canada for further Canadian regulations

08/14/2015 EN (English) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

PEAK Premium Universal Tractor Hydraulic Oil		
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed	
SARA Section 313 - Emission Reporting	This product contains or may contain the following chemicals, in the following percentages that are subject to SARA 313 reporting: Zinc (CAS # 7440-66-6) [0.01 - 0.1], Diphenylamine (CAS # 122-39-4) [0.001 - 0.01%], Diethanolamine (CAS # 111-42-2) [0.001 - 0.01%], Toulene (CAS # 108-88-3) [0.001 - 0.01%], Vinyl acetate (CAS # 108-05-4) [0.001 - 0.01%], Cumene (CAS # 98-82-8) [0.001 - 0.01%], Benzene (CAS # 71-43-2) [0.001 - 0.01%], Naphthalene (CAS # 91-20-3) [< 10 ppm], Arsenic (CAS # 7440-38-2) [< 10 ppm], Methyl isobutyl ketone (CAS # 108-10-1) [< 10 ppm], Cadmium (CAS # 7440-43-9) [< 10 ppm], Ethylbenzene (CAS # 100-41-4) [< 10 ppm],	

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

WHMIS Classification

Uncontrolled product according to WHMIS classification criteria

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

08/14/2015 EN (English) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PEAK Premium Universal Tractor Hydraulic Oil	
U.S California - Proposition 65 - Other information	This products contains or may contain the following chemicals in the percentages listed, which are subject to the California Prop 65 regulation listed: 2-2'Iminodiethanol (CAS # 111-42-2) [0.001 - 0.01 %] (California Prop 65 - Cancer), Cumene (CAS # 98-82-8) [0.001 - 0.01 %] (California Prop 65 - Cancer), Benzene (CAS # 71-43-2) [0.001 - 0.01 %] (California Prop 65 - Cancer, California Prop 65 - Developmental Toxicity, California Prop 65 - Cancer) Isobutyl Methyl Ketone (CAS # 108-10-1) [<10 ppm] (California Prop 65 - Cancer, California Prop 65 - Developmental Toxicity), Cadmium (CAS # 7440-43-9) [<10 ppm] (California Prop 65 - Cancer, California Prop 65 - Developmental Toxicity), California Prop 65 - Reproductive Male), Ethylbenzene (CAS # 100-41-4) [< 10 ppm] (California Prop 65 - Cancer), Toulene (CAS # 108-88-3) [0.001 - 0.01 %] (California Prop 65 - Developmental Toxicity),

SECTION 16: Other information

Full text of H-statements:

At of 11 statements.	
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Sens. 1	Sensitisation — Skin, Category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H411	Toxic to aquatic life with long lasting effects


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 °F (93 °C). (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection B - Safety glasses, Gloves

SDS GHS US (GHS HazCom 2012) OWI w/Supp OEL's

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

08/14/2015 EN (English) 7/7