

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 02/05/2022

SECTION 1: Identification of the su	bstance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
Product name	: PEAK dexcool [™] Concentrate Antifreeze and Coolant
SDS ID	: 115007
1.2. Relevant identified uses of the sub	ostance or mixture and uses advised against
Use of the substance/mixture	: Antifreeze & Coolant
1.3. Details of the supplier of the safety	y data sheet
Old World Industries, LLC 3100 Sanders Road Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com	
1.4. Emergency telephone number	
Emergency number	: 800 424 9300 (United States); 00 1 703 527 3887 (International) Chemtrec
SECTION 2: Hazards identification	
2.1. Classification of the substance or	mixture
GHS-US classification	
Acute toxicity (oral), H302	Harmful if swallowed.
Category 4 Reproductive toxicity, H361 Category 2	Suspected of damaging fertility or the unborn child.
Specific target organ H373 toxicity — Repeated exposure, Category 2 Full text of H-statements: see section 16	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
2.2. Label elements	
GHS US labelling	
Hazard pictograms (GHS US)	: GHS07 GHS08
Signal word (GHS US)	: Warning
Hazard statements (GHS US)	: Harmful if swallowed. Suspected of damaging fertility or the unborn child. May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Precautionary statements (GHS US)	 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wear personal protective equipment as required. If swallowed: Immediately call doctor/physician or poison center. If swallowed: rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
ethylene glycol	(CAS-No.) 107-21-1	90 – 97	Acute Tox. 4 (Oral), H302
diethylene glycol	(CAS-No.) 111-46-6	0.5 – 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
water	(CAS-No.) 7732-18-5	1 – 5	Not classified
potassium 2-ethylhexanoate	(CAS-No.) 3164-85-0	0 – 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361
sodium 2-ethylhexanoate	(CAS-No.) 19766-89-3	0-5	Repr. 2, H361
denatonium benzoate	(CAS-No.) 3734-33-6	0.003 - 0.005 [30 - 50 ppm]	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If you feel unwell, seek medical advice.
First-aid measures after skin contact	:	Wash skin with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Rinse immediately with plenty of water (for at least 15 minutes), Get medical advice/attention.
First-aid measures after eye contact	:	Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	:	Obtain emergency medical attention. Rinse mouth. If the person is fully conscious, make him/her drink two glasses of water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whiskey. For children, give proportionally less liquor, according to weight.
4.2. Most important symptoms and effe	ects	, both acute and delayed
Symptoms/effects	:	Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	:	May cause moderate irritation.
Symptoms/effects after eye contact	:	Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	:	Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).
4.3. Indication of any immediate medic	al a	ttention and special treatment needed
A more effective intravenous antidate for physic	aian	uses is 4 methylpyrazaela, a potent inhibitor of alcohol dehydrogeneses, which effectively blocks the

A more effective intravenous antidote for physician uses is 4-methylpyrazaole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occured.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Carbon dioxide. Dry chemical. Foam. Sand. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. May spread fire.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the su	Ibstance or mixture
Fire hazard	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Product is not flammable or combustible but may burn under fire conditions.
Reactivity	: No dangerous reactions known under normal conditions of use.
5.3. Special protective equipment and p	precautions for fire-fighters
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTIO	ON 6: Accidental release measu	ires	
6.1.	Personal precautions, protective equipment and emergency procedures		
6.1.1.	For non-emergency personnel		
Emergen	cy procedures	Evacuate unnecessary personnel.	
6.1.2.	For emergency responders		
Protective	e equipment	Equip cleanup crew with proper protection. Use personal protective equipment as required.	
Emergen	cy procedures	Ventilate area.	
6.2.	Environmental precautions		
Prevent e	entry to sewers and public waters. Notify a	authorities if liquid enters sewers or public waters.	

6.3.	Methods and	material	for containment	and c	leaning u	р	
Methods	for cleaning up)	:	Soak	up spills v	with iner	t solids, s

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.
7.2. Conditions for safe storage, including	ng any incompatibilities
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. Product may become solid at temperatures below -18 °C (0 °F). Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.
Incompatible products	: Keep away from strong acids, strong bases and oxidizing agents.
Incompatible materials	: Sources of ignition.
7.3. Specific end use(s)	
No additional information available	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

denatonium benzoate (3734-33-6)				
Not applicable	Not applicable			
ethylene glycol (107	7-21-1)			
ACGIH	Local name	Ethylene glycol		
ACGIH	ACGIH OEL TWA	10 mg/m ³		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107	7-21-1)		
ACGIH	ACGIH OEL TWA [ppm]	25 ppm (Vapor fraction)	
ACGIH	ACGIH OEL STEL	10 mg/m ³ (Inhalable fraction, Aerosol only)	
ACGIH	ACGIH OEL STEL [ppm]	50 ppm (Vapor fraction)	
ACGIH	Remark (ACGIH)	Upper respiratory tract & eye irritant	
ACGIH	Regulatory reference	ACGIH 2018	
diethylene glycol (111-46-6)			
Not applicable			
water (7732-18-5)			
Not applicable			
potassium 2-ethylhexanoate (3164-85-0)			
Not applicable			
sodium 2-ethylhexa	noate (19766-89-3)		
Not applicable			

8.2. Appropriate engineering controls

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Respiratory protection not required in normal conditions. If exposed to levels above exposure limits wear appropriate respiratory protection.



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemica	l properties	
9.1. Information on basic physical and	d chemical properties	
Physical state	: Liquid	
Molecular mass	: 62.07 g/mol Ethylene Glycol	
Color	: Orange	
Odor	: Mild	
Odor threshold	: No data available	
pH 50% water solution	: 8	
Relative evaporation rate (butylacetate=1)	: Nil	
Freezing point	: -18 °C (0 °F)	
Boiling point	: 158 °C (317 °F)	
Flash point	: No data available	
02/05/2022	EN (English)	4/10

Safety Data Sheet

ccording to Federal Register / Vol. 77, No. 58 / Monday,	-
Auto-ignition temperature	: 400 °C (752 °F) [100% Ethylene Glycol] <i>Literature</i>
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.1 @ 20 ℃
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 1.12
Density	: 1.12 kg/l (9.34 lbs/gal)
Solubility	: Water: Complete
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: 3.2 – 15.3 vol %
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
9.2. Other information	
VOC content	: 0%
SECTION 10: Stability and reactivity	
10.1. Reactivity	
No dangerous reactions known under normal con	ditions of use.
10.2. Chemical stability	
Stable.	
10.3. Possibility of hazardous reactions	Plane - free
No dangerous reactions known under normal con	actions of use.
10.4. Conditions to avoid	
Extremely high or low temperatures. Keep away f	rom any flames or sparking source.
10.5. Incompatible materials	
Keep away from strong acids, strong bases and o	oxidizing agents.
10.6. Hazardous decomposition products	
Alcohols. Aldehydes. Carbon dioxide. Carbon mo	noxide. Ethers. Fume.
SECTION 11: Toxicological informati	
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
denatonium benzoate (3734-33-6)	
LD50 oral rat	584 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	 > 2000 mg/kg (Rabbit, Literature study, Dermal)
ATE US (oral)	584 mg/kg bodyweight
ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male / female,
	Experimental value, Aqueous solution, Oral, 7 day(s))
LOE0 lub station Dat	

> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))

19600 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value,

LC50 Inhalation - Rat

diethylene glycol (111-46-6)

ATE US (oral)

LD50 oral rat

ATE US (oral)

ATE US (dermal)

Skin corrosion/irritation

LD50 dermal rabbit

LC50 Inhalation - Rat

Oral)

500 mg/kg bodyweight

500 mg/kg bodyweight

11890 mg/kg bodyweight

11890 mg/kg (Rabbit, Dermal)

> 4.6 mg/l/4h (Other, 4 h, Rat, Weight of evidence)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	,,
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).

SECTION 12: Ecological information

12.1. Toxicity				
Ecology - general	No additional information available.			
denatonium benzoate (3734-33-6)				
LC50 - Fish [1]	> 1,000.00 mg/l (96 h, Salmo gairdneri, Literature study)			
EC50 - Crustacea [1]	13.00 mg/l (48 h, Daphnia magna, Literature study)			
ethylene glycol (107-21-1)	ethylene glycol (107-21-1)			
LC50 - Fish [1]	40,761.00 mg/l (96 h, Salmo gairdneri, Static system)			
EC50 - Crustacea [1]	> 10,000.00 mg/l (24 h, Daphnia magna)			
diethylene glycol (111-46-6)				
LC50 - Fish [1]	> 5,000.00 ppm (24 h, Carassius auratus)			
EC50 - Crustacea [1]	> 10,000.00 mg/l (24 h, Daphnia magna)			
LC50 - Fish [2]	75,200.00 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Experimental value)			
EC50 - Crustacea [2]	> 10,000.00 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)			

12.2. Persistence and degradability

denatonium benzoate (3734-33-6)		
Persistence and degradability	Biodegradability in water: no data available. No (test) data on mobility of the substance available.	
ethylene glycol (107-21-1)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.47 g O_2/g substance	
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance	
ThOD	1.29 g O ₂ /g substance	
BOD (% of ThOD)	0.36	
diethylene glycol (111-46-6)		
Persistence and degradability	Biodegradable in the soil. Biodegradable in water.	
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.51 g O ₂ /g substance	
ThOD	1.51 g O ₂ /g substance	
BOD (% of ThOD)	0.02	
02/05/2022	EN (English) 6/	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential	
denatonium benzoate (3734-33-6)	
Partition coefficient n-octanol/water (Log Pow)	1.78 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
ethylene glycol (107-21-1)	
BCF - Fish [1]	10.00 (72 h, Leuciscus idus)
BCF - Other aquatic organisms [1]	0.21 – 0.60 (Procambarus sp., Chronic)
BCF - Other aquatic organisms [2]	190.00 (24 h, Algae)
Partition coefficient n-octanol/water (Log Pow)	-1.34 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
diethylene glycol (111-46-6)	
BCF - Fish [1]	100.00 (Other, 3 day(s), Leuciscus melanotus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-1.98 (Calculated, Other)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

denatonium benzoate (3734-33-6)			
Ecology - soil	No (test)data on mobility of the substance available.		
ethylene glycol (107-21-1)			
Surface tension	48.00 mN/m (20 °C)		
Ecology - soil	No (test)data on mobility of the substance available.		
diethylene glycol (111-46-6)			
Surface tension	0.05 N/m		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.00 (log Koc, SRC PCKOCWIN v1.66, Calculated value)		
Ecology - soil	Highly mobile in soil.		

12.5. Other adverse effects				
Effect on the ozone layer	: No known effect on the ozone layer			
Other information	: Avoid release to the environment.			
SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.			

Ecology - waste materials

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Non Bulk (in quantities under 5,000 lbs in any one inner package): Not regulated by the US DOT

Bulk (in quantities 5,000 lbs or over in any one inner package):

Transport document description (DOT)	: UN3082 Environmentally hazardous substances, liquid, n.o.s. (Ethylene Glycol), 9, III
UN-No.(DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s.
	Ethylene Glycol
Class (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (DOT)	:	III - Minor Danger
Hazard labels (DOT)	:	9 - Class 9 (Miscellaneous dangerous materials)
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Symbols	:	G - Identifies PSN requiring a technical name
DOT Packaging Exceptions (49 CFR 173.xxx)	:	155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	No limit
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	:	No supplementary information available.

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

ADR

Not regulated

Transport by sea

In accordance with IMDG / IMO Not regulated

Air transport

In accordance with IATA / ICAO Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

PEAK dexcool™ Concentrate Antifreeze and Coolant				
EPA TSCA Regulatory Flag		Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed		
denatonium benzoate (3734-33-6)				
Listed on the United States TSCA (Toxic Substa	nces Control Act) i	nventory		
ethylene glycol (107-21-1)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313				
EPA TSCA Regulatory Flag	T - T - indicates	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.		
CERCLA RQ	5000 lb(s)			
SARA Section 311/312 Hazard Classes	Refer to Section 2 for the OSHA hazard classification Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.			
SARA Section 313 - Emission Reporting	Ethylene glycol is subject to Form R Reporting requirements.			
diethylene glycol (111-46-6)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
water (7732-18-5)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pota	ssium 2-ethylhexanoate (3164-85-0)
Liste	d on the United States TSCA (Toxic Substances Control Act) inventory
sodi	um 2-ethylhexanoate (19766-89-3)
Liste	d on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PEAK dexcool [™] Concentrate Antifreeze and Coolant	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

water (7	/732-18-5)
Listed on	n the Canadian DSL (Domestic Substances List)
sodium	2-ethylhexanoate (19766-89-3)
Listed on	n the Canadian DSL (Domestic Substances List)

15.3. US State regulations

WARNING: This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ethylene glycol (107-21-1)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)	
No	Yes	No	No		(ingested) 8,700 (oral) μg/day	

ethy	lene g	lycol (107-21-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

diethylene glycol (111-46-6)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

Revision date

: 02/05/2022

Full text of H-statements:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated
	exposure.

NFPA health hazard

: 1 - Materials that, under emergency conditions, can cause significant irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard NFPA reactivity : 1 - Materials that must be preheated before ignition can occur.
: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.