

# THERMAL CHARGE®

HEAT TRANSFER FLUID

## XL NOAT

Inhibited Ethylene Glycol-Based Nitrited Extended Life Coolant For Stationary Engines



### DESCRIPTION

Thermal Charge® XL NOAT is a nitrited Organic Acid Technology (OAT), ethylene glycol-based extended life coolant which contains organic inhibitors to provide guaranteed protection for all system metals. Its phosphate-free formula helps prevent scaling that can impede heat transfer and cause cylinder head cracking. With proper maintenance, Thermal Charge XL NOAT can protect cooling systems for up to 15,000 hours in stationary engines without the use of additional inhibitors.

### BENEFITS

- Works in ALL heavy duty stationary engines
- Protection for up to 15,000 hours
- Excellent heat transfer for high temperature applications such as engines with EGR and SCR systems
- Provides protection against freezing and boilover
- Excellent protection against corrosion and wet-sleeve liner cavitation
- Non-abrasive formula can improve water pump seal life
- Phosphate, silicate and borate-free formula reduces the risk of scale
- Meets the ASTM D3306 requirements for ASTM D1384, which is the industry standard test method to demonstrate corrosion protection of all system metals (copper, standard solder, brass, steel, cast iron, cast aluminum)
- Meets ASTM D6210 requirements for use in heavy duty applications
- Can be mixed with similar heat transfer fluids

### SUITABLE APPLICATIONS

- All heavy duty diesel, gasoline and natural gas stationary engines
- Gas distribution line heaters
- Indirect heaters

THERMAL CHARGE XL NOAT FREEZE/BOIL PROTECTION CHART	% of System Capacity	PROTECTS FROM	
		Freezing Down to	Boiling up to**
	40	-13°F	+205°F
	50	-34°F	+265°F
	60	-62°F	+270°F

\*\*Using a 15 lb. pressure cap at sea level.

#### SPECIFICATIONS/RECOMMENDED USE

##### Meets these specifications:

- ASTM D6210
- ASTM D3306
- ASTM D4985

##### Recommended for use where the following equipment and specifications are cited:

- Agco
- CAT
- CNH
- Cummins
- Detroit Diesel
- Deutz
- Fendt
- International
- John Deere
- Komatsu
- Kubota
- MAN
- Mercedes
- MTU
- Navistar
- Volvo/Mack
- Waukesha

To order, please call **1-800-323-5440** or email [commercial@owi.com](mailto:commercial@owi.com)

For technical support, call 1-800-477-5847

PROPERTIES	ASTM TEST METHOD	% VOL		
		40%	50%	100%
Specific Gravity @ 60/60 °F	D1122	1.054	1.072	.126
pH of Solution	D1287	8.2 min	8.5 min	9.0 min†
Reserve Alkalinity, mL	D1121	2 min	3 min	4 min
Freezing Point, °F/°C	D1177, D3321, D6660	-13/-24	-34/-37	-34/-37†
Burst Point, °F/°C	-	-60/-51	-60/-51	-60/-51
Boiling Point*, °F/°C	D1120	221/105	226/108	325/163
Chloride, ppm	D5827	<25	<25	<25
Odor	-	Not Offensive		
Color	-	Red		

\* At atmospheric pressure  
† At 50/50 dilution

### PRODUCT AVAILABILITY

	PART NUMBER		
Bulk	TIAB40	TIAB50	TIAO80
275 Gallon Tote	TIAB48	TIAB58	TIAO88
55 Gallon Drum	TIAB41	TIAB51	TIAO81



Manufactured for Old World Industries, LLC Northbrook, IL 60062 • (800) 289-7234  
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT  
©2019 Old World Industries, LLC. All Rights Reserved.  
THERMAL CHARGE, PEAK and PEAK & Mountain Graphic are trademarks of Old World Industries, LLC.



[peakhd.com](https://www.peakhd.com)