

PEAK
ORIGINAL
EQUIPMENT
TECHNOLOGY

ASIAN VEHICLES

GREEN
ANTIFREEZE + COOLANT

DESCRIPTION

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **ASIAN VEHICLES** is a line of premium coolants specifically designed to match the technology and color requirements of **Asian** vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **ASIAN VEHICLES - GREEN** is an ethylene glycol-based antifreeze/coolant specifically developed for use in any Asian vehicle requiring a green phosphate-enhanced organic acid technology (POAT) formulation. It contains high-quality organic acid corrosion inhibitors and is free of borate, nitrite, silicate and amines.

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for **ASIAN VEHICLES - GREEN** meets the performance requirements of ASTM D3306 and JIS K2234. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 400,000 miles or 15 years*.

FEATURES & BENEFITS

- Matches each Asian vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and JIS K2234
- Service life of up to 15 years/400,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

Use **PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT concentrate** to perform a complete flush/fill or top-off.

Use **PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ 50/50 PREDILUTED ANTIFREEZE + COOLANT** when just topping off your system.

* If properly maintained. See warranty details at PEAKAUTO.com

**A PERFECT MATCH
FOR EVERY VEHICLE**



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
40/60	-13°F (-25°C)	260°F (127°C)
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)

*Using a 15 psig (103 kPa) pressure cap in good condition

50/50 Prediluted: For optimum performance and corrosion protection, coolant concentration should be maintained at 50% by volume.

Concentrate: For optimum performance coolant concentration should be maintained between 40-60% by volume.



**Available in both 50/50 Prediluted
and Concentrate**



ORIGINAL EQUIPMENT TECHNOLOGY™

ANTIFREEZE + COOLANT

APPLICATIONS

PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT for ASIAN VEHICLES - GREEN is specifically engineered for use in all Asian vehicles requiring a GREEN PHOSPHATE-ENHANCED organic acid technology (POAT) extended life antifreeze/coolant:

- Hyundai, Kia & Genesis: 1990-2021, includes hybrid and electric vehicles
- Infiniti & Nissan: 1990-2008, includes hybrid vehicles
- Mazda: 1990 and newer: includes hybrid and electric vehicles
- Mitsubishi: Pre-2012
- Subaru: 1990-2008
- Suzuki: Pre-2010

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance	Visual	Green	Green	Distinctive
pH	D1287	7.7 (50% vol)	7.7	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °C (°F)	D1120	162.8 (325)	109.5 (229.1)	108 (226) Min
Freezing point, °C (°F)	D1177	-	-37.9 (-36.2)	-36.4 (-33.5) Max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 Max ¹
Ash content, mass %	D1119	1.62	0.82	5 Max ¹ / 2.5 Max ²
Chloride, ppm	D3634	<25	<25	25 Max
Shelf Life, Years-Unopened original container	-	3	5	-

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PAG0B3

1 Gallon Bottle

0-74804-06370-7

6/1 Gallon Case

0-74804-16372-8

PAG0B1

55 Gallon Drum

0-74804-07037-8



50/50 PREDILUTED

PAGB53

1 Gallon Bottle

0-74804-06371-4

6/1 Gallon Case

0-74804-16371-1

PAGB51

55 Gallon Drum

0-74804-07027-9

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PAG0B3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PAGB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PAG0B1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PAGB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK® Original Equipment Technology™ Asian GREEN Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK® Original Equipment Technology™ Asian GREEN Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestion of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

To order, please call Old World Industries Customer Service
at 1-800-323-8755

For Technical Product Support, please call
1-800-477-5847

Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

Manufactured for Old World Industries, LLC, Northbrook, IL 60062
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2023 Old World Industries, LLC. All Rights Reserved.
PEAK, PEAK & Mountain Graphic, PEAK Original Equipment Technology graphic and
Original Equipment Technology are trademarks of Old World Industries, LLC

