

CONVENTIONAL GREEN TECHNOLOGY



ANTIFREEZE + COOLANT

GREEN

ENGINEERED FOR OLDER AUTOMOTIVE & DIESEL APPLICATIONS  
2 YEARS / 50,000 MILES\*

## DESCRIPTION

PEAK® Antifreeze + Coolant is a conventional green, ethylene glycol based antifreeze for use in older automotive and light duty diesel applications. PEAK® Antifreeze + Coolant provides maximum protection from freezing to -84°F and boil over to +276°F. Protects all metals, including aluminum, against damaging rust and corrosion when used as recommended.

## FEATURES & BENEFITS

- Maximum Freeze Up Protection To -84°F Boil Over Protection To +276°F\*
- Provides Year-Round Protection Against Damaging Rust and Corrosion
- Compatible with All Conventional Green Antifreeze
- Meets or exceeds ASTM D3306 and D4985 specifications

## APPLICATIONS

Engineered for use in older passenger cars, and light duty trucks including:

- Ford & Chrysler 2000 + earlier
- GM 1995 + earlier
- All makes + models 1989 + earlier

Also recommended for use where the following are cited:

- Chrysler/FCA MS-7170
- Ford ESE-M97844-A
- General Motors GM 1899M, GM 1825M
- TMC RP 302C
- SAE J814

\*See warranty details at [PEAKGuarantee.com](http://PEAKGuarantee.com)



## FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTS FROM	
	Freezing Down to	Boiling Up to <sup>Δ</sup>
40/60	-13°F (-25°C)	260°F (127°C)
50/50	-34°F (-37°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)

<sup>Δ</sup>Using a 15 psi (103 Pa) pressure cap

Provides corrosion protection when diluted by volume to a minimum of 33% coolant concentration.

**50/50 Prediluted:** For optimum performance coolant concentration should be maintained at 50% by volume.

**Concentrate:** For optimum performance coolant concentration should be maintained between 40-60% by volume.



Available in both 50/50 Prediluted and Concentrate

CONVENTIONAL GREEN TECHNOLOGY



ANTIFREEZE + COOLANT

PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Green	Green	Distinctive
pH, 50 vol %	D1287	10.0-11.0	10.0-11.0	7.5-11.0
Specific gravity	D1122	1.120-1.130	1.070-1.8	1.110-1.145 <sup>1</sup> / 1.065 min <sup>2</sup>
Boiling point <sup>3</sup> , °F (°C)	D1120	325(162.8)	229 (109.5)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-34 (-37)	-33.5 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	5	50	5 max <sup>1</sup>
Ash content, mass %	D1119	<5	<2.5	5 max <sup>1</sup> /2.5 max <sup>2</sup>
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

<sup>1</sup>For concentrate product only, <sup>2</sup>Prediluted (50/50) only, <sup>3</sup>Unpressurized

## SHIPPING INFORMATION



### CONCENTRATE

PKA0B3

1 Gallon Bottle

0-74804-00400-7

6/1 Gallon Case

1-00-74804-00400-4

PKA0B1

55 Gallon Drum

0-74804-00401-4



### 50/50 PREDILUTED

RUAB53

1 Gallon Bottle

0-74804-00225-6

6/1 Gallon Case

1-00-74804-00225-3

RUAB51

55 Gallon Drum

0-74804-03396-0

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PKA0B3	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,210
RUAB53	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	57	36	20	2,138
PKA0B1	Drum	55 Gal	23.5" dia. x 34.5" H	529	4	20	2,262
RUAB51	Drum	55 Gal	23.5" dia. x 34.5" H	553	4	20	2,166

\*\*Includes pallet weight of 50 lbs each

## ADDITIONAL INFORMATION

**Testing Requirements:** For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

**Storage Recommendations:** PEAK® Green Antifreeze + Coolant can be stored in original container at ambient temperature and limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

**Safety and Environmental Guidance:** PEAK® Green Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from [peakauto.com](http://peakauto.com). Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries  
Northbrook, IL 60062 • 800-323-5440  
[Peakauto.com](http://Peakauto.com)

To order, please call  
Old World Industries Customer Service at  
**1-800-323-8755**

Manufactured for Old World Industries, Northbrook, IL 60062 • (800) 289-7234  
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT  
©2023 Old World Industries, All Rights Reserved.  
PEAK, PEAK & Mountain Graphic are trademarks of Old World Industries.

