

ALL VEHICLES

PEAK

ANTIFREEZE+COOLANT

**YEAR-ROUND ENGINE PROTECTION
10+ YEARS / 300,000+ MILES***

DESCRIPTION

PEAK® All Vehicles provides YEAR-ROUND ENGINE PROTECTION 10+ Years / 300,000 Miles Guaranteed Protection*.

PEAK® All Vehicles Antifreeze + Coolant is formulated to protect all cooling system metals, including aluminum. It immediately protects against damaging rust and corrosion and is free of phosphates, borates, nitrites, silicates and amines.

FEATURES & BENEFITS

- Year round engine protection
- Compatible for use in all automobiles, light duty trucks and motorcycles
- Provides 300,000 miles or 10 years of maximum protection when a complete cooling system flush and fill is performed
- Meets European phosphate-free and Japanese silicate-free requirements
- Meets ASTM D3306 + ASTM D4985

APPLICATIONS

PEAK® All Vehicles Antifreeze + Coolant is designed for use in all North American, Asian and European passenger cars, SUVs, motorcycles and light/medium duty trucks, regardless of make, model or year.

Best performance is achieved when a complete flush & fill is performed using PEAK® All Vehicles Antifreeze + Coolant.

* 10+ years/300,000 miles guarantee when a complete cooling system flush and fill is performed and proper cooling system maintenance is followed. Always follow vehicle owner's manual for top-off requirements, change intervals and specified maintenance. See PEAKGuarantee.com for more details.



**Old World
Industries**



PROTECTION CHART†

FREEZE PROTECTION	-34°F (-36°C)
BOILOVER PROTECTION^Δ	265°F (129°C)
CORROSION PROTECTION	Protects All Cooling System Metals Meets ASTM D3306 & D4985

^ΔUsing a 15 psig (103 kPa) pressure cap

[†]For optimum performance and corrosion protection, coolant concentration should be maintained at 50% by volume.



**Available in both 50/50 Prediluted
and Concentrate**

ALL VEHICLES

PEAK[®]

ANTIFREEZE+COOLANT

Properties	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Fluorescent Yellow	Fluorescent Yellow	Distinctive
Specific gravity	D1122	1.115-1.124	1.066	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °F (°C), 50 vol %	D1120	325 (162.8)	229 (109.5)	226 (108) min.
pH	D1287	8.3, 50 vol %	8.3	7.5-11.0
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PKPOB3

1 Gallon Bottle
0-74804-07187-0

6/1 Gallon Case
0-74804-17187-7

PKPOB1
55 Gallon Drum
0-74804-07201-3

PKPOB8
275 Gallon Tote
0-74804-07203-7



50/50 PREDILUTED

PKPB53

1 Gallon Bottle
0-74804-07188-7

6/1 Gallon Case
0-74804-17188-4

PKPB51
55 Gallon Drum
0-74804-07200-6

PKPB58
275 Gallon Tote
0-74804-07202-0

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PKPOB3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,217
PKPB53	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	58	36	20	2,145
PKPOB1	Drum	55 gal	23.5" dia. x 34.5" H	525	4	20	2,157
PKPB51	Drum	55 gal	23.5" dia. x 34.5" H	553	4	20	2,269
PKPOB8	Tote	275 gal	40" L x 40" W x 46" H	2,679	1	14	2,679
PKPB58	Tote	275 gal	40" L x 40" W x 46" H	2,503	1	14	2,503

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK[®] All Vehicles Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) provided the container for 3-5 years, remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK[®] All Vehicles Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.
Northbrook, IL 60062

Peakauto.com

Manufactured for Old World Industries, LLC, Northbrook, IL 60062 (800) 289-7234
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2024 Old World Industries, LLC. All Rights Reserved. PEAK and PEAK Mountain
Graphic are trademarks of Old World Industries, LLC

To order, please call Old World Industries Customer Service
at 1-800-323-5440

For Technical Product Support, please call
1-800-477-5847

