

The manual shut-off nozzle is a very economical nozzle for transferring DEF. This lightweight nozzle has a poly body with a stainless steel spout.

- Compatible with all BlueDEF pumps and systems.
- Lock pin feature



TECHNICAL DATA

Connection:	G 1" male with hose liner, NW 19
Flow capacity max. (l/min):	80
Outside diameter discharge tube (mm):	18
Hose connection Swivel:	DN 19
Housing material:	plastic
Material discharge spout:	stainless steel-
Switch-off:	manually
Working pressure (bar):	0.5 – 4
Operating pressure max. (bar):	4
Dimensions LxWxH (inch):	12.99 x 6.69 x 1.97
Weight (lb):	1.17

DEF-MN

UPC: 0-74804-06500-8

SCC 14 Bar Code: 1-00-74804-06500-5

PACKAGING

Packaging:	white carton
Dimensions LxWxH (inch):	15.75 x 6.69 x 2.36
Weight including package (lb):	1.17
Packaging unit:	1.0

SPECIFICATION

- Automatic nozzle for DEF with swivel

SPECIAL NOTES

- In the case of the formation of crystals: To dissolve the crystals, bring the DEF nozzle in the compressed [open] position and put it in hot water for half an hour (max. 50°C)

