

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 01/01/2024

SECTION 1: Identifi	cation of the s	substance/mixture and of the company/undertaking
1.1. Product identif		
Product form		: Mixture
Product name		: Blue Mountain Professional Long Life Concentrate Antifreeze and Coolant
SDS ID		: 115092
1.2. Relevant identi	ified uses of the s	ubstance or mixture and uses advised against
Use of the substance/mixt		: Antifreeze & Coolant
1.3. Details of the s	supplier of the safe	atv data shoot
Old World Industries, LLC 3100 Sanders Road Northbrook, IL 60062 - US T (847) 559-2000 www.oldworldind.com		
1.4. Emergency tel	ephone number	
Emergency number		: 800 424 9300 (United States); 00 1 703 527 3887 (International) Chemtrec
SECTION 2: Hazard		
	of the substance of	or mixture
GHS-US classification		
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Reproductive toxicity,	H361	Suspected of damaging fertility or the unborn child.
Category 2 Specific target organ toxicity — Repeated exposure, Category 2 Full text of H statements :	H373 see section 16	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
2.2. Label elements	5	
GHS-US labelling		
Hazard pictograms (GHS-	US)	: GHS07 GHS08
Signal word (GHS-US)		: Warning
Hazard statements (GHS-	US)	<ul> <li>Harmful if swallowed.</li> <li>Suspected of damaging fertility or the unborn child.</li> <li>May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).</li> </ul>
Precautionary statements	(GHS-US)	<ul> <li>Obtain special instructions before use.</li> <li>Do not handle until all safety precautions have been read and understood.</li> <li>Do not breathe mist, spray, vapors</li> <li>Wash affected areas thoroughly after handling.</li> <li>Do not eat, drink or smoke when using this product.</li> <li>Wear personal protective equipment as required.</li> <li>If swallowed: Immediately call doctor/physician or poison center</li> </ul>

If inhaled: Remove person to fresh air and keep comfortable for breathing

If exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

### No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/information on ingredients

3.1. Substances

### Not applicable

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
ethylene glycol (antifreezing agent)	(CAS-No.) 107-21-1	90 - 97	Acute Tox. 4 (Oral), H302
diethylene glycol (antifreezing agent)	(CAS-No.) 111-46-6	0.5 - 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
water (solvent0	(CAS-No.) 7732-18-5	1 - 5	Not classified
potassium 2-ethylhexanoate (corrsion inhibitor)	(CAS-No.) 3164-85-0	0 - 5	Repr. 2, H361
sodium 2-ethylhexanoate (corrsion inhibitor)	(CAS-No.) 19766-89-3	0 - 5	Repr. 2, H361
denatonium benzoate (embittering agent)	(CAS-No.) 3734-33-6	0.003 - 0.005 [30 - 50 ppm]	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash skin with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Rinse immediately with plenty of water (for at least 15 minutes), Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. If eye irritation persists: Get medical advice and attention.
First-aid measures after ingestion	: Obtain emergency medical attention. Rinse mouth. If the person is fully conscious, make him/her drink two glasses of water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whiskey. For children, give proportionally less liquor, according to weight.
4.2. Most important symptoms and effe	ts, both acute and delayed
Symptoms/effects	: Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn child.
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).
4.3. Indication of any immediate medica	l attention and special treatment needed

A more effective intravenous antidote for physician uses is 4-methylpyrazaole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occured.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Carbon dioxide. Dry chemical. Foam. Sand. Water fog.</li><li>Do not use a heavy water stream. May spread fire.</li></ul>

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2.	Special hazards arising from the sub	stance or mixture
Fire haza	rd	: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Product is not flammable or combustible but may burn under fire conditions.
Reactivit	/	: No dangerous reactions known under normal conditions of use.
5.3.	Special protective equipment and pre-	ecautions for fire-fighters
Firefighti	ng instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protectio	n during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTIC	SECTION 6: Accidental release measures		
6.1.	Personal precautions, protective equi	pment and emergency procedures	
6.1.1.	For non-emergency personnel		
Emergen	cy procedures :	Evacuate unnecessary personnel.	
6.1.2.	For emergency responders		
Protective	equipment :	Equip cleanup crew with proper protection. Use personal protective equipment as required.	
Emergen	cy procedures :	Ventilate area.	
6.2.	Environmental precautions		
Prevent e	ntry to sewers and public waters. Notify a	uthorities if liquid enters sewers or public waters.	
6.3.	Methods and material for containment	and cleaning up	
Methods	for cleaning up :	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect	

## Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.
7.2. Conditions for safe storage, including	g any incompatibilities
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. Product may become solid at temperatures below -18 °C (0 °F). Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.
Incompatible products	: Keep away from strong acids, strong bases and oxidizing agents.
Incompatible materials	: Sources of ignition.
7.3. Specific end use(s)	

No additional information available

### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

denatonium benzoate (3734-33-6)			
Not applicable			
ethylene glycol (107-21-1)			
ACGIH	Local name	Ethylene glycol	
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)		
ACGIH	ACGIH TWA (ppm)	25 ppm (Vapor fraction)
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable fraction, Aerosol only)
ACGIH	ACGIH STEL (ppm)	50 ppm (Vapor fraction)
ACGIH	Remark (ACGIH)	Upper respiratory tract & eye irritant
ACGIH	Regulatory reference	ACGIH 2018
diethylene glycol (111-46-6	)	
Not applicable		
water (7732-18-5)		
Not applicable		
potassium 2-ethylhexanoate (3164-85-0)		
Not applicable		
sodium 2-ethylhexanoate (19766-89-3)		
Not applicable		

### 8.2. Appropriate engineering controls

### No additional information available

Individual protection measures/Personal protective equipment 8.3.

### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

### Hand protection:

Wear protective gloves.

### Eye protection:

Chemical goggles or safety glasses

### **Respiratory protection:**

Respiratory protection not required in normal conditions. If exposed to levels above exposure limits wear appropriate respiratory protection.



Other information:

Do not eat, drink or smoke during use.

<b>SECTION 9: Physical and chemical</b>	l properties	
9.1. Information on basic physical and	I chemical properties	
Physical state	: Liquid	
Molecular mass	: 62.07 g/mol Ethylene Glycol	
Color	: Yellow	
Odor	: Mild	
Odor threshold	: No data available	
pH 50% water solution	: 8	
Relative evaporation rate (butylacetate=1)	: Nil	
Freezing point	: -18 °C (0 °F)	
Boiling point	: 158 °C (317 °F)	
01/01/2024	EN (English)	4/10

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

. 116 °C (241 °C) (100% Ethylana Church ASTAL DEC	
: 116 °C (241 °F) [100% Ethylene Glycol] <i>ASTM D56</i>	
: 400 °C (752 °F) [100% Ethylene Glycol] <i>Literature</i>	
: No data available	
: No data available	
: < 0.1 @ 20 °C	
°C : No data available	
: 1.12	
: 1.12 kg/l (9.34 lbs/gal)	
: Water: Complete	
: No data available	
: 3.2 - 15.3 vol %	
: Not applicable.	
: Not applicable.	
1	
: 0%	

SECTION 10: Stability and reactivity		
10.1. Reactivity		
No dangerous reactions known under normal conditions of use.		
10.2. Chemical stability		
Stable.		
10.3. Possibility of hazardous reactions		
No dangerous reactions known under normal cond	litions of use.	
10.4. Conditions to avoid		
Extremely high or low temperatures. Keep away from	om any flames or sparking source.	
10.5. Incompatible materials		
Keep away from strong acids, strong bases and ox	xidizing agents.	
10.6. Hazardous decomposition products		
Alcohols. Aldehydes. Carbon dioxide. Carbon mon	oxide. Ethers. Fume.	
<b>SECTION 11: Toxicological informatio</b>	n	
11.1. Information on toxicological effects		
Acute toxicity	Not classified	
denatonium benzoate (3734-33-6)		
LD50 oral rat	584 mg/kg (Rat, Literature study, Oral)	
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Literature study, Dermal)	
ATE US (oral)	584 mg/kg bodyweight	
ethylene glycol (107-21-1)		
LD50 oral rat	7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))	
LC50 inhalation rat (mg/l)	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))	
ATE US (oral)	500 mg/kg bodyweight	
diethylene glycol (111-46-6)		
LD50 oral rat	19600 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral)	
LD50 dermal rabbit	11890 mg/kg (Rabbit, Dermal)	
LC50 inhalation rat (mg/l)	> 4.6 mg/l/4h (Other, 4 h, Rat, Weight of evidence)	
ATE US (oral)	500 mg/kg bodyweight	
01/01/2024	EN (English) 5/10	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

diethylene glycol (111-46-6)		
ATE US (dermal)	11890 mg/kg bodyweight	
	Nist stars (C. J.	
Skin corrosion/irritation	Not classified	
Serious eye damage/irritation	Not classified	
Respiratory or skin sensitisation	Not classified	
Germ cell mutagenicity	Not classified	
Carcinogenicity	Not classified	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
STOT-single exposure	Not classified	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).	
Aspiration hazard	Not classified	
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.	
Symptoms/effects	Causes damage to organs (kidneys) Oral. Suspected of damaging fertility or the unborn	child.
Symptoms/effects after skin contact	May cause moderate irritation.	
Symptoms/effects after eye contact	Direct contact with the eyes is likely to be irritating.	
Symptoms/effects after ingestion	Swallowing a small quantity of this material will result in serious health hazard. The lethal in humans is estimated to be 100 mL (3 oz).	l dose

### **SECTION 12: Ecological information** 12.1. Toxicity Ecology - general : No additional information available. denatonium benzoate (3734-33-6) > 1,000.00 mg/l (96 h, Salmo gairdneri, Literature study) LC50 fish 1 EC50 Daphnia 1 13.00 mg/l (48 h, Daphnia magna, Literature study) ethylene glycol (107-21-1) LC50 fish 1 40,761.00 mg/l (96 h, Salmo gairdneri, Static system) EC50 Daphnia 1 > 10,000.00 mg/l (24 h, Daphnia magna) diethylene glycol (111-46-6) LC50 fish 1 > 5,000.00 ppm (24 h, Carassius auratus) EC50 Daphnia 1 > 10,000.00 mg/l (24 h, Daphnia magna) LC50 fish 2 75,200.00 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Experimental value)

# LC50 fish 2 75,200.00 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Experimental value) EC50 Daphnia 2 > 10,000.00 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value) 12.2. Persistence and degradability

denatonium benzoate (3734-33-6)		
Persistence and degradability	Biodegradability in water: no data available. No (test) data on mobility of the substance available.	
ethylene glycol (107-21-1)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.47 g $O_2/g$ substance	
Chemical oxygen demand (COD)	1.24 g O <sub>2</sub> /g substance	
ThOD	1.29 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.36	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

diethylene glycol (111-46-6)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g $O_2/g$ substance
Chemical oxygen demand (COD)	1.51 g $O_2/g$ substance
ThOD	1.51 g $O_2/g$ substance
BOD (% of ThOD)	0.02

### **Bioaccumulative potential** 12.3.

denatonium benzoate (3734-33-6)	
Log Pow	1.78 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
ethylene glycol (107-21-1)	
BCF fish 1	10.00 (72 h, Leuciscus idus)
BCF other aquatic organisms 1	0.21 - 0.6 (Procambarus sp., Chronic)
BCF other aquatic organisms 2	190.00 (24 h, Algae)
Log Pow	-1.34 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
diethylene glycol (111-46-6)	
BCF fish 1	100.00 (Other, 3 day(s), Leuciscus melanotus, Static system, Fresh water, Experimental value)
Log Pow	-1.98 (Calculated, Other)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. **Mobility in soil**

denatonium bonzoato (3734-33-6)	
denatonium benzoate (3734-33-6)	
Ecology - soil	No (test)data on mobility of the substance available.
ethylene glycol (107-21-1)	
Surface tension	48.00 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.
diethylene glycol (111-46-6)	
Surface tension	0.05 N/m
Log Koc	0.00 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.
12.5. Other adverse effects	
Effect on the ozone layer	: No known effect on the ozone layer
Other information	: Avoid release to the environment.
SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Department of Transportation (DOT)

In accordance with DOT


Non Bulk (in quantities under 5,000 lbs in any one inner package): Not regulated by the US DOT

### Bulk (in quantities 5,000 lbs or over in any one inner package):

Transport document description
UN-No.(DOT)
Proper Shipping Name (DOT)

Class (DOT) Packing group (DOT) Hazard labels (DOT) : UN3082 Environmentally hazardous substances, liquid, n.o.s. (Ethylene Glycol), 9, III : UN3082

- Environmontally baza
- : Environmentally hazardous substances, liquid, n.o.s.
- Ethylene Glycol
- : 9 Class 9 Miscellaneous hazardous material 49 CFR 173.140
- : III Minor Danger
- : 9 Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Symbols	:	G - Identifies PSN requiring a technical name
DOT Packaging Exceptions (49 CFR 173.xxx)	:	155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	No limit
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	:	No supplementary information available.

### Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Transport by sea In accordance with IMDG / IMO	
Proper Shipping Name (IMDG)	: Not regulated by IMDG (in quantites under 5,000 lbs in any one inner package)
Air transport	

In accordance with IATA / ICAO

Proper Shipping Name (IATA)

: Not regulated by IATA (in quantites under 5,000 lbs in any one inner package)

### SECTION 15: Regulatory information

15.1. US Federal regulations

Blue Mountain Professional Long Life Concentrate Antifreeze and Coolant		
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed	
denatonium benzoate (3734-33-6)		
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313			
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
CERCLA RQ	5000 lb(s)		
SARA Section 311/312 Hazard Classes	Refer to Section 2 for the OSHA hazard classification Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.		
SARA Section 313 - Emission Reporting	Ethylene glycol is subject to Form R Reporting requirements.		
diethylene glycol (111-46-6)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
water (7732-18-5)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
potassium 2-ethylhexanoate (3164-85-0)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
sodium 2-ethylhexanoate (19766-89-3)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			

### 15.2. International regulations

### CANADA

Blue Mountain Professional Long Life Concentrate Antifreeze and Coolant	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

	sodium 2-ethylhexanoate (19766-89-3)	
--	--------------------------------------	--

Listed on the Canadian DSL (Domestic Substances List)

### 15.3. US State regulations

**WARNING**:

This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ethylene glycol (107-21-1)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)	
No	Yes	No	No		(ingested) 8,700 (oral) µg/day	

ethylene glycol (107-21-1)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		
U.S Pennsylvania - RTK (Right to Know) List		
diethylene glycol (111-46-6)		
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		

### **SECTION 16: Other information**

Revision date

: 01/01/2024

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-statements:

riekt of fi-statements.	
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



### SDS GHS US (GHS HazCom 2012) OWI 1

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC as to the data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.