

PEAK[®]

ANTIFREEZE + COOLANT

dexcool[™]
GM APPROVED

FOR ALL
GM
VEHICLES
1995 & NEWER

5 YEARS / 150,000 MILES*

DESCRIPTION

PEAK[®] DEX-COOL[®] Antifreeze + Coolant is a GM-approved ethylene glycol based premium coolant that can be used in all GM vehicles 1995 and newer. **PEAK[®] DEX-COOL[®] Antifreeze + Coolant** is a factory-approved technology that contains a well-balanced mix of Organic Acid Technology (OAT) and corrosion inhibitors for complete protection of modern, high-performance GM vehicle engines. It is compatible for use with other extended-life coolants and is free of silicate, borate, phosphate, nitrite, and amines. **PEAK[®] DEX-COOL[®] Antifreeze + Coolant** guarantees maximum cooling system performance for up to 5 years/150,000 miles*.

FEATURES & BENEFITS

- Designed for use in all GM vehicles 1995 and newer requiring an orange organic acid technology (OAT) coolant
- Provides protection against damaging rust and corrosion for all cooling system metals, including aluminum
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Free of amines, phosphate, borate, nitrite and silicate
- Meets the performance requirements of ASTM D3306, D4985 and GMW3420, GM6277M
- Service life of up to 5 years/150,000* miles with a complete cooling system flush and fill

APPLICATIONS

PEAK[®] DEX-COOL[®] Antifreeze + Coolant is designed for use in all GM passenger cars, SUVs and light/medium duty trucks 1995 and newer.

Best performance is achieved when a complete flush & fill is performed using **PEAK[®] DEX-COOL[®] Antifreeze + Coolant**.

*See warranty details at PEAKGuarantee.com



FREEZE/BOIL PROTECTION CHART

PROTECTION		
Coolant/Water Ratio	PROTECTS FROM	
	Freezing Down to	Boiling Up to ^Δ
40/60	-13°F (-25°C)	260°F (127°C)
50/50	-34°F (-37°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)

Provides corrosion protection when diluted by volume to a minimum of 33% coolant concentration.

50/50 Prediluted: For optimum performance coolant concentration should be maintained at 50% by volume.

Concentrate: For optimum performance coolant concentration should be maintained between 40-60% by volume.



Available in both 50/50 Prediluted and Concentrate

PEAK[®]

ANTIFREEZE + COOLANT

dexcool[™]
GM APPROVED

FOR ALL
GM
VEHICLES
1995 & NEWER

PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Orange	Orange	Distinctive
pH, 50 vol %	D1287	8.3	8.3	7.5-11.0
Specific gravity	D1122	1.113	1.077	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °F (°C)	D1120	325 (162.8)	229 (109)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-37.8 (-38.8)	-34 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PDC0B3

1 Gallon Bottle
0-74804-07591-5

6/1 Gallon Case
0-74804-17591-2

PDC0B1

55 Gallon Drum
0-74804-07666-0



50/50 PREDILUTED

PDCB53

1 Gallon Bottle
0-74804-07592-2

6/1 Gallon Case
0-74804-17592-9

PDCB51

55 Gallon Drum
0-74804-07667-7

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PDC0B3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,217
PDCB53	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	58	36	20	2,145
PDC0B1	Drum	55 gal	23.5" dia. x 34.5" H	545	4	20	2,230
PDCB51	Drum	55 gal	23.5" dia. x 34.5" H	545	4	20	2,620

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK[®] DEX-COOL[®] Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK[®] DEX-COOL[®] Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

PEAK[®] DEX-COOL[®] Concentrate SDS ID: 115007

PEAK[®] DEX-COOL[®] 50/50 Prediluted SDS ID: 115006

Old World Industries, LLC.
Northbrook, IL 60062 • 800-323-5440
Peakauto.com

To order, please call
Old World Industries Customer Service at
1-800-323-8755



Old World Industries, Northbrook, IL 60062 • (800) 283-7234
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2023 Old World Industries. All Rights Reserved.
PEAK and PEAK Mountain Graphic are trademarks of Old World Industries.
DEX-COOL[®] and the dex-cool[™] logo are trademarks of GENERAL MOTORS, LLC and used under license. Old World Industries. License Identification Number DC-21-7

11-14-22