



DESCRIPTION:

PEAK FULL SYNTHETIC EUROPEAN FORMULA MOTOR OILS deliver the highest level of engine protection available, even under severe operating conditions. They are formulated using premium synthetic base oil and engineered to meet the stringent high performance requirements of European passenger car and light duty diesel vehicles.

BENEFITS:

- Delivers dependable long-term performance for the extended drain intervals set by all major automakers including: Audi, BMW, Mercedes Benz, Opel, Porsche, Volkswagen
- Provides outstanding protection in high RPM, hot running engines
- Specially designed to prevent sludge and varnish deposits for reduced oil consumption, extended engine life, and maximum overall performance resulting in a clean engine
- Designed for newer vehicle emission control systems
- Meets industry and vehicle manufacturer requirements for long life protection of gasoline vehicle catalytic converters

APPLICATION:

EURO 5W-30

APPROVED

- API SL

MEETS PERFORMANCE

- ACEA A5/B5-10
- BMW LL-01
- MERCEDES BENZ 229.5, 229.3
- OPEL GM-LL-B-025
- RENAULT 0700
- VOLKSWAGEN 502 00, 505 00

EURO 5W-40

APPROVED

- API SN

MEETS PERFORMANCE

- ACEA A3/B4-12
- BMW LL-01
- MERCEDES BENZ 229.5, 229.3
- OPEL GM-LL-B-025
- PORSCHE A40
- PSA B71 2296
- RENAULT 0700 & 0710
- VOLKSWAGEN 502 00, 505 00

May be used in select diesel engine specifications listed above.
Always follow vehicle manual recommendations.



SHIPPING INFORMATION:

Pack	6/1 Quart	Bag in a Box
Unit Weight (lbs.)	2.0	43
Case/Pallet Weight*	12.3/1,973*	-/1856*
Units per Pallet	936	42
Cases per Pallet	156	-
Units per Truck	20,592	924
Cases/Pallets per Truck	3,432/22	-/22
Case Size (inches)	9.5 x 7.6 x 9.6	19 x 13 x 7.25
Cases per row/Rows high	26/6	7/6
Pallet Size (inches)	48 x 40 x 61.4	48 x 40 x 72

(*) Including pallet weight of 50lbs.

PRODUCT INFORMATION:

	EURO 5W-30	EURO 5W-40		EURO 5W-30	EURO 5W-40
Test (Method)	API Service: SL	SN	Quart Part Number	-	P4MSE576
API Gravity (ASTM D287)	34.69	33.98	Bulk Part Number	-	P4ME50
Specific Gravity			Bag in a Box Part Number	P3ME5BX6	P4ME5BX6
@ 60°F (15.6°C) (ASTM D4052)	0.8514	0.8551			
Viscosity			Quart UPC Code	-	0-74804-05476-7
'@ 40 °C, cSt (ASTM D445)	62	77.27	Quart Case UPC Code	-	0-74804-15476-4
'@ 100 °C, cSt (ASTM D445)	10.6	13.18	Quart Case SCC-14 Code	-	1-00-74804-05476-4
Viscosity Index (ASTM D2270)	164	173	Bag in a Box UPC Code	0-74804-06220-5	0-74804-06221-2
Pour Point °C (°F) (ASTM D5950)	-40°C (-40°F)	-45°C (-49°F)			
Noack Volatility, % loss (ASTM D6375)	10	10			
Flash Point °C (°F)	231 (448)	-			