



# Blue DEF<sup>®</sup>

DIESEL EXHAUST FLUID

## DESCRIPTION

PEAK<sup>®</sup> BlueDEF<sup>®</sup> is a mixture of 32.5% high purity synthetic urea and 67.5% deionized water that is used in Selective Catalytic Reduction (SCR) systems on diesel engines. DEF is the primary ingredient used to help convert NOx to harmless nitrogen and water. BlueDEF<sup>®</sup> is stable, colorless, non-flammable, and is classified as minimum risk for transportation. BlueDEF<sup>®</sup> conforms to the ISO-22241-1 specification for DEF, is API registered and meets or exceeds OEM specifications.

PEAK<sup>®</sup> BlueDEF<sup>®</sup>'s exclusive TRIPLE-FILTERED formula ensures the highest product purity. Every batch is guaranteed pure.

## MATERIALS RECOMMENDED FOR USE WITH BLUEDEF<sup>®</sup>

- Highly alloyed austenitic Cr-Ni-Mo -steels or stainless steel 304 (S30 4 00), 304L (S30403), 316 (S31600) AND 31 6L (S31603) in accordance with ASTM A240, ASTM A276, and ASTM A312
- Titanium
- Ni-Mo-Cr-Mn-Cu-Si-Fe Alloys, e.g. Hastelloy c/c-276
- Polypropylene, free of additives
- Polyethylene, free of additives
- Perfluoroalkoxyl Alkane (PFA), free of additives
- Polyfluoroethylene (PFE), free of additives
- Polyvinylidene fluoride (PVDF), free of additives
- Polytetrafluoroethylene (PTFE), free of additives
- Copolymers of Vinylidene fluoride and Hexafluoropropylene, free of additives

## MATERIALS NOT RECOMMENDED FOR USE WITH BLUEDEF<sup>®</sup>

- Carbon Steels, Zinc Coated Carbon Steels, and Mild Iron
- Non ferrous metals and alloys: Copper, Copper Alloys, Zinc, Lead
- Solders containing Lead, Silver, Zinc, or Copper
- Aluminum, Aluminum Alloys
- Magnesium, Magnesium Alloys
- Plastics or metals coated with Nickel



# GUARANTEED PURE

AMERICA'S  
**#1**  
DEF BRAND



## FEATURES & BENEFITS

- PEAK<sup>®</sup> BlueDEF<sup>®</sup>'s exclusive TRIPLE-FILTERED formula ensures the highest product purity
- America's #1 brand of Diesel Exhaust Fluid
- Purity Guarantee is our assurance the DEF you are purchasing has been tested to meet or exceed the strictest OEM standards
- Conforms to the ISO-22241-1 specification for DEF, and is an American Petroleum Institute (API) certified diesel exhaust fluid
- Compatible with all diesel SCR systems
- Non-flammable formula makes handling safe and easy



DEF ISO 22241

AMERICA'S  
**#1**  
DEF BRAND



## HANDLING AND STORAGE

The shelf life of DEF is directly related to the temperature at which it is stored. Failure to store below 86°F (30°C) may significantly reduce shelf life and effectiveness of product. If BlueDEF® freezes, its efficacy will not be effected upon thawing. To maintain the purity of DEF and not harm the SCR Catalyst System care must be taken regarding the material of construction for all items that come in contact with the DEF solution. Included from the ISO-22241-1 standards are the recommended and not recommended materials for contact with DEF.




## PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point</b>	>212° F
<b>Freezing Point</b>	12° F
<b>Pounds/Gallons</b>	9.09
<b>Specific Gravity (Water=1)</b>	1.09
<b>Vapor Pressure (mm of Hg)</b>	Not applicable
<b>Vapor Density (Air=1)</b>	0.6 H2O >1
<b>Water Solubility</b>	100%
<b>Appearance</b>	Colorless, clear liquid
<b>Odor</b>	None to slight ammonia



DEF ISO 22241

## PACKAGING OPTIONS

	2.5 Gallon	55 Gallon Drum	330 Gallon Tote
			
<b>Part Number</b>	DEF002	DEF001	DEF330P
<b>UPC Code</b>	0-74804-03211-6	0-74804-03522-3	0-74804-03309-0
<b>Case SCC-14 Code</b>	1-00-74804-03211-6		
<b>Pack/Unit Case</b>	1 per case	522.5 lbs. (per drum)	
<b>Weight/Case</b>	22.75 lbs.	22.5" dia. x 35.5" high	3,148 lbs. (per tote)
<b>Case Dimensions</b>	9.5"W x 9.5"L x 10"H	4 (drums)	40"W x 48"L x 53"H
<b>Cases Per Pallet</b>	80	20	1 (tote)
<b>Pallets/Cases Per Truck</b>	22/1,760	80	14
<b>Units Per Truck</b>	1,760	42,822 lbs.	14
<b>Truckload Weight*</b>	41,140 lbs.	40"W x 48"L x 40.5"H	44,068 lbs.
<b>Pallet Size</b>	40"W x 48"L x 45"H	2,141 lbs.	40"W x 48"L x 53"H
<b>Pallet Weight*</b>	1,870 lbs.		3,148 lbs.
<b>Cases/Rows High</b>	20/4		

\*includes product and pallet weight



Distributed by Old World Industries, LLC. Northbrook, IL 60062 | phone 800.323.5440

©2024 Old World Industries, LLC. All Rights Reserved. BlueDEF® and BlueDEF® 8 Drop Graphic are trademarks of Old World Industries, LLC. API American Petroleum Institute Certified Diesel Exhaust Fluid Design is a registered trademark of the American Petroleum Institute Corporation.

[bluedef.com](http://bluedef.com)  
 @PEAKBlueDEF