

ALL VEHICLES

PEAK TITANIUM™

**GUARANTEED ULTIMATE PROTECTION
15+ YEARS / 500,000+ MILES***

DESCRIPTION

PEAK® TITANIUM's advanced formula contains a proprietary chemistry designed to clean component surfaces†, while also protecting against the formation of heat-insulating films or coatings that impair heat-transfer and are major contributors of lost coolant flow and overheating.

TITANIUM is free of 2-EHA, silicate, nitrite, borate and amines, ensuring maximum cooling system performance for 15+ years/500,000+ miles*. It is compatible for use with any color or type of antifreeze/coolant in the system.

FEATURES & BENEFITS

- Advanced formula, cleans and protects against rust and corrosion
- Specially formulated to deliver Guaranteed Lifetime Protection* against damaging scale and corrosion
- Protection demonstrated by earning a perfect 10 score in industry standard water pump protection test, ASTM D2809
- All vehicle formula is compatible with any color or type of antifreeze/coolant
- Meets the performance requirements of ASTM D6210, D3306 & D4985

APPLICATIONS

PEAK® TITANIUM™ Antifreeze + Coolant is designed for use in all North American, Asian and European passenger cars, SUVs, motorcycles and light/medium duty trucks, regardless of make, model or year.

Best performance is achieved when a complete flush & fill is performed using PEAK® TITANIUM™ Antifreeze + Coolant.

* 15+ years/500,000 miles guarantee when a complete cooling system flush and fill is performed and proper cooling system maintenance is followed. Always follow vehicle owner's manual for top-off requirements, change intervals and specified maintenance. See PEAKGuarantee.com for more details or call 1-800-323-5440.

† Designed to clean component surfaces for improved removal of post-braze flux residues from the surface of aluminum heat exchangers such as radiators & heater cores manufactured using the controlled atmosphere brazing (CAB) process. This enables improved passivation and protects against the formation of corrosion on metallic cooling system components.



PROTECTION CHART**	
FREEZE PROTECTION	-34°F (-36°C)
BOILOVER PROTECTION^Δ	265°F (129°C)
CORROSION PROTECTION	Protects All Cooling System Metals Meets ASTM D6210, D3306 & D4985

ΔUsing a 15 psig (103 kPa) pressure cap

**For optimum performance and corrosion protection, coolant concentration should be maintained at 50% by volume.



**Available in both 50/50 Prediluted
and Concentrate**

ALL VEHICLES

PEAK TITANIUM™

Properties	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Yellow	Yellow	Distinctive
pH	D1287	8.3, 50 vol %	8.3	7.5-11.0
Specific gravity	D1122	1.113	1.077	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³ , °F (°C)	D1120	325 (162.8)	229 (109)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-36.2 (-37.9)	-34 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 max ¹
Ash content, mass %	D1119	<5	<2.5	5 max ¹ /2.5 max ²
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PKTOD3

1 Gallon Bottle
0-74804-08011-7

6/1 Gallon Case
0-74804-18011-4

PKTOD1
55 Gallon Drum
0-74804-08012-4

PKTOD8
275 Gallon Tote
0-74804-08013-1



50/50 PREDILUTED

PKT5D3

1 Gallon Bottle
0-74804-08008-7

6/1 Gallon Case
0-74804-18008-4

PKT5D1
55 Gallon Drum
0-74804-08009-4

PKT5D8
275 Gallon Tote
0-74804-08010-0

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PKTOD3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,217
PKT5D3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	58	36	20	2,145
PKTOD1	Drum	55 gal	23.5" dia. x 34.5" H	525	4	20	2,157
PKT5D1	Drum	55 gal	23.5" dia. x 34.5" H	553	4	20	2,269
PKTOB8	Tote	275 gal	40" L x 40" W x 46" H	2,679	1	16	2,679
PKTB58	Tote	275 gal	40" L x 40" W x 46" H	2,503	1	16	2,503

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK® TITANIUM™ Antifreeze + Coolant can be stored in original container for 3-5 years at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK® TITANIUM™ Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from peakauto.com. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC.
Northbrook, IL 60062
Peakauto.com

To order, please call Old World Industries Customer Service
at 1-800-323-5440

For Technical Product Support, please call
1-800-477-5847



Manufactured for Old World Industries, LLC, Northbrook, IL 60062 (800) 289-7234
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT
©2024 Old World Industries, LLC All Rights Reserved. PEAK, PEAK G Mountain
Graphic and TITANIUM are trademarks of Old World Industries, LLC

05-02-24