

900mm ActiveSmart™ Slide-in Refrigerator

Model no:

RS90AU1 (with Stainless Steel Door panels PART NO. RD90U)

Product Dimensions	mm
Overall height of fridge	1798
® Overall width of fridge	896
© Depth of fridge front panels (excl. handles)	18
Overall depth of fridge (excl. front door panels)	606
E Height from bottom datum to top of toekick	100
© Depth of toekick measured from front of door	50
© Height of bottom drawer panel	598
H Height of top door panels	1096
① Height from bottom datum to top of drawer panel	698
Gap between top and bottom door panels	4
Height from bottom datum to centre of bottom handle	626
① Width of bottom handle	727
M Thickness of handles	15
N Height from bottom datum to bottom of top handle	767
Height from bottom datum to top of top handle	1494
P Height of top handles	727
Distance from centre of fridge to the centre of top handles	67
® Depth of handle (measured from front of door)	42
Depth of door (widest opening) measured from front of door	445
Depth of drawer (open) measured from front of drawer, including handle	400
Depth of drawer (open) measured from front of drawer, excluding handle	360
Minimum door clearance to adjacent wall (115° - full internal access)	300
Minimum Clearances	mm
Minimum cabinetry gap clearance from edge of product	4
Overall height of cavity	1800
Overall width of cavity	
when adjoining cabinetry can share 4mm door gap	900
when adjoining cabinetry cannot share 4mm door gap	904
Overall depth of cavity	650

DATE: 06.04.2015

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ± 2 mm (3/32"). Please read the installation manual for detailed information on installing the product. www.fisherpaykel.com

