

# FISHER & PAYKEL

## DATA SHEET

30" Integrated Column Fridge / Freezer

### Model nos:

RS3084SR1 / RS3084SRK1 / RS3084FRJ1 / RS3084FRJK1 with Stainless Steel Door panel RD3084R4D, Handle AHD3-RD84 and Stainless Steel Toekick Panel AKRS30041 NOTE: Left hand hinge model is a mirrored version of image shown. RS3084SL1 / RS3084SLK1 / RS3084FLJ1 / RS3084FLJK1 with Stainless Steel Door panel RD3084L4D, Handle AHD3-RD84 and Stainless Steel Toekick Panel AKRS30041 (refer page 2 for metric measurements) Product Dimensions Overall height of product
 B Overall width of product 29 3/4" © Depth of product front panels (excl. handles)

in

84″

3/4"

Overall depth of product (excl. front door panels)	24"
(E) Height from bottom datum to bottom of door	4"
© Depth of toekick (excl. door front and toekick panels)	2 11/16"- 4"
© Height of door panel	79 7/8"
(ii) Width of door panel	29 3/4"
<ol> <li>Height from bottom datum to bottom of handle</li> </ol>	32 1/8"
③ Height from bottom datum to top of handle	65 11/16"
© Thickness of handles	5/8"
© Distance from side of fridge to the center of handle	2 1/2"
Depth of handle (measured from front of door)	1 5/8"

Clearance Dimensions	in
Minimum cabinetry gap clearance from edge of door panel	1/8"
Overall height of cavity	84"
Overall width of cavity	30"
Minimum depth of cavity	25″
Minimum door clearance to adjacent wall (115° - full internal access)	16 1/2"
Minimum door clearance at 90° open, measured from front of door	32"

INDICATES CAVITY CLEARANCES ------INDICATES PRODUCT DATUM -----

#### DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



# FISHER & PAYKEL

## DATA SHEET

30" Integrated Column Fridge / Freezer

### Model nos:

RS3084SR1 / RS3084SRK1 / RS3084FRJ1 / RS3084FRJK1 with Stainless Steel Door panel RD3084R4D, Handle AHD3-RD84 and Stainless Steel Toekick Panel AKRS30041 NOTE: Left hand hinge model is a mirrored version of image shown. RS3084SL1 / RS3084SLK1 / RS3084FLJ1 / RS3084FLJK1 with Stainless Steel Door panel RD3084L4D, Handle AHD3-RD84 and Stainless Steel Toekick Panel AKRS30041 (refer page 1 for imperial measurements) Product Dimensions mm Overall height of product
 2134 B Overall width of product 756 C D E E 6

© Depth of product front panels (excl. handles)	19
Overall depth of product (excl. front door panels)	610
© Height from bottom datum to bottom of door	102
© Depth of toekick (excl. door front and toekick panels)	68 - 101
© Height of door panel	2029
(ii) Width of door panel	756
③ Height from bottom datum to bottom of handle	816
④ Height from bottom datum to top of handle	1668
© Thickness of handles	16
© Distance from side of fridge to the centre of handle	64
Depth of handle (measured from front of door)	41

Clearance Dimensions	mm
Minimum cabinetry gap clearance from edge of door panel	3
Overall height of cavity	2134
Overall width of cavity	762
Minimum depth of cavity	635
Minimum door clearance to adjacent wall (115° - full internal access)	419
Minimum door clearance at 90° open, measured from front of door	813

#### DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com