

PLANNING GUIDE

PLANNING GUIDE
762mm COLUMN REFRIGERATOR
& FREEZER
SINGLE PRODUCT INSTALL

—
10/10/2018

FISHER & PAYKEL

CONTENTS

762mm Integrated Column Refrigerator and Freezer with Stainless Steel Door panels

Model Nos:

Right Hinge Fridge RS7621SRK1

Right Hinge Freezer RS7621FLJK1

Stainless Steel Door Panel RD7621R10D

Handle AHD3-RD21

Stainless Steel Toekick Panel AKRS07610

Left Hinge Fridge RS7621SLK1

Left Hinge Freezer RS7621FLJK1

Stainless Steel Door Panel RD7621L10D

Handle AHD3-RD21

Stainless Steel Toekick Panel AKRS07610

Product & Cavity Dimensions	3	page
-----------------------------	---	------

Door Opening & Clearance Dimensions	4
-------------------------------------	---

Hinge Range of Movement	7
-------------------------	---

Cavity Preparation	9
--------------------	---

Max Distance of Hose & Cord	12
-----------------------------	----

762mm Integrated Column Refrigerator and Freezer for Custom Door panels

Model Nos:

Right Hinge Fridge RS7621SRK1

Right Hinge Freezer RS7621FRJK1

Left Hinge Fridge RS7621SRK1

Left Hinge Freezer RS7621FLJK1

Product & Cavity Dimensions	5	page
-----------------------------	---	------

Product & Cavity Dimensions	5
-----------------------------	---

Door Opening & Clearance Dimensions	6
-------------------------------------	---

Hinge Range of Movement	7
-------------------------	---

Custom Panel Dimensions	8
-------------------------	---

Cavity Preparation	9
--------------------	---






Custom Panel Preparation	11
--------------------------	----

Max Distance of Hose & Cord	12
-----------------------------	----

Note: This guide shows specifications for right hinge models.
For left hinge models, door related specifications are mirrored.

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS 762mm Integrated Column Fridge / Freezer



Model nos:

RS7621SRK1 / RS7621FRJK1
with Stainless Steel Door panel RD7621R10D, Handle AHD3-RD21
and Stainless Steel Toe Kick Panel AKRS07610

NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1
with Stainless Steel Door panel RD7621L10D, Handle AHD3-RD21
and Stainless Steel Toe Kick Panel AKRS07610

Cavity Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	762
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity	650

Product Dimensions	mm
Ⓐ Overall height of product	2134
Ⓑ Overall width of product	756
Ⓕ Minimum cabinetry gap clearance from edge of door panel	3
Ⓒ Overall depth of product (excl. door front panel)	610
Ⓓ Height of door front panel	2029
Ⓔ Depth of door front panel (excludes handles)	19
Ⓙ Height of toe kick*	102
Ⓚ Depth of toe kick (excl. door front and toe kick panels)	68 - 101

*Standard toe kick height is 102mm with the optional stainless door panel.

INDICATES CAVITY CLEARANCES - - - - -

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

DOOR OPENING CLEARANCE DIMENSIONS 762mm Integrated Column Fridge / Freezer

Model nos:


RS7621SRK1 / RS7621FRJK1
with Stainless Steel Door panel RD7621R10D
and Handle AHD3-RD21

NOTE: Left hand hinge model is a mirrored version of image shown.


RS7621SLK1 / RS7621FLJK1
with Stainless Steel Door panel RD7621L10D
and Handle AHD3-RD21

Door Opening & Clearance Dimensions	mm
Ⓐ Depth of door (90° open) measured from front of door	813
Ⓑ Minimum door clearance to adjacent wall* (115° - full internal access)	419
Ⓒ Minimum door clearance to adjacent wall* (90° - reduced internal access)	110

* Measured from front cabinetry edge.



90° DOOR OPENING




115° DOOR OPENING
[FULL ROTATION]

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS 762mm Integrated Column Fridge / Freezer



Model nos:

RS7621SRK1 / RS7621FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1

Cavity Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	762
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity*	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity*	650

* Assumes a door panel thickness of 19mm.

Total front panel width with required gaps at sides = 762mm
(Refer custom panel dimensions - panel width + 2 x Ⓔ cabinetry gaps).

Product Dimensions	mm
Ⓐ Overall height of product	2134
Ⓑ Overall width of product	756
Ⓔ Minimum cabinetry gap clearance from edge of custom panels**	3
Ⓒ Overall depth of product (excl. door front panel)	610
Ⓘ Height of toekick**	50 - 152
Ⓛ Width of toekick**	759
Ⓜ Depth of toekick** (excl. door front and toekick panels)	68 - 101

** For custom panel dimensions refer to page 8.

Door panel and custom toekick panel to be manufactured and fitted by cabinetmaker. Door panel thickness min 16mm - max 25mm

INDICATES CAVITY CLEARANCES - - - - -

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

DOOR OPENING CLEARANCE DIMENSIONS 762mm Integrated Column Fridge / Freezer

Model nos:

RS7621SRK1 / RS7621FRJK1


NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1


Door Opening & Clearance Dimensions	mm
Ⓐ Depth of door (90° open) measured from front of door	813
Ⓑ Minimum door clearance** to adjacent wall* (115° - full internal access)	419
Ⓒ Minimum door clearance** to adjacent wall* (90° - reduced internal access)*	110

* Does not include the custom door panels or handles to be manufactured and fitted by cabinetmaker.

** Measured from front cabinetry edge.



90° DOOR OPENING



115° DOOR OPENING
[FULL ROTATION]

DATE: **10.10.2018**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com


FISHER & PAYKEL

CUSTOM PANEL PREPARATION - HINGE 762mm Integrated Column Fridge / Freezer

Model nos:
RS7621SRK1 / RS7621FRJK1
NOTE: Left hand hinge model is a mirrored version of image shown.
RS7621SLK1 / RS7621FLJK1

Dwg & Dxf Files
Dwg and Dxf files of the panel preparation are available within the download folder for this product and can be found on <http://thekitchentools.fisherpaykel.com>

Door Hinge - Hettich K05




DATE: **10.10.2018**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CUSTOM PANEL DIMENSIONS 762mm Integrated Column Fridge / Freezer



Model nos:

RS7621SLK1 / RS7621FLJK1

NOTE: Right hand hinge model is a mirrored version of image shown.

RS7621SRK1 / RS7621FRJK1

Custom Panel Dimensions*	mm
Ⓐ Height of door panel	1978 - 2080
Ⓑ Width of door panel - single install Width of door panel - dual install	756 757.5
Ⓒ Maximum depth of custom panel	min 16 max 25
Ⓓ Height of toekick panel**	50 - 152
Ⓔ Width of toekick panel	762
Maximum weight of door panel***	30kg

* Custom door panels, toekick and handles to be manufactured / fitted by cabinetmaker.

** The bottom grille can be reduced to allow for a higher toekick. Adjust the height of the door panel accordingly.



*** Includes weight of handle.

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CAVITY PREPARATION - FRAMELESS 762mm Integrated Column Fridge / Freezer



ISO VIEW OF CAVITY

Model nos:

RS7621SRK1 / RS7621FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Minimum Cavity Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	762
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity*	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity*	650
Minimum required finished return	102

*Assumes a door panel depth of 19mm.

Electrical / Plumbing Supply Dimensions	mm
Ⓓ Overall height of supply area	229
Ⓔ Overall depth of supply area	25
Ⓕ Width of notch in supply area (both sides)	13
Ⓖ Height of sides of supply area (both sides)	127

Specifications

Electrical

Supply	115 VAC, 60 Hz
Service	10 amp circuit

Plumbing

Supply	1/4" (6mm) comp. stainless steel braided hose with adaptor
Pressure	min 150 kPa (22 psi) max 827 kPa (120 psi) @ 20°C (68°F)



NOTE: Connections may be located in an adjacent cabinet to either side of the fridge.

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CAVITY PREPARATION - FRAMED 762mm Integrated Column Fridge / Freezer



ISO VIEW OF CAVITY

Model nos:

RS7621SRK1 / RS7621FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Minimum Cavity Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	762
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity*	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity*	650
Minimum required finished return	102

*Assumes a door panel depth of 19mm.

Electrical / Plumbing Supply Dimensions	mm
Ⓓ Overall height of supply area	229
Ⓔ Overall depth of supply area	25
Ⓕ Width of notch in supply area (both sides)	13
Ⓖ Height of sides of supply area (both sides)	127


Specifications	
Electrical	
Supply	115 VAC, 60 Hz
Service	10 amp circuit
Plumbing	
Supply	1/4" (6mm) comp. stainless steel braided hose with adaptor
Pressure	min 150 kPa (22 psi) max 827 kPa (120 psi) @ 20°C (68°F)

NOTE: Connections may be located in an adjacent cabinet to either side of the fridge.

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

762MM
COLUMN DOOR PANEL
REAR VIEW



FISHER & PAYKEL

CUSTOM PANEL PREPARATION 762mm Integrated Column Fridge / Freezer

Model nos:

RS7621SRK1 / RS7621FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS7621SLK1 / RS7621FLJK1

Custom Panel Preparation

Dimensions are shown in millimetres (mm).

Dimensions apply for the preparation and installation of custom panels

Handles

Ensure handle screw heads are countersunk into back of panel to avoid interfering with hanging bracket, and clear of side brackets as indicated.

Dwg & Dxf Files

Dwg and Dxf files of the panel preparation are available within the download folder for this product and can be found on

<http://thekitchentools.fisherpaykel.com>

DATE: **10.10.2018**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


POWER AND WATER CONNECTIONS 762mm Integrated Column Fridge / Freezer

Model nos:

RS7621SRK1 / RS7621FRJK1

RS7621SLK1 / RS7621FLJK1

* Water inlets apply to freezers only



DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL