

PLANNING GUIDE

PLANNING GUIDE

INTEGRATED REFRIGERATOR FREEZER, 24"

INTEGRATED TRIPLE ZONE REFRIGERATOR, 24"

INTEGRATED TRIPLE ZONE FREEZER, 24"

JANUARY 2023

FISHER & PAYKEL

CONTENTS

Integrated Refrigerator Freezer, 24"

Dual Door Refrigerator

Model Nos:

Right Hinge Refrigerator & Freezer

Integrated Refrigerator Freezer - RS2474BRU1

Left hand hinge can be achieved using supplied parts

Integrated Triple Zone Refrigerator, 24"

Integrated Triple Zone Freezer, 24"

Single Door Refrigerator or Freezer

Model Nos:

Right Hinge Refrigerator

Integrated Triple Zone Refrigerator -RS2474S3RH1

Left hand hinge can be achieved using supplied parts

Left Hinge Freezer


Integrated Triple Zone Freezer - RS2474F3LJ1

Right hand hinge can be achieved using supplied parts

	page
Purchase Decision	3
Product & Cavity Dimensions	5 - 6
Door Opening & Clearance Dimensions	7
Hinge Range of Movement	8
Custom Panel Dimension	9
Custom Panel Flexibility	10
Gap Consideration	11
Custom Door Panel Preperation	12
Cavity Preparation	13
Max Distance of Hose & Cord	14
Multiple Installation	15 - 16
Handle Data Sheets	17 - 20

	page
Purchase Decision	3
Product & Cavity Dimensions	22 -23
Door Opening & Clearance Dimensions	24
Hinge Range of Movement	25
Custom Panel Dimensions	26
Custom Panel Preparation	27
Cavity Preparation (Frameless and Framed)	28
Max Distance of Hose & Cord	29
Multiple Installations	30 - 31
Handle Data Sheets	32 -35

PURCHASE DECISION REFRIGERATOR & FREEZER COMBINATION, REFRIGERATION AND FREEZER 24"



PRODUCT & DOOR OPENING	INTERIOR ZONES	ICE & WATER	PANEL STYLE*	HANDLES	STAINLESS STEEL TOE KICK*	JOINER KIT*
	Refrigerator Freezer	3 Temperature Zone				
	Refrigerator		Left Hinge			
	Freezer		Right Hinge			
Refrigerator Freezer	RS2474 BRU1*	*Ice & Water	Refrigerator Freezer Stainless Steel Panels**	① Square Fine Handle Aluminium	867869A	Single Installation
Refrigerator	RS2474S3RH1**	**Water	Refrigerator Stainless Steel Panel***	② Square Fine Handle Black	Dual Toe Kick	Dual Installation*
Freezer	RS2474F3LJ1***	***Ice	Freezer Stainless Steel Panel***	③ Round Handle	Triple Toe Kick	Triple Installation*
				④ Classic Handle		
				⑤ Professional Round Flush		
			ASSISTED OPENING			*1 joiner kit included with the following Freezer models:
			Refrigerator Freezer available Q1 2024			RS2474F3LJ1
			Refrigerator available Q1 2024			
			Freezer available Q1 2024			

*Custom door panels to be manufactured and fitted by cabinetmaker
 **Two panels supplied in panel kit
 ***One panel supplied in panel kit

*Two handles supplied in handle kit
 **One handle kit supplied in handle kit

*Toe kick to be manufactured and fitted by cabinet maker

*Each joiner kit contains 4 brackets and one trim

Integrated Refrigerator Freezer, 60cm

FISHER & PAYKEL


PRODUCT & CAVITY DIMENSIONS Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU
Integrated Freezer
Stainless Steel Panels RD2474BR
Handle Kit AHD5RDSF
Stainless Steel Toe Kick Panel AKRS06010

NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.



VERTICAL GAP
CLEARANCE FROM SIDE
OF DOOR PANEL



Product Dimensions	inch
Ⓐ Overall height of product	74
Ⓑ Overall width of product	23 5/16
Ⓒ Overall depth of product (excl. front door panels)	22 13/16
Ⓓ Height from top of top door panel to floor	73 7/8
Ⓔ Height from top of bottom door panel to floor	34 3/8
Ⓕ Minimum cabinetry clearance from side of door panel	5/32
Ⓖ Minimum cabinetry clearance from top of door panel	1/8
Ⓗ Height of top door panel	39 13/32
Ⓘ Height of bottom door panel	30 3/8
⓵ Depth of door panels	3/4
⓷ Gap between door panels	1/8
⓸ Height from floor to bottom of bottom door panel	4
⓹ Depth of toe kick (excl. front door and toe kick panels)	2 - 4

Cavity Dimensions	inch
Ⓝ Overall height of cavity	74
Ⓖ Overall width of cavity	23 5/8
Ⓒ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16

Note: Product shown installed on the floor. Slide into cabinetry position.

Alternatively can be installed on a plinth. Adjust your cavity height accordingly.

INDICATES CAVITY CLEARANCES (dashed red line)
INDICATES PRODUCT DATUM (dashed blue line)

DATE: **9.1.2023** 90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU1
Integrated Dual and Triple Zone Refrigerator
Custom Panel

NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.



Product Dimensions	inch
Ⓐ Overall height of product	74
Ⓑ Overall width of product	23 5/16
Ⓒ Overall depth of product	22 13/16
Ⓓ Minimum cabinetry clearance from side of door panels*	5/32
Ⓔ Minimum cabinetry clearance from top of door panel*	1/8
Ⓕ Depth of door panels*	5/8 - 3/4
Ⓖ Height of toe kick panel*	4
Ⓗ Depth of toe kick (excl. front door and toe kick panels*)	2 - 4

Cavity Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	23 5/8
Ⓒ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16

Note: Product shown installed on the floor. Slide into cabinetry position.
Alternatively can be installed on a plinth. Adjust your cavity height accordingly.


For custom panel dimensions refer to page 9.
*Custom door panels and toe kick panel to be manufactured and fitted by cabinetmaker.

INDICATES CAVITY CLEARANCES (Red dashed line)
INDICATES PRODUCT DATUM (Blue dashed line)


DATE: 9.1.2023 90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com


CLEARANCES



CONFIGURATIONS




HINGE TO HINGE
Both doors open at the same time
- requires space between models




HINGE TO HINGE
Only allows a single door open at a time

DUAL INSTALL



TRIPLE INSTALL



FISHER & PAYKEL

DOOR OPENINGS & CLEARANCE DIMENSIONS Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"
Stainless Steel Panels RD2474BR
Handle Kit AHD5RDSF
Stainless Steel Toe Kick Panel AKRS06010

NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

Clearance Dimensions	inch
Ⓐ Depth of door (90° open, measured from front of cabinetry)	23 5/8
Ⓑ Minimum door clearance to adjacent wall (90° - reduced internal access)* **	3 1/8
Ⓒ Minimum door clearance to adjacent wall (115° - full internal access)* **	10 3/4
Ⓓ Minimum cabinetry clearance from side of door panel to adjacent wall (non hinge side)	5/32
Ⓔ Minimum clearance between products when opening hinge to hinge. Allowing both doors to open at the same time**	4

Minimum Door Clearance (Vertical Gap)	inch
Ⓕ Dual Install: Stainless steel door panels (gaps equalized during installation)	3/16
Custom panels (width of custom panel increased to maintain 4mm gap across multiple products)***	5/32
Ⓖ Triple Install: Stainless steel door panels (gaps equalized during installation)	1/4
Custom panels (width of custom panel increased to maintain 4mm gap across multiple products)***	5/32

*Use hinge limiting pin to restrict door opening to 90° where necessary.
**Minimum dimensions shown are for the contemporary handle kit AHD5RDSF. Custom panel and handle details need to be taken into account.
***Refer to Custom Panel Dimensions and Multiple Install pages for further details.

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: **9.1.2023** **90003015A**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CUSTOM PANEL PREPARATION - HINGE Integrated Refrigerator Freezer, 24"


Model nos:
RS2474BRU1
Integrated Refrigerator Freezer, 24"

NOTE: Left hand hinge model is a mirrored version of image shown.

Dwg & Dxf Files

Dwg and Dxf files of the panel preparation are available within the download folder for this product and can be found on.
<http://thekitchentools.fisherpaykel.com>

Door Hinge - Hettich K08



1 SQUARE = 1/16 INCH

DATE: 9.1.2023

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CUSTOM PANEL DIMENSIONS Integrated Refrigerator Freezer, 24"


Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"
Custom Panels

NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.


Custom Panel Dimensions	inch
Ⓐ Height of top door panel	39 13/32
Ⓑ Height of bottom door panel	28 7/16 - 33 3/4
Ⓒ Width of door panel: Single install	23 5/16
Dual install*	23 3/8
Triple install*	23 13/32
Ⓓ Depth of custom panel**	5/8 - 3/4
Ⓔ Gap between door panels	5/32
Ⓕ Height from floor to top of top door panel	73 7/8
Ⓖ Height from floor to bottom of top door panel	34 1/2
Ⓗ Height from floor to top of bottom door panel	34 3/8
Ⓙ Height from floor to bottom of bottom door panel***	9/16 - 5 15/16
Ⓚ Height of toe kick panel	4
Ⓛ Width of toe kick panel****	23 1/2
Maximum weight of top door panel*****	21lbs
Maximum weight of bottom door panel*****	20lbs

Custom door panels, handles and toe kick panel to be manufactured and fitted by cabinetmaker.

*For further details on multiple installation refer to page 16.
**At 3/4mm thickness, we recommend an edge radius of 1mm or more to avoid the possibility of panel clash when opening.
***The grille becomes visible at heights over 4".
****Toe kick can be continuous.
*****Includes weight of handle.



ISO VIEW



PROFILE VIEW



DATE: 9.1.2023

90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CUSTOM PANEL FLEXIBILITY Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"

Left hand hinge can be achieved with a converter kit (supplied).
Please refer to Installation Guide for details.



FRONT VIEW

SIDE VIEW



Custom Panel Dimensions	inch
Ⓐ Floor to top of of bottom panel (splitline height)	min 34 1/8 max 34 17/32
Ⓑ Floor to bottom of door panel	min 19/32 max 5 29/32
Ⓒ Bottom door panel height	min 28 1/4 max 33 15/16
Ⓓ Top panel height	min 39 1/4 max 39 5/8
Ⓔ Height from floor to top of door panel	73 7/8
Ⓕ Cavity height	74
Ⓖ Gap between panels	1/8

To be used when the cavity height is 74", dimensions will vary for other cavity heights.

To calculate bottom panel height (splitline height)
Ⓐ minus Ⓑ

To calculate top panel height
Ⓔ minus 1/8" minus Ⓓ

For bench heights above 34 17/32" with a 35 5/16" splitline can be achieved with a cavity height of 74 13/16"

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 9.1.2023 90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

GAP CONSIDERATION Integrated Refrigerator Freezer, 24" Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
RS2474BRU1
Integrated Refrigerator Freezer, 24"

RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer



IMPORTANT!
For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Product Stainless Steel Door Gaps	inch
Ⓐ Vertical gaps between doors	1/4
Ⓑ Horizontal gaps between doors	1/8
Ⓒ Vertical gaps between door and neighbouring cabinetry	5/32
Ⓓ Horizontal I gaps between door and neighbouring cabinetry	1/8

Product Custom Panel Door Gaps	inch
Ⓐ Vertical gaps between doors	5/32
Ⓑ Horizontal gaps between doors	1/8
Ⓒ Vertical gaps between door and neighbouring cabinetry	5/32
Ⓓ Horizontal gaps between door and neighbouring cabinetry	1/8

Dual Installation 1 Joiner Kit required - AJRS74LR.
Triple Installation 2 Joiner Kits required - AJRS74LR.
Freezer Model RS2474F3LJ1 include 1 Joiner Kit

DATE: **9.1.2023**

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ ($1/16''$). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

REAR VIEW

FISHER & PAYKEL

CUSTOM PANEL PREPARATION Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"

Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

Custom Panel Preparation

Dimensions are shown in inches ("").
Dimensions apply for the preparation and installation of custom panels.

Handles

Ensure handle screw heads are countersunk into back of panel to avoid interfering with hanging bracket, and clear of side brackets as indicated.


Dwg & Dxf Files

Dwg and Dxf files of the panel preparation can be downloaded from Trade Resources www.fisherpaykel.com

Template

A template for marking and drilling the holes is provided with the product.

TOP PANEL



BOTTOM PANEL


DATE: 9.1.2023

90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ ($1/16"$). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CAVITY PREPARATION Integrated Refrigerator Freezer, 24"



FINISHED RETURN
CAVITY SIDES & TOP



ALTERNATIVE AREA
ABOVE CAVITY FOR
ELEC / WATER CONNECTION

Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"

NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

IMPORTANT!
**For ease of installation, ensure cavity has consistent dimensions
top to bottom and left to right.**

Minimum Cavity Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	23 5/8
Ⓒ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16
Minimum required finished return	4

Electrical / Plumbing Supply Dimensions	inch
Ⓓ Overall height of supply routing area at rear of cavity	1 7/16
Overall width of supply routing area at rear of cavity	23 5/8
Ⓔ Overall depth of supply routing area at rear of cavity	13/16
Ⓕ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	4
Ⓖ Depth of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓗ Minimum depth above cavity for services to be routed through	2 3/16

Recommended that services are routed to the adjacent cabinet or either side of the product.

DATE: 9.1.2023 90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

POWER AND WATER CONNECTIONS Integrated Refrigerator Freezer, 24"

Model No:
RS2474BRU1
Integrated Refrigerator Freezer, 24"


NOTE: Left hand hinge is a mirrored version of the image shown.
Left hand hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

Specifications	
Electrical	
Supply	115 VAC, 60 Hz
Service	10 amp circuit
Plumbing	
Supply	Braided hose, 7/16" x 24 UNS
Pressure	min 40 psi (275 kPa) max 12 psi (827 kPa) @ 68°F (20°C)

NOTE: Recommended that services are routed to the adjacent cabinet.

Hose and Cord Lengths	inch
Electrical	
Ⓐ Power cord length (from the left edge of the product)*	70 7/8
Ⓑ Power cord length (from the right edge of the product)*	78 3/4
Ⓒ Power cord length (from the top of the product)*	14 15/16
Water	
Ⓓ Water inlet hose length (from the left edge of the product)	96 7/16
Ⓔ Water inlet hose length (from the right edge of the product)	78 3/4
Ⓕ Water inlet hose length (from the top of the product)	27 9/16

* Excluding plug.



LEFT HAND SIDE

FRONT VIEW


RIGHT HAND SIDE

DATE: 9.1.2023 90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

MULTIPLE INSTALLATION - STAINLESS STEEL DOOR PANELS Integrated Refrigerator Freezer, 24" Integrated Refrigerator, 24" Integrated Freezer, 24"



Model no:

RS2474BRU1
Stainless Steel Door Panel RD2474BR

RS2474F3LJ1 or RS2474S3RH1
Stainless Steel Door Panel RD2474R
Stainless Steel Toe kick for Dual Installation AKRS12010
Joiner Kit AJRS74LR

IMPORTANT!
For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Clearance Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	47 1/4
Ⓒ Minimum overall depth of cavity: When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16
Ⓓ Overall height of supply routing area at rear of cavity	17/16
Ⓔ Overall depth of supply routing area at rear of cavity	13/16
Ⓕ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	4
Ⓖ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓗ Minimum depth above cavity for services to be routed through	2 3/16

Stainless Steel Panel Dimensions	inch
Ⓐ Height of fridge top door panel	39 7/16
Ⓑ Height of freezer bottom door panel	30 3/8
Ⓒ Height of freezer or fridge door panel	69 7/8
Ⓓ Gap between door and drawer panel	1/8
Ⓔ Depth of door panel	3/4
Ⓕ Width of door panel	23 3/4
Ⓖ Width of toe kick panel	47 7/8
Ⓗ Height of toe kick panel	4
Ⓙ Gap between the center of the door panel	3/16

Dual Installation 1 Joiner Kit required - AJRS74LR
Triple Installation 2 Joiner Kits required - AJRS74LR
Freezer Models, RS2474F2L1 and RS2474F3LJ1 include 1 Joiner Kit

Recommended that services are routed to the adjacent cabinet or either side of the products.

HANDLES: Handle Kits are sold separately.
Please refer to the handle datasheets for more information.

DATE: **9.1.2023** **90003015A**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


MULTIPLE INSTALLATION - CUSTOM DOOR PANELS Integrated Refrigerator Freezer, 24" Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
RS2474BRU1
Custom Door Panels

RS2474F3LJ1 or RS2474S3RH1
Custom Door Panel and Custom Toe kick
Joiner Kit AJRS74LR

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.



Clearance Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	47 1/4
Ⓒ Minimum overall depth of cavity: When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16
Ⓓ Overall height of supply routing area at rear of cavity	1 7/16
Ⓔ Overall depth of supply routing area at rear of cavity	13/16
Ⓕ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	3 15/16
Ⓖ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓜ Minimum depth above cavity for services to be routed through	2 3/16

Custom Door Panel Dimensions	inch
Ⓙ Height of fridge top door panel	39 13/32
Ⓚ Height of freezer bottom door panel	28 7/16 - 33 3/4
Ⓛ Height of freezer or fridge door panel	68 - 73 5/16
Ⓢ Gap between door and drawer panel	1/8
Ⓝ Depth of door panel	5/8 - 3/4
Ⓞ Width of door panel	23 3/8
Ⓟ Width of toe kick panel	47
Ⓠ Height of toe kick panel	4
Ⓡ Gap between the center of the door panel	5/32

Dual Installation 1 Joiner Kit required - AJRS74LR

Triple Installation 2 Joiner Kits required - AJRS74LR

Freezer Models, RS2474F2L1 and RS2474F3LJ1 include 1 Joiner Kit

Recommended that services are routed to the adjacent cabinet or either side of the products

HANDLES: Handle Kits are sold separately.




Please refer to the handle datasheets for more information

DATE: 9.1.2023






90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

1 TOP HANDLE



2 BOTTOM HANDLE



FISHER & PAYKEL

HANDLE DATA SHEET Integrated Refrigerator Freezer, 24"

Model no:

Square Fine Aluminium Handle AHD5RDB74

Square Fine Aluminium Handle Black AHD5RDB74B

For Model:

RS2474BRU1, Integrated Refrigerator Freezer, 24"

1 Vertical Handle Top Door Dimensions*	inch
Ⓐ Overall length of handle	20 5/8
Ⓑ Overall height of handle	1 5/8
Ⓒ Overall width of handle	5/8
Ⓓ Length of off-stand	4 3/4
Ⓔ Length of off-stand	1 3/4
Ⓕ Distance between attachment holes	1 3/16
Ⓖ Distance between attachment holes	13/16
Ⓗ Distance between inner attachment holes	15 9/16
Ⓘ Distance between outer attachment holes	17 3/16
Ⓣ Thickness of handle rail	5/8

2 Vertical Handle Bottom Door Dimensions*	inch
Ⓚ Overall length of handle	11 9/16
Ⓛ Overall height of handle	1 5/8
Ⓜ Overall width of handle	5/8
Ⓝ Length of off-stand	4 3/4
Ⓞ Length of off-stand	1 3/4
Ⓟ Distance between attachment holes	1 3/16
Ⓢ Distance between attachment holes	13/16
Ⓡ Distance between inner attachment holes	7 1/4
Ⓣ Distance between outer attachment holes	9 5/16
Ⓢ Thickness of handle rail	5/8



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring or longer screws.




INDICATES PRODUCT DATUM

DATE: 9.1.2023






90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

1 TOP HANDLE



2 BOTTOM HANDLE



FISHER & PAYKEL

HANDLE DATA SHEET Integrated Refrigerator Freezer, 24"

Model no:
Round Handle AHSRDB74

For Model:
RS2474BRU1, Integrated Refrigerator Freezer, 24"

① Vertical Handle Top Door Dimensions*	inch
Ⓐ Overall length of handle	20 5/8
Ⓑ Overall height of handle	1 5/8
Ⓒ Overall width of handle	11/16
Ⓓ Length of off-stand	4 3/4
Ⓔ Length of off-stand	1 3/4
Ⓕ Distance between attachment holes	1 3/16
Ⓖ Distance between attachment holes	13/16
Ⓗ Distance between inner attachment holes	16 5/16
Ⓘ Distance between outer attachment holes	18 3/8
Ⓝ Thickness of handle rail	11/16

② Vertical Handle Bottom Door Dimensions*	inch
Ⓚ Overall length of handle	11 9/16
Ⓛ Overall height of handle	1 5/8
Ⓜ Overall width of handle	11/16
Ⓝ Length of off-stand	4 3/4
Ⓟ Length of off-stand	1 3/4
Ⓕ Distance between attachment holes	1 3/16
Ⓖ Distance between attachment holes	13/16
Ⓗ Distance between inner attachment holes	7 1/4
Ⓘ Distance between outer attachment holes	9 5/16
Ⓝ Thickness of handle rail	11/16



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring or longer screws.


INDICATES PRODUCT DATUM

DATE: 9.1.2023



90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

1 TOP HANDLE



2 BOTTOM HANDLE



FISHER & PAYKEL

HANDLE DATA SHEET Integrated Refrigerator Freezer, 24"

Model no:
Classic Handle AHCLRDB

For Model:
RS2474BRU1, Integrated Refrigerator Freezer, 24"

① Vertical Handle Top Door Dimensions*	inch
Ⓐ Overall length of handle	20 5/8
Ⓑ Overall height of handle	2 3/16
Ⓒ Overall width of handle	7/8
Ⓓ Length of off-stand	3 1/8
Ⓔ Length of off-stand	1 3/4
Ⓕ Distance between attachment holes	1 3/16
Ⓖ Distance between attachment holes	13/16
Ⓗ Distance between inner attachment holes	16 5/16
Ⓙ Distance between outer attachment holes	18 3/8
⓫ Thickness of handle rail	13/16

② Vertical Handle Bottom Door Dimensions*	inch
Ⓚ Overall length of handle	11 9/16
Ⓛ Overall height of handle	2 3/16
Ⓜ Overall width of handle	7/8
Ⓝ Length of off-stand	3 1/8
Ⓞ Length of off-stand	1 3/4
Ⓟ Distance between attachment holes	1 3/16
Ⓡ Distance between attachment holes	13/16
Ⓢ Distance between inner attachment holes	7 1/4
Ⓣ Distance between outer attachment holes	9 5/16
⓫ Thickness of handle rail	13/16



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring or longer screws..


INDICATES PRODUCT DATUM

DATE: 9.1.2023



90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

1 TOP HANDLE



2 BOTTOM HANDLE



FISHER & PAYKEL

HANDLE DATA SHEET Integrated Refrigerator Freezer, 24"

Model no:
Professional Flush Handle AHP3RDB74

For Model:
RS2474BRU1, Integrated Refrigerator Freezer, 24"

① Vertical Handle Top Door Dimensions*	inch
Ⓐ Overall length of handle	19 5/8
Ⓑ Overall height of handle	2 1/4
Ⓒ Overall width of handle	1 7/16
Ⓓ Length of off-stand	2 3/8
Ⓔ Distance between attachment holes	13/16
Ⓕ Distance between attachment holes	13/16
Ⓖ Distance between inner attachment holes	16 5/16
Ⓗ Distance between outer attachment holes	18 3/8
Ⓘ Thickness of handle rail	1

② Vertical Handle Bottom Door Dimensions*	inch
Ⓐ Overall length of handle	10 9/16
Ⓑ Overall height of handle	2 1/4
Ⓒ Overall width of handle	1 7/16
Ⓓ Length of off-stand	2 3/8
Ⓔ Distance between attachment holes	13/16
Ⓕ Distance between attachment holes	13/16
Ⓖ Distance between inner attachment holes	7 1/4
Ⓗ Distance between outer attachment holes	9 5/16
Ⓘ Thickness of handle rail	1



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring or longer screws.

INDICATES PRODUCT DATUM

DATE: 9.1.2023

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

Integrated Triple Zone Refrigerator, 24"

Integrated Triple Zone Freezer, 24"

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS Integrated Refrigerator, 24" Integrated Freezer, 24"


Model No:
RS2474S3RH1
Refrigerator
Stainless Steel Panels RD2474
Handle Kit AHD5RDSF
Stainless Steel Toe Kick Panel AKRS06010

RS2474F3LJ1
Freezer
Stainless Steel Panels RD2474
Handle Kit AHD5RDSF
Stainless Steel Toe Kick Panel AKRS06010

Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.



VERTICAL GAP
CLEARANCE FROM SIDE
OF DOOR PANEL



Product Dimensions	inch
Ⓐ Overall height of product	74
Ⓑ Overall width of product	23 5/16
Ⓒ Overall depth of product (excl. front door panels)	22 13/16
Ⓓ Height from top of door panel to floor	73 7/8
Ⓔ Minimum cabinetry clearance from side of door panel	5/32
Ⓕ Minimum cabinetry clearance from top of door panel	1/8
Ⓖ Height of door panel	69 7/8
Ⓗ Depth of door panel	3/4
Ⓙ Height from floor to bottom of door panel	4
Ⓚ Depth of toe kick (excl. front door and toe kick panels)	2 - 4

Cavity Dimensions	inch
Ⓛ Overall height of cavity	74
Ⓜ Overall width of cavity	23 5/8
Ⓨ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16

Note: Product shown installed on the floor. Slide into cabinetry position.
Alternatively can be installed on a plinth. Adjust your cavity height accordingly.

INDICATES CAVITY CLEARANCES (dashed red line)
INDICATES PRODUCT DATUM (dashed blue line)

DATE: 9.1.2023 90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com




FISHER & PAYKEL


PRODUCT & CAVITY DIMENSIONS Integrated Refrigerator, 24" Integrated Freezer, 24"

Model No:
RS2474S3RH1
Integrated Dual and Triple Zone Refrigerator
RS2474F3LJ1
Integrated Dual and Triple Zone Freezer

Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.



VERTICAL GAP
CLEARANCE FROM SIDE
OF DOOR PANEL



PLAN VIEW

FRONT VIEW

PROFILE VIEW

Product Dimensions	inch
Ⓐ Overall height of product	74
Ⓑ Overall width of product	23 5/16
Ⓒ Overall depth of product	22 13/16
Ⓓ Minimum cabinetry clearance from side of door panel*	5/32
Ⓔ Minimum cabinetry clearance from top of door panel*	1/8
Ⓕ Depth of door panel*	5/8 - 3/4
Ⓖ Height of toe kick panel*	4
Ⓗ Depth of toe kick (excl. front door and toe kick panels)	2 - 4

Cavity Dimensions	inch
Ⓘ Overall height of cavity	74
Ⓚ Overall width of cavity	23 5/8
Ⓛ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16

Note: Product shown installed on the floor. Slide into cabinetry position.
Alternatively can be installed on a plinth. Adjust your cavity height accordingly.

For Custom Panel dimensions refer to page 26.
*Custom door panel and toe kick panel to be manufactured and fitted by cabinetmaker.


INDICATES CAVITY CLEARANCES (dashed red line)
INDICATES PRODUCT DATUM (dashed blue line)

DATE: 9.1.2023 90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com




CLEARANCES




DUAL INSTALL




TRIPLE INSTALL



CONFIGURATIONS



HINGE TO HINGE
Both doors open at the same time
- requires space between models



HINGE TO HINGE
Only allows a single door open at a time

FISHER & PAYKEL

DOOR OPENINGS & CLEARANCE DIMENSIONS Integrated Refrigerator, 24" Integrated Freezer, 24"

Model No:
RS2474S3RH1
Integrated Dual and Triple Zone Refrigerator
RS2474F3LJ1
Integrated Dual and Triple Zone Freezer

Opposite hinge can be achieved using supplied parts.

Clearance Dimensions	inch
Ⓐ Depth of door (90° open, measured from front of cabinetry)	23 5/8
Ⓑ Minimum door clearance to adjacent wall (90° - reduced internal access)* **	3 1/8
Ⓒ Minimum door clearance to adjacent wall (115° - full internal access)* **	10 3/4
Ⓓ Minimum cabinetry clearance from side of door panel to adjacent wall (non hinge side)	5/32
Ⓔ Minimum clearance between products when opening hinge to hinge. Allowing both doors to open at the same time**	4

Minimum Door Clearance (Vertical Gap)	inch
Ⓕ Dual Install: Stainless steel door panels (gaps equalized during installation)	3/16
Custom panels (width of custom panel increased to maintain 4mm gap across multiple products)***	5/32
Ⓖ Triple Install: Stainless steel door panels (gaps equalized during installation)	1/4
Custom panels (width of custom panel increased to maintain 4mm gap across multiple products)***	5/32

*Use hinge limiting pin to restrict door opening to 90° where necessary.
**Minimum dimensions shown are for the contemporary handle kit AHD5RDSF. Custom panel and handle details need to be taken into account.
***Refer to Custom Panel Dimensions and Multiple Install pages for further.

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: **9.1.2023** **90003015A**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CUSTOM PANEL PREPARATION - HINGE Integrated Refrigerator, 24" Integrated Freezer, 24"


Model nos:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer

Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

Dwg & Dxf Files

Dwg and Dxf files of the panel preparation are available within the download folder for this product and can be found on <http://thekitchentools.fisherpaykel.com>

Door Hinge - Hettich K08



DATE: 9.1.2023

90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


CUSTOM PANEL DIMENSIONS Integrated Refrigerator, 24" Integrated Freezer, 24"

Model No:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer
with Custom Panels

Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.



ISO VIEW



PROFILE VIEW

Custom Panel Dimensions	inch
Ⓐ Height of door panel	68 - 73 5/16
Ⓑ Width of door panel:	
Single install	23 5/16
Dual install*	23 3/8
Triple install*	23 13/32
Ⓒ Depth of custom panel**	5/8 - 3/4
Ⓓ Height from floor to top of door panel	73 7/8
Ⓔ Height from floor to bottom of door panel***	9/16 - 5 15/16
Ⓕ Height of toe kick panel	4
Ⓖ Width of toe kick panel****	23 1/2
Maximum weight of door panel*****	42lbs

Custom door panel, handle and toe kick panel to be manufactured and fitted by cabinetmaker.

*For further details on multiple installation refer to page 31.

**At 3/4" thickness, we recommend an edge radius of 1mm or more to avoid the possibility of panel clash when opening.

***The grille becomes visible at heights over 4" (100mm)

****Toe kick can be continuous.


*****Includes weight of handle.

DATE: 9.1.2023

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

REAR VIEW



FISHER & PAYKEL

CUSTOM PANEL PREPARATION
Integrated Refrigerator, 24"
Integrated Freezer, 24"

Model No:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer

Opposite hinge can be achieved using supplied parts.
 Please refer to Installation Guide for details.

Custom Panel Preparation

Dimensions are shown in inches ("").
 Dimensions apply for the preparation and installation of custom panels.

Handles

Ensure handle screw heads are countersunk into back of panel to avoid interfering with hanging bracket, and clear of side brackets as indicated.

Dwg & Dxf Files

Dwg and Dxf files of the panel preparation can be downloaded from Trade Resources www.fisherpaykel.com

Template

A template for marking and drilling the holes is provided with the product.

DATE: **9.1.2023**

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

CAVITY PREPARATION Integrated Refrigerator, 24" Integrated Freezer, 24"

Model No:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer


Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

IMPORTANT!
For ease of installation, ensure cavity has consistent dimensions
top to bottom and left to right.


Minimum Cavity Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓓ Overall width of cavity	23 5/8
Ⓒ Minimum overall depth of cavity:	
When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16
Minimum required finished return	4

Electrical / Plumbing Supply Dimensions	inch
Ⓔ Overall height of supply routing area at rear of cavity	1 7/16
Overall width of supply routing area at rear of cavity	23 5/8
Ⓕ Overall depth of supply routing area at rear of cavity	13/16
Ⓖ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	4
Ⓒ Depth of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓜ Minimum depth above cavity for services to be routed through	2 3/16

NOTE: Recommended that services are routed to the adjacent cabinet or either side of the product.



FINISHED RETURN
CAVITY SIDES & TOP



ALTERNATIVE AREA
ABOVE CAVITY FOR
ELEC / WATER CONNECTION

ISO VIEW

DATE: 9.1.2023

9003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

POWER AND WATER CONNECTIONS Integrated Refrigerator, 24" Integrated Freezer, 24"

Model No:

RS2474S3RH1

Integrated Dual and Triple Zone Refrigerator

RS2474F3LJ1

Integrated Dual and Triple Zone Freezer

Opposite hinge can be achieved using supplied parts.
Please refer to Installation Guide for details.

Specifications

Electrical

Supply 115 VAC, 60 Hz

Service 10 amp circuit

Plumbing

Supply Braided hose, 7/16" x 24 UNS

Pressure min 40 psi (275 kPa)
max 12 psi (827 kPa) @ 68°F (20°C)

NOTE: Recommended that services are routed to the adjacent cabinet.

Hose and Cord Lengths

Electrical

Ⓐ Power cord length (from the left edge of the product)* 70 7/8

Ⓑ Power cord length (from the right edge of the product)* 78 3/4

Ⓒ Power cord length (from the top of the product)* 14 15/16


Water

Ⓓ Water inlet hose length (from the left edge of the product) 96 7/16

Ⓔ Water inlet hose length (from the right edge of the product) 78 3/4

Ⓕ Water inlet hose length (from the top of the product) 27 9/16

* Excluding plug.



LEFT HAND SIDE

FRONT VIEW

RIGHT HAND SIDE

DATE: 9.1.2023

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL

MULTIPLE INSTALLATION - STAINLESS STEEL DOOR PANELS Integrated Refrigerator Freezer, 24" Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:

RS2474BRU1

Stainless Steel Door Panel RD2474BR

RS2474F3LJ1, RS2474S3RH1

Stainless Steel Door Panel RD2474

Stainless Steel Toe kick for Dual Installation AKRS06010

Joiner Kit AJRS74LR

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Clearance Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	47 1/4
Ⓒ Minimum overall depth of cavity: When services are located outside of cavity (shallow)	23 5/8
When services are located in the cabinet above the cavity	24
When services are located at rear of cavity (deep)	25 9/16
Ⓓ Overall height of supply routing area at rear of cavity	1 7/16
Ⓔ Overall depth of supply routing area at rear of cavity	1/16
Ⓕ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	4
Ⓖ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓗ Minimum depth above cavity for services to be routed through	2 3/16

Stainless Steel Panel Dimensions	inch
Ⓐ Height of fridge top door panel	39 7/16
Ⓑ Height of freezer bottom door panel	30 3/8
Ⓒ Height of freezer or fridge door panel	69 7/8
Ⓓ Gap between door and drawer panel	1/8
Ⓔ Depth of door panel	3/4
Ⓕ Width of door panel	23 3/4
Ⓖ Width of toe kick panel	47 7/8
Ⓓ Height of toe kick panel	4
Ⓗ Gap between the center of the door panel	3/16

Dual Installation 1 Joiner Kit required - AJRS74LR

Triple Installation 2 Joiner Kits required - AJRS74LR

Recommended that services are routed to the adjacent cabinet or either side of the products.


HANDLES: Handle Kits are sold separately.

Please refer to the handle datasheets for more information.

DATE: 28.11.2022

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



FISHER & PAYKEL

MULTIPLE INSTALLATION - CUSTOM DOOR PANELS Integrated Refrigerator Freezer, 24" Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
RS2474BRU1
Custom Door Panels

RS2474F3LJ1 or RS2474S3RH1
Custom Door Panel and Custom Toe kick
Joiner Kit AJRS74LR

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Clearance Dimensions	inch
Ⓐ Overall height of cavity	74
Ⓑ Overall width of cavity	47 1/4
Ⓒ Minimum overall depth of cavity: When services are located outside of cavity (shallow) When services are located in the cabinet above the cavity When services are located at rear of cavity (deep)	23 5/8 24 25 9/16
Ⓓ Overall height of supply routing area at rear of cavity	1 7/16
Ⓔ Overall depth of supply routing area at rear of cavity	1/16
Ⓕ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	4
Ⓖ Height of notch at rear of cavity for services to be routed into adjacent cabinet (either side)	2 3/16
Ⓜ Minimum depth above cavity for services to be routed through	2 3/16

Custom Door Panel Dimensions	inch
Ⓛ Height of fridge top door panel	39 7/16
Ⓜ Height of freezer bottom door panel	28 7/16 - 33 3/4
Ⓨ Height of freezer or fridge door panel	68 - 73 5/16
Ⓧ Gap between door and drawer panel	1/8
Ⓝ Depth of door panel	5/8 - 3/4
Ⓞ Width of door panel	23 3/8
Ⓟ Width of toe kick panel	47
Ⓠ Height of toe kick panel	4
Ⓡ Gap between the center of the door panel	3/16


Dual Installation 1 Joiner Kit required - AJRS74LR
Triple Installation 2 Joiner Kits required - AJRS74LR

Recommended that services are routed to the adjacent cabinet or either side

DATE: 9.1.2023

90003015A

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com




FISHER & PAYKEL



HANDLE DATA SHEET Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
Square Fine Aluminium Handle AHD5RDSF
Square Fine Aluminium Handle Black AHD5RDSFB

For Models:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer



Handle Dimensions	inch
Ⓐ Overall length of handle	33 9/16
Ⓑ Overall height of handle	1 5/8
Ⓒ Overall width of handle	9/16
Ⓓ Length of off-stand	4 3/4
Ⓔ Distance between attachment holes	1 3/16
Ⓕ Distance between inner attachment holes	28
Ⓖ Distance between outer attachment holes	30 7/16
Ⓗ Thickness of handle rail	5/8



INDICATES PRODUCT DATUM - - - - -

DATE: **9.1.2023** **90003015A**


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


HANDLE DATA SHEET Integrated Dual and Triple Zone Refrigerator, 24" Integrated Dual and Triple Zone Freezer, 24"

Model no:
Round Handle AHCLRDB

For Model:
**RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer**



Handle Dimensions	inch
Ⓐ Overall length of handle	33 9/16
Ⓑ Overall height of handle	1 5/8
Ⓒ Overall width of handle	1 1/16
Ⓓ Length of off-stand	4 3/4
Ⓔ Distance between attachment holes	1 3/16
Ⓕ Distance between inner attachment holes	28
Ⓖ Distance between outer attachment holes	30 7/16
Ⓗ Thickness of handle rail	1 1/16



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring
or longer screws.

INDICATES PRODUCT DATUM

DATE: 9.1.2023

90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


HANDLE DATA SHEET Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
Classic Handle AHCLRDSF

For Model:
RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer



Handle Dimensions	inch
Ⓐ Overall length of handle	33 9/16
Ⓑ Overall height of handle	2 3/16
Ⓒ Overall width of handle	7/8
Ⓓ Length of off-stand	3 1/8
Ⓔ Distance between attachment holes	13/16
Ⓕ Distance between inner attachment holes	28
Ⓖ Distance between outer attachment holes	30 7/16
Ⓗ Thickness of handle rail	13/16



M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring
or longer screws.

INDICATES PRODUCT DATUM

DATE: 9.1.2023

90003015A


IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


HANDLE DATA SHEET Integrated Refrigerator, 24" Integrated Freezer, 24"

Model no:
Professional Handle AHP3RDSF

For Model:
**RS2474S3RH1
Integrated Refrigerator
RS2474F3LJ1
Integrated Freezer**



Handle Dimensions	inch
Ⓐ Overall length of handle	31 9/16
Ⓑ Overall height of handle	2 1/4
Ⓒ Overall width of handle	1 7/16
Ⓓ Length of off-stand	2 3/8
Ⓔ Distance between attachment holes	13 3/16
Ⓕ Distance between inner attachment holes	28
Ⓖ Distance between outer attachment holes	30 7/16
Ⓗ Thickness of handle rail	1





M5 X 12" Pan Head Socket Screw (4 per handle)
Suits standard 3/4inch panel. Thicker panels may require counterboring or longer screws.

INDICATES PRODUCT DATUM

DATE: **9.1.2023** **90003015A**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the Installation Guide for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL