

0 100 200 400 millimetres

FISHER & PAYKEL

DATA SHEET Warming Drawer, 600mm - Contemporary Style

Model no:

WB60SDEX2

Product Dimensions	mn
Overall height of warming drawer	140
Overall width of warming drawer	596
© Overall depth of drawer (incl. front panel & power plug, excludes stainless cap)	567
Height of drawer front panel	136
Width of chassis	543
© Depth of drawer front panel and flange (excludes stainless cap)	20
Depth of chassis (includes power plug, excludes flange)	547
Distance from side of chassis to side of drawer front	26.5
① Depth of open drawer (measured from front of drawer panel)	414
Height from bottom of chassis to bottom of front panel	2

Clearance Dimensions	mm
Minimum inside height of cavity	142
Minimum inside width of cavity	560
Minimum inside depth of cavity	550
Overall width of cabinetry	600
Minimum clearance between top of front panel and upper cabinetry panel	3
Minimum clearance between bottom of front panel and lower cabinetry panel	

INDICATES CABINETRY / PRODUCT DATUM ------INDICATES CABINETRY CLEARANCES ------

DATE: 06.04.2021

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com