FISHER & PAYKEL

DATA SHEET

Induction Cooktop, 300mm, 2 Zones, Black





Model no: CI302DTB4

Product Dimensions	mm
 Overall height of cooktop 	54
Overall width of cooktop	299
© Overall depth of cooktop	530
 Height of cooktop glass (includes flange and tape) 	6
© Height of chassis	48
© Width of chassis	260
© Depth of chassis	480
Distance from side of edges of cooktop to chassis	20
 Distance from front of edge of cooktop to chassis 	13
 Distance from back edge of cooktop to chassis 	37
© Distance from rear of cooktop to cutout	32
© Distance from front of cooktop to cutout	8

Product Clearances	mm
ninimum clearance from side edges of cutout to nearest combustible surface	30
ninimum clearance from rear edge of cutout to nearest combustible surface	39
ninimum clearance from front edge of cutout to front edge of counter	35
Minimum clearance from glass surface to rangehood	650
dinimum clearance from glass surface to overhead cabinet not directly above cooktop	450
Minimum ventilation gap between bottom of counter and top of cabinetry fronts (not shown)	4
Minimum clearance from counter top to top of any appliances, companion product or obstruction below cooktop*	65
Control Con	ooktop glass
NOTE: The oven installed below the cooktop MUST have a cooling fan. It is importar induction cooktop receives adequate air supply. For ventilation requirements please	

Cutout Dimensions	mm
Overall width of cutout**	265
Overall depth of cutout***	490

** Note cutout position is centred to the cooktop width.

 *** Note cutout is offset 8mm towards the front of the cooktop.

DATE: 08.12.2021

installation manual.

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2mm$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com