SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (_) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	103
	LAST NO. USED	32

MISSING SYMBOLS

NO MISSING SYMBOL NUMBER

DWG STATUS DATE	STS	REC	N/P	DIR	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
25MY04	R	B1	-	-	-	CLEARED REV COLUMN AND REDRAWN TO PD1 [12029991 & 12089077 - RESTRICTED] 15492531 & 15492584 - RELEASED	295769	JBD	JAA	MGR
18OCT05	R	B3	-	-	-	12029991 - OBSOLETE	273752	CCV	JAA	MGR
23NOV06	R	B4	-	-	-	15492531 AND 15492584 - UPDATED PDM ATTRIBUTES	280589	JTZ	JAA	RTW
05DEC06	R	B5	-	-	-	15492584 & 15492531 - COLOR REMOVED FROM CHART	287527	RJD	RJD	TM
13JUL2	R	B6	-	-	-	15492531 & 15492584 - ADDED "TORQUE REQ'D" & "APPLICATION DATA" NOTES	416771	JBM	JWD	AB





MOUNTING HOLE

VIEW FROM ENGINE COMPARTMENT

INSPECTION SYMBOLS SHOWN IN THIS VIEW ARE FOR REFERENCE ONLY











NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. NUT MUST NOT ROTATE IN CONNECTOR BODY WHEN ASSEMBLED WITH MATING CONNECTOR USING A TORQUE OF 13.6 NEWTON-METERS.
3. MATING CONNECTOR ASSEMBLY - SEE CHART.
4. PUSH OUT OF BOLTS FROM CONNECTOR TO BE 53 NEWTONS MIN.
5. SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN ESA-644 (WEATHER-PACK), ESA-710 (METRI-PACK), ESA-650 (UNDERHOOD MICRO-PACK), C-4006 (WORLD CONNECTOR), ETC WHEN MATED TO MATING PART OR EQUIVALENT
6. THE T-NUT MUST WITHSTAND A MINIMUM PUSH OUT FORCE OF 980 NEWTONS (220 POUNDS).
1. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR BLEMISHES, GATE VESTIGE, AND SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER DFMP-4.7-CS-01.
7. T-NUT 15492503 MUST WITHSTAND A TORQUE OF 11.3 NM W/O SHEARING. IF FUTURE CONNECTOR ASSEMBLIES USING THIS COMPONENT REQUIRE AN ASSEMBLY TORQUE OF OVER 11.3 NM TESTING SHOULD BE PERFORMED TO VERIFY THE INTEGRITY OF CONNECTOR ASSEMBLY. A DESIGN CHANGE MAY BE REQUIRED TO MEET A TORQUE VALUE OF OVER 11.3 NM.
8. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

PART NO	REV	N/P	CONN	BOLT	T-NUT	SEAL CONN	MATING CONNECTOR
15492584	01	AC	12089076	15492507	15492503	12010851	12077378
15492531	01	AC	12020985	15492507	15492503	12010851	12020005
12089077	A2	-	12089076	08917392	06288940	12010851	12077378
12029991	A2	-	12020985	08917392	06288940	12010851	12020005

THE DRAWN FEATURES / FORM SHOWN ON THIS PRINT PHYSICAL PARTS ARE NOT AVAILABLE FOR INSPECTION.

PART NUMBERS THAT OR SET HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT DELPHI SALES TO ASSURE AVAILABILITY OF PARTS.

DWG TYPE: PART DRAWING

STYLE

RELEASE (DAY) | SIGNIFICANT CHANGE

UNLESS OTHERWISE SPECIFIED

THIS DOCUMENT IS TO BE INTERPRETED WITH ASME Y14.5M-1994 AND ASME Y14.5.1M-1994 AS MODIFIED BY DELPHI ENGINEERING STANDARD CS-01. DIMENSIONS AND TOLERANCES APPLY IN THE UNCOATED STATE UNLESS OTHERWISE SPECIFIED. FEATURES NOT SHOWN ARE NOT CONTROLLED BY THIS DRAWING. REFERENCE DIMENSIONS ARE NOT TOLERANCED.

(N/A) PROCESS SENSITIVE DIMENSION

DIMENSIONS AND LIMITS ARE IN MILLIMETERS

REFERENCE

ALL DIMENSIONS ARE IN MILLIMETERS

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

ATMOSPHERIC PRESS. (MPa)									
FROM	0	25	75	125	150	200	250	300	400
TO	25	75	125	150	200	250	300	400	

TEMPERATURE (DEGREES CENTIGRADE)																								
-40	-35	-30	-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80

VOLTS (V)																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

CURRENT (A)																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

FREQUENCY (Hz)																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

SURFACE FINISH (µm)																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

ANGLES (DEGREES)																								
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2

DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE

COPYRIGHT 1998 DELPHI TECHNOLOGIES INC. AND/OR ITS AFFILIATES. ALL RIGHTS RESERVED.

THIS DRAWING IS THE PROPRIETARY PROPERTY OF DELPHI CORPORATION. THE INFORMATION, DISCLOSURE OR UTILIZATION THEREOF IS RESTRICTED BY THE TERMS OF THE AGREEMENT OR AS WELL AS COMMUNICATIONS OF ALL KIND(S) TO DELPHI. WITHOUT EXPRESS AUTHORIZATION IS PROHIBITED.

DR	DATE
APVD1: J. HOUGELMAN	05SEP88
APVD2: F. HESTON	13SEP88
APVD3: R. G. C.	15SEP88
APVD4	
APVD5	

SUBSTANCES OF CONCERN: ANY PRODUCT COMPLIANT PER DELPHI GMW4063

MATERIAL: SEE DWG

DRAWING NAME: TAXI ASM CONN F W/P TWR SLD

DRAWING NUMBER: 12089253

SIZE	SCALE	TYPE	SHEET NO	QTY	REV	N/P
A2	2:1	1	1 OF 1	1	R	D6 -