
TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN
BODY TYPE I
TYPE 103
SAME AS TYPE 101
EXCEPT AS SHOWN
OPTIONAL CONSTRUCTION
FOR 10 WAY
TYPE 101
10 WAY
BODY TYPE II
SAME AS BODY TYPE I
EXCEPT WITH ANTI-ROUNDING
LUGS ON SHORT ENDS OF CONN
MATERIAL SPECIFICATIONS
MATING BLADE INFORMATION
SCALE B:1
INSPECTION SYMBOLS SHOWN IN THIS VIEW ARE FOR REFERENCE ONLY
TYPE 101 & 103
TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN
SECTION B-B
SECTION A-A
MATING PART INFORMATION
SYMBOL DEFINITION
MISSING SYMBOLS
NO MISSING SYMBOL NUMBER
KEY PRODUCT CHARACTERISTICS
SAFETY/COMPLIANCE
FIT/FUNCTION
S/C DESIGNATORS
F/F DESIGNATORS
NOTES
1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY MEASURED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS (NOT SHOWN, BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL MATH DATA. DRAFT IS 1° ON ALL OUTSIDE SURFACES
2. RECOMMENDED MATERIAL: GLASS FILLED NYLON OR POLYESTER
3. TERMINAL MUST WITHSTAND A MINIMUM PUSHOUT FORCE OF 89 N (20 LBS)
4. WHEN USING THIS INFORMATION FOR A NEW DESIGN REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC
5. KEY PRODUCT CHARACTERISTIC SYMBOLS (K,D) INDICATE PRODUCT CHARACTERISTICS THAT REQUIRE SPECIAL CARE, DOCUMENTATION, AND CONTROL PER GM 1927-M AND DELPHI DELCO ON AND DELPHI PACKARD ELECTRIC SYSTEMS PROCEDURES.
6. THIS PART IS NOT CONTROLLED FOR AUTOMATIC FEEDING
7. CONNECTOR ACCEPTS CPA 12020833
TPA 12177082
8. SEALING CODE #3
9. FOR PART NUMBERS WITH ADHESIVE, USE M3510001 OR ADHESIVE APPROVED BY MATERIALS ENGINEERING TO GLUE CONNECTOR SEAL TO CONNECTOR
10. MINIMUM RETENTION OF PERIPHERAL SEAL TO CONNECTOR IS 4.1 N
11. CONNECTOR TO ACCEPT CAP/COVER 12129589
DELPHI
TAST ASM CONN F WP 150 SLD
12048226
PART DRAWING
PHIL M. DAVIS
MIKE J. COLDSMITH
MIKE N. BARTLEY
PART NO. WITH ADHESIVE
REV/N/P
NO. OF CAVITIES
CAVITIES BLOCKED
CONNECTOR BODY
CONNECTOR SEAL
MATING CONNECTOR
NOTES
INDEX TYPE
REPLACED BY
12048226 A1 1 OF 2 1 OF 1 34