

SYMBOL DEFINITION

A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ($\square$) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	3
	LAST NO. USED	3

MISSING SYMBOLS

DATE	SIG	REV	N/P	CHK	ZONE	REVISION HISTORY	AUTH	DR	APPROV	PAGE
19JAI8	R	01	-	-	-	CREATED PART DRAWING	438642	NNH	WOL	TY

NOTES:

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
- PART MUST BE FREE OF MICRO CRACK, BURRS, SHARP EDGE, OIL, GREASE OR OTHER CONTAMINANTS.
- ALL DIMENSIONS ARE AFTER PLATING.
- PLATING:
UNDERPLATE: THICKNESS OF NICKEL SHALL BE 1.5um - 4um PER ASTM B-689, TYPE I, CLASS X.
OVERPLATE: THICKNESS OF SILVER SHALL BE 3um - 6um PER ASTM B-700, TYPE 3, GRADE B, CLASS II, 16SH VLN.
ANTI TARNISH TREATMENT PER DELPHI MSBIS SPECIFICATION REQUIREMENTS. ANY COATING BRAND OTHER THAN EVABRITE MUST BE APPROVED BY DELPHI.
- COMPONENTS MUST BE PACKAGED IN A SEALED BAG.
- THIS PART USED IN ASSEMBLY 33367709 TYPICALLY.
- ONLY RECOMMENDED CABLE ACC. TO LV216-2.
CABLE SIZE: 2X4.0MM²2X0.5MM² PER M6803 VALIDATED.
2X4.0MM² & 3X2.5MM² PER M6803 VALIDATED.
ALL OTHER CABLE SUPPLIERS / CABLE SIZES MUST BE VALIDATED.

DELPHI
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
MATERIAL OR COPYRIGHT IS IN DELPHI CORPORATION AND/OR ITS AFFILIATES. ALL RIGHTS RESERVED.
THIS DRAWING IS THE PROPERTY OF DELPHI CORPORATION AND CONTAINS DELPHI CONFIDENTIAL INFORMATION. THE INFORMATION DISCLOSED HEREON IS UNCLASSIFIED UPON REQUEST OF ITS RELATED CDA WITH DPA. AS WELL AS COMPARISON OF THE TWO DOCUMENTS, WITHOUT EXPRESS AUTHORIZATION, IS PROHIBITED.

35174278
PART NO REV N/P DESCRIPTION MATERIAL VOLUME (CM)
01 - OUTER FERRULE COPPER ALLOY 0.125

33254934
THIRD ANGLE PROJECTION
DO NOT SCALE
USE MATH DATA
ANALYSIS TOLERANCE 100%

35174269
SCALE PHONE NO SHEET NO STD TRY N/P
A1 10:1 1 OF 1 1 OF 1 R 01 -