


TYPE 101



TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN

- NOTES
1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
 - DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (FEAT) MODEL FOR ALL DIMENSIONS EXCEPT FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, USE MATR MODEL FOR PRECISION WITH DATA.
 2. RECOMMENDED MATING BLADE THICKNESS 0.4 MM
RECOMMENDED MATING BLADE WIDTH NOT TO EXCEED 1.2
 3. MAXIMUM CURRENT CAPACITY 15 AMPS
 4. MATING COMPONENTS OR EQUIVALENT:
MATING CONTACTS: CAVITY FEMALE C04111U
PIN T5150480
 5. MAX. INSULATION GRIP WIDTH 1.9 MM
MAX. INSULATION GRIP THICKNESS 2.2 MM
 6. REFER TO SAE/ASAP-2 APRIL 2000
(TEMPERATURE CLASS 1, VIBRATION FOR COMPONENTS COUPLED TO ENGINE) FOR PRODUCT PERFORMANCE REQUIREMENTS.
SEALING CODE 0 - UNSEALED
 7. DO NOT PROBE, TEST OR OTHERWISE CONTACT THE INTERIOR REGION OF THE SPRING OR ANY MOVING PART OF THIS TERMINAL. SEVERE DAMAGE CAN OCCUR TO THE SPRING OR THE ELECTRICAL CONTACTS.

13226148	05	AA	105	0.5 X 5	WETL NONFERROUS C42500 EX HD	0.12-0.22	25	1.61-0.00	1.4	1.6	1.5	1.7	
15447878	05	AA	101	0.5 X 2.75	WETL NONFERROUS C42500 EX HD	0.12-0.22	25	1.61-0.00	2.6	2.6	2.6	2.9	
15447878	05	AA	101	0.5 X 2.75	WETL NONFERROUS C42500 EX HD	0.35-0.5	21	1.83-1.47	2	2.6	2.2	2.9	
PART NO	REV	N/P	TYPE	STATUS	MAT'L SIZE	MAT'L SPEC	SIZE (MMF)	ID	DIA	B ₁ ±0.2	B ₂ ±0.3	H ₁	H ₂

[illegible]