





SYMBOL DEFINITION			MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	22	NO MISSING SYMBOL NUMBER
	LAST NO. USED	14	

DWG STATUS DATE	STS	REV	N/P	DIR	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
280C99	R	01	-	-	-	ALL PARTS - REDRAWN TO PD & 12129925 - MAT'L SPEC REVISED	196890	JDR	CAM	RH
21FE00	R	02	-	-	-	15329419 - RELEASED	030695	JDR	PDK	RH
23M100	R	03	-	-	-	15393182 - RELEASED	030695	MAC	MAC	MC
040K02	R	04	-	-	-	ALL PARTS - REVISED MAT'L SPEC	229962	KRA	BEB	JR
18M903	R	05	-	-	-	12186823 - OBSOLETE	238033	EDW	EDV	JR
15M804	R	06	-	-	-	12640756, 12640945, 12647040, 12952842, 12959184, 12966601, 12139367-ADDED ALTERNATE MAT'L SPEC, REVISED CHART DIMS, REVISED PER NIN END BOLTS	251647	ADK	ADK	MR
05M904	R	07	-	-	-	15488729 - RELEASED	254451	ADK	ADK	RAP
18JN04	R	08	-	-	-	ADDED PART 15497759 - RELEASED; ADDED DIMS "A" & "E" FROM TOOL REMOVED SECTION VIEWS A-A, B-B, C-C & D-D; MOVED DIM "J" TO TOP ONLY; ADDED ALTERNATE MAT'L SPEC TO CHART	256197	RH	RH	MR
10AU04	R	09	-	-	-	12640750 - REVISED PER NIN END BOLTS	257890	LMD	LMD	MR
02SE04	R	10	-	-	-	15488729 - 11.2 WAS 11.8	258952	ADK	ADK	RAP
12OC04	R	11	-	-	-	12640750 - CANCELLED REV 03	259646	CTR	JAM	MPR
02FE05	R	12	-	-	-	ALL PARTS - REVISED COLOR COLUMN TO BE REFERENCE	263887	END	ADK	MPR
29DE05	R	13	-	-	-	12611298 AND 15355369 WERE SEPARATE DRAWINGS ALL ACTIVE PARTS - REMOVED OPTIONAL CONSTRUCTION VIEW REVISED CHART AND NOTES	273706	RH	RH	MPR
15N06	R	14	-	-	-	ALL ACTIVE PARTS - ADDED "ANTI-STICK BUMPS" NOTE AND REVISED "SEALING RIBS" NOTE, MATERIAL SPEC CALLOUTS & INSPECTION SYMBOL NUMBERS	285913	MS	DKD	MPR
04D06	R	15	-	-	-	12059184 - DIM "C" WAS 20.44±0.15	287477	MS	DKD	MPR
10N06	R	16	-	-	-	12124681 - MAT'L SPEC WAS M22520/4 AND ADDED ALTERNATE MAT'L SPEC	426734	MM	MM	MPR
13AP09	R	17	-	-	-	ALL ACTIVE PARTS - REVISED MATERIAL CALLOUT TO GENERIC CALLOUT AND REMOVED ALTERNATE MATERIAL SPEC COLUMN FROM CHART; 15497759 - ADDED SPECIAL NOTE FOR POST BAKE?S	437795	JTZ	PKV	MPR
28SE09	R	18	-	-	-	ALL ACTIVE PARTS - ADDED VOLUME COLUMN ON CHART	459815	MEA	GLG	DSL
17DE09	R	19	-	-	-	15329419 - OBSOLETE	459684	MPS	MPR	MPR
29AU10	R	20	-	-	-	ALL ACTIVE PARTS TYPE 201 - CORRECTED TO TYPE 201 INSTEAD OF TYPE 192	411779	AMY	JAM	MAD

PART NO	REV	N/P	STATUS	RESTRICTED USAGE	MATERIAL SPECIFICATION AND COLOR	TYPE	A▲	B▲	C▲	D▲	P▲	E	F	SPECIAL NOTES	REPLACED BY	TYPICAL MATING CONNECTOR (REF)	VOLUME(CM³)
15497759	01	AF	-	RESTRICTED	SILICONE METHYL/VINYL OCHER	201	15.14	6.72	20.44±0.15	12.02	7.25	-	-	#7	-	12059180	0.516
15488729	01	AH	-	-	SILICONE METHYL/VINYL BLUE	201	11.2	6	16.5±0.3	11.3±0.3	7.25	-	-	-	-	12052675	0.425
15393182	01	AG	-	-	FLUOROSILICONE METHYL/V GREEN	201	22.1±0.15	6	27.4±0.3	11.3±0.3	7.25	-	-	-	-	12047947	0.442
15355369	01	AD	-	-	SILICONE METHYL/VINYL BLUE	203	12.35	4.9	17.65	10.2	7.25	-	-	#6	-	15326594	0.454
15324919	01	AS	OBSOLETE	-	SILICONE METHYL/VINYL PURPLE	201	15.5	4.9	20.8±0.3	10.2	7.25	4.29.5	-	-	-	12047795	0.513
15305078	AB	-	-	-	SILICONE METHYL/VINYL PINK	201	24.84±0.15	7.99	29.1±0.15	12.29	4.8	-	-	#1	-	NONE	0.450
15111248	01	AD	-	-	SILICONE METHYL/VINYL WHITE	203	9.2	4.9	14.5	10.2	7.25	-	-	#6	-	15449024	0.379
12186974	AB	-	-	-	SILICONE METHYL/VINYL WHITE	201	16.9	6	22.2±0.3	11.3±0.3	7.25	-	-	-	-	12052841	0.553
12186824	AB	-	-	-	SILICONE METHYL/VINYL WHITE	201	12.35	4.9	17.65	10.2	7.25	-	-	-	-	12047906	0.423
12186823	A3	-	OBSOLETE	-	SILICONE METHYL/VINYL PINK	201	15.5	4.9	20.8±0.3	10.2	7.25	4.29.5	-	-	-	12040755	-
12186822	AB	-	-	-	SILICONE METHYL/VINYL WHITE	201	21.94±0.15	4.9	27.2±0.3	10.2	7.25	-	-	-	-	12059220	0.667
12160724	A11	-	-	-	SILICONE METHYL/VINYL YELLOW	201	24.94±0.15	8.07	29.74±0.15	12.93	4.8	-	-	#1 & #4	-	NONE	0.546
12129925	B14	-	-	-	FLUOROSILICONE METHYL/V ORANGE	201	11	5.94±0.3	16.3±0.3	11.3±0.3	7.1	-	-	#5	-	12052675	0.397
12124684	B10	-	-	-	SILICONE METHYL/VINYL RED	201	29.32±0.15	9.97	34.6±0.15	15.27	7.25	-	-	-	-	12045697	0.886
12124527	A11	-	-	-	SILICONE METHYL/VINYL GREEN	201	18.95	10.1	24.25±0.15	15.4	7.25	-	-	-	-	12110535	0.646
12110555	A12	-	-	-	EPICHLOROHYDRIN BLACK	201	12.35	4.9	17.65	10.2	7.25	-	-	-	-	12047910	0.423
12110212	B11	-	-	-	FLUOROCARBON BLUE	201	11.8	5	16	9.2	4.8	-	-	-	-	12066502	0.242
12103067	02	AG	-	-	SILICONE METHYL/VINYL GRAY	201	11.2	6	16.5±0.3	11.3±0.3	7.25	-	-	-	-	12052675	0.425
12092580	A15	-	-	-	FLUOROSILICONE METHYL/V ORANGE	202	10.1	5.43	14.5±0.3	10.1±0.3	4.357	-	-	#5	-	12092581	0.220
12066601	04	AG	-	-	SILICONE METHYL/VINYL BLUE	201	12.6	5.1	16.3±0.3	9.4	4.8	-	-	-	-	12066602	0.252
12065812	A14	-	-	-	SILICONE METHYL/VINYL GRAY	201	9.25	5	13.55	9.3	4.8	-	-	-	-	12052887	0.210
12065297	C12	-	-	-	SILICONE METHYL/VINYL GREEN	201	15.7	11.8	21.3±0.3	17.3±0.3	7.25	-	-	-	-	12048076	0.694
12059672	B14	-	-	-	SILICONE METHYL/VINYL GRAY	201	27.40.15	5.95	32.3±0.15	11.25	7.25	-	-	-	-	12059494	0.779
12059226	B14	-	-	-	SILICONE METHYL/VINYL BLUE	201	21.94±0.15	4.9	27.2±0.30	10.2	7.25	-	-	-	-	12059220	0.667
12059184	01	AH	-	-	SILICONE METHYL/VINYL TAN	201	15.14	6.72	20.44±0.3	12.02	7.25	-	-	-	-	12059180	0.516
12052888	B13	-	-	-	EPICHLOROHYDRIN BROWN	202	10.1	5.6	14.5±0.3	10.1±0.3	4.75	-	-	#3	-	12052887	0.221
12052842	03	AG	-	-	SILICONE METHYL/VINYL VIOLET	201	16.9	6	22.2±0.3	11.3±0.3	7.25	-	-	-	-	12052841	0.553
12052633	C	-	OBSOLETE	-	SILICONE METHYL/VINYL BLUE	201	11.2	6	16.5±0.3	11.3±0.3	7.25	-	-	-	12103067	12052675	-
12052052	B12	-	-	-	SILICONE METHYL/VINYL ORANGE	201	16.7	8.6	22±0.3	13.9±0.3	7.25	-	-	-	-	12048356	0.574
12018116	B15	-	-	-	SILICONE METHYL/VINYL GREEN	201	28.48±0.13	8.96	33.1±0.15	14.22	7.25	-	-	-	-	12048111	1.092
12048077	B	-	OBSOLETE	-	SILICONE METHYL/VINYL DARK RED	201	15.7	11.8	21.3±0.3	17.3±0.3	7.25	-	-	-	12065297	12048076	-
12047949	04	AS	-	-	SILICONE METHYL/VINYL TAN	201	22.1±0.15	6	27.4±0.3	11.3±0.3	7.25	-	-	-	-	12047947	0.669
12047908	A16	-	-	-	SILICONE METHYL/VINYL GREEN	201	12.35	4.9	17.65	10.2	7.25	-	-	#2	-	12047905	0.430
12045698	A	-	OBSOLETE	-	SILICONE METHYL/VINYL GREEN	201	21.40.15	10.9	26.3	16.2	7.25	-	-	-	-	12045697	-
12041399	A14	-	-	-	SILICONE METHYL/VINYL GREEN	202	9.2	4.9	14.5±0.3	10.2±0.3	4.75	-	-	-	-	12041400	0.226
12040945	02	AS	-	-	SILICONE METHYL/VINYL GREEN	201	18.7	4.9	24±0.3	10.2	7.25	4.49.5	-	-	-	12040944	0.575
12040756	03	AS	-	-	SILICONE METHYL/VINYL GREEN	201	19.5	4.9	25.8±0.3	10.2	7.25	4.29.5	-	-	-	12040795	0.513
12040750	B16	-	-	-	SILICONE METHYL/VINYL BLUE	201	9.2	4.9	14.5±0.3	10.2	7.25	4.29.7	-	-	-	12040752	0.366
12020818	08	-	-	-	SILICONE METHYL/VINYL ORANGE	201	15.65	7.05	20.65±0.15	12.05	6±0.3	6.5	-	-	-	12020838	0.442

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS); FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. PARTS ARE TO BE PACKAGED IN SEALED PLASTIC BAGS. GROSS WEIGHT INCLUDING CARTON IS NOT TO EXCEED 34 POUNDS.

3. THIS PART IS CONTROLLED FOR AUTOMATIC FEEDING AS DENOTED ON DRAWING WITH ▲.

4. REFERENCE MATING COMPONENTS OR EQUIVALENT:

   SEE CHART

5. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR BLEMISHES, GATE VESTIGE, AND SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER DMP-4.7-CS-01.

6. THIS PART IS NOT CONTROLLED FOR AUTOMATIC FEEDING.

SPECIAL NOTES

1. PARTS ARE TO BE PACKAGED 1200 PER SEALED PLASTIC BAGS. GROSS WEIGHT INCLUDING CARTON IS NOT TO EXCEED 34 LBS. (THIS NOTE APPLIES TO P/N 12160724 & 15305078 ONLY)

2. FOR P/N 12047908 PART MUST BE WASHED AND DRIED AFTER MOLDING.

3. THIS PART IS TOOLED OR USED AT REINSHAGEN. PHYSICAL CHANGES TO THIS PART MUST BE APPROVED BY REINSHAGEN COMPONENT ENGINEERING.

4. THIS PART IS NOT TO STANDARD AND SHOULD NOT BE USED ON NEW DESIGNS.

5. MATERIAL IS FLUOROSILICONE. PARTS MUST BE POST CURED FOR 4 HOURS AT 400 °F.

6. THIS PART MEETS ALL SEALING REQUIREMENTS OF SAE/USCAR-2, INCLUDING HIGH TEMP AND IMMERSION

7. FOR P/N 15497759 ONLY: PART TO BE POST BAKED FOR 4 HOURS AT 400 °F.

DWG TYPE: PART DRAWING
STYLE
VOLUME (CM³): SEE CHART
SCHEM DWG: D

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS WITH NON-CUMULATIVE TOLERANCING PER ASME Y14.5M-1994. GEOMETRIC TOLERANCING PER ASME Y14.5M-1994. MACHINED SURFACES ARE 1.6 µm (63 µin) AVERAGE ROUGHNESS (Ra) OR BETTER UNLESS OTHERWISE SPECIFIED. BREAK ALL SHARP EDGES 0.2 MAX UNLESS OTHERWISE SPECIFIED. DRAFT ANGLES ARE 1° MINIMUM UNLESS OTHERWISE SPECIFIED. ALL DIMENSIONS ARE IN MILLIMETERS.

REFERENCE

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

ATMOSPHERIC MOISTURE (MAX)

FROM	0	25	50	75	100	125	150	175	200	225	250	275	300	325	350	375	400
TO	25	50	75	100	125	150	175	200	225	250	275	300	325	350	375	400	

TOLERANCE ON DIES WITH ACTUAL SPECIFIED LIMITS ARE EQUAL (MAX)

.XX	.XXX	ANGLES	FRACTIONS
±0.25	±0.127	±1°	±1/32

(4) PROCESS INSPECTION DIMENSION	DIMENSIONS ON DWGS AT ( ) INDICATE PROCESS INSPECTION. NOT TO BE USED AS TOLERANCE LIMITS OR DESIGN DIMS.		

DELPHI
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
WARREN, OH

DR	DATE
APVD1 P. YABUR	02JN94
APVD2 D. BRANTINGHAM	06JN94
APVD3 K.D. MURPHY	27JN94
APVD4	
APVD5	

SUBSTANCES OF CONCERN AND RECYCLED
COPYRIGHT 1994 BY DELPHI (DRAWING)

MATERIAL
SEE CHART

DRAWING NAME
TAXI SEAL CONN

DRAWING NUMBER
12077524

SIZE	SCALE	TRANS NO	SHEET NO	REV	NO/TYP
A0	5:1	1 OF 1	2 OF	R	20 -