

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, GILDING, EXTRA SPRING TEMPER
PLATING - 0.0050±0.0025 MM THICK TIN

MINIMUMS

ELECTRICAL CONDUCTIVITY - > 20% IACS @ 20°C. USE OF A MATERIAL WITH CONDUCTIVITY < 20% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 407 MPa

PLATING - FOR LOW ENERGY (< 5V) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.0050±0.0025MM THICK TIN. FOR MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.005±0.0025 MM THICK IS REQUIRED.

MATING BLADE INFORMATION

SCALE 10:1
INSPECTION SYMBOLS SHOWN IN THESE VIEWS ARE FOR REFERENCE ONLY





SECTION A-A



SECTION B-B

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
   ALL RADII 0.4
   DRAFT IS 1° ON ALL SURFACES
2. TERMINALS MUST WITHSTAND A MINIMUM PUSHOUT FORCE OF 67 NEWTONS.
3. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC DIVISION.

RECOMMENDED MATERIAL:

GLASS REINFORCED NYLON OR POLYESTER.



MATING CONNECTOR INFORMATION



	15496460	01	-		12162207	12092580	12092579 - RUST ORANGE
	12162218	A	-		12162214	12065812	12084429 - YELLOW
4	12162217	A	-		12162214	12052888	12084421 - GRAY
	12162216	A	-		12162214	12065812	12065799 - LT GRAY
4	12162215	A	-		12162214	12052888	12052887 - BROWN
4	12162208	A	-		12162207	12052888	12052887 - BROWN
4	12162206	A	-		12162205	12052888	12052887 - BROWN
	12162204	A	-		12162203	12092580	12092579 - RUST ORANGE
NOTES	PART NO	REV	N/P	STATUS	CONN	CONN SEAL	CABLE SEAL & COLOR

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. REFERENCE MATING COMPONENTS OR EQUIVALENT:
   TERMINAL 12124075
   THROTTLE BODY INJECTOR
3. WHEN PARTS ARE SHIPPED, THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.
4. USE 10 ML PER 1,000 SEALS OF S-60-T LUBEWELL AT 10:1 CONCENTRATION FOR ASSEMBLY OF CABLE SEALS ONLY.
5. FOR LEAD LENGTH CALCULATIONS, DISTANCE FROM MATING END OF CONNECTOR TO FRONT OF CABLE CORE IS 10.15/7.05.

VIEW SCALE DOES NOT REFLECT ACTUAL PART SIZE

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 65	NO MISSING SYMBOL NUMBER
	LAST NO. USED: 56	

DWG STATUS DATE	STS	REV	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD J.E.	APVD LN
03JNO4	R	01	-	-		CLEARED REVISION COLUMN & REDRAWN TO PDI: 15496460 - RELEASED	255443	ECB	AUG	LN

	DATE
DR APVD1 J. COLDSNOR	07FEB94
APVD2 J. COLDSNOR	07FEB94
APVD3 S.J. VUKMER	15FEB94
APVD4	
APVD5	

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI 10PM004

MATERIAL: SEE DRAWING

FINISH: AMS CONN DF M/P 150.2 P2S

DRAWING NUMBER: 12162267

SIZE A0 | SCALE 5:1 | FRAME NO 1 OF 1 | SHEET NO 1 OF 1 | STS R | REV 01 | WT -

DELPHI
DELPHI PACKARD ELECTRIC SYSTEMS
WARREN, OH

NAME TYPE: PART DRAWING
STYLE
VOLUME (OPT)
STATE CODE: D
RELEASE: 6900

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ANSI Y14.5M-1994
THIS DRAWING IS THE PROPRIETARY PROPERTY OF DELPHI PACKARD ELECTRIC SYSTEMS AND IS NOT TO BE REPRODUCED OR USED IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DELPHI PACKARD ELECTRIC SYSTEMS OR DATUM REFERENCES

ALL DIMENSIONS ARE IN MILLIMETERS

(13) PROCESS SENSITIVE DIMENSION
REFERENCE
FORMULA OF CRITICAL TO QUALITY (CTQ) VALUES: NONE
LIMITS ON ENGINEERING

0.1 MAX
± 0.2 MAX
SHARP CORNER TOLERANCE

DIMENSIONAL RANGE (MM) | CHART ID
FROM 0.5 | 3.15 | 6.30 | 10 | 18 | 30 | 50 | 80 | 120 | 180 | 250 | 315 | 400
TO 3.15 | 6.30 | 10 | 18 | 30 | 50 | 80 | 120 | 180 | 250 | 315 | 400 | 500
TOLERANCE CLASS IT (UNLESS OTHERWISE SPECIFIED)
10 | 14 | 18 | 22 | 27 | 33 | 39 | 46 | 54 | 63 | 72 | 81 | 89 | 97
ISO286-1 AT 20°C

THIRD ANGLE PROJECTION
DO NOT SCALE
USE MATH DATA