DO NOT SCALE

D

DELPHI PACKARD ELECTRIC SYSTEMS
WARREN, OHIO 44486

PART NO 1206 5978

SYMBOL DEFINITION			MISSING NUMBERS
THE NUMBER INSIDE THE SYMBOL ◯ CORRESPONDS TO THE NUMBER ON THE INSPECTION REPORT FOR THIS DRAWING/PART NUMBER	TOTAL NO. OF SYMBOLS ON DRAWING	16	
	LAST NO. USED	25	

DATE	SYM	REVISION RECORD	AUTH	DR	CK
26MY99	E5	REDRAWN TO PD & ADDED			
		4X 1 TYP DIM	19358	BDA	ACMF









PART NO 1206 5978

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. MATING COMPONENTS OR EQUIVALENT:
   MICRO RELAY 12065118
3. THIS PART ACCEPTS THE FOLLOWING COMPONENTS OR EQUIVALENT:
   CAVITIES "1", "4" & "2" TO ACCEPT 12065892 METRI-PACK-SPECIAL TERMINAL OR EQUIVALENT.
   CAVITIES "5" & "3" TO ACCEPT 12015865 (630 MP SPECIAL) TERMINAL OR EQUIVALENT.
   CAVITY "1" TO ACCEPT 3.7 MAX HIGH X 5 MAX WIDE INSULATION CRIMP.
   MAX INSULATION CRIMP MUST BE LESS THAN 3.52 HIGH AND 6 WIDE (CAVITIES "5" & "3").
   SECONDARY TERMINAL LOCK 12065979
4. CLIP SLOT IS NON STANDARD. CLIP SLOT WILL ACCEPT 2984621 STYLE CLIPS (METAL) OR EQUIVALENT.

(2) PROCESS SENSITIVE DIMENSION

DIMENSIONS ENCLOSED IN ( ), INDICATE REFERENCE DIMENSIONS AND NO TOLERANCE LIMITS ARE ESTABLISHED

DIMENSIONAL RANGE					
FROM	0	> 20	> 30	> 70	> 100
TO	20	30	70	100	
TOLERANCE UNLESS OTHERWISE SPECIFIED					
	±0.1	±0.2	±0.3	±0.4	±0.5
ANGULAR TOLERANCE ± 2°					

PART DRAWING

Unigraphics

THIRD ANGLE PROJECTION

CODE NO 6900 | QC

METRIC
DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED

DWG DATE 23MY86

SCALE 5:1

DES

REFERENCE NO 001,701

DR R. BALDWIN 23MY86
CK F. HESTON 28MY86
APPR J.C. GRIFFIN 29MY86

VOL CM³ 6.560

MATERIAL SPEC R0100151 PBT-REPELLETIZED-BLK

NAME CONN 5F M/P 480, 630 SPL

PART NUMBER 1206 5978

SIZE A1