SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (☐) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 12	NO MISSING SYMBOL NUMBER
	LAST NO. USED: 8	

DWG STATUS DATE	STR	REV	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD I.E.	APVD I.E.
JOL02	R	C3	-	-		REDRAWN TO PD; MAT'L SPEC WAS R0:00151, ADDED NOTES 13 PLUS1, REVISED LOGO & RECYCLING CODE	226929	RCH	RH	ET
16MR04	R	04	-	-		ADDED RADIUS TO LOCK 4 PLACES	253102	LMR	MB	BG
29MR04	R	04	AA	-		REVISED "PART ACCEPTS" NOTE TO "2.65 WIDE"	253521	ADK	ADK	BG















OPTIONAL CONSTRUCTION





NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS!). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. MATERIAL RECYCLING CODE >PBT< PER SAE J1344. (1)X(0.1) RAISED CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE.
3. MATING COMPONENTS OR EQUIVALENT:
   CONNECTOR 12064758
4. THIS PART ACCEPTS THE FOLLOWING COMPONENTS OR EQUIVALENT:
   CAVITIES TO ACCEPT 12040993 TERMINAL OR EQUIVALENT.
   MAX INSULATION CRIMP MUST BE LESS THAN 3 HIGH AND 2.65 WIDE.
   SECONDARY TERMINAL LOCK 12047784
5. THIS CONNECTOR WILL PASS THROUGH A 20.5 DIA MIN HOLE.
6. (1)X(0.1) RAISED DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION TO BE "PBT" OR NO LOGO.

NAME TYPE	PART DRAWING
STYLE	
VOLUME (CAT)	2.002
ENTITY CODE	D
RUNTIME	6900

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
TOLERANCING PER ISO 1101. ALL DIMENSIONS, TOLERANCES AND DRAFTING STANDARDS ARE IN SI (MM) UNITS. FINAL PLATING/COATING SHALL NOT EXCEED MAXIMUM DIMENSIONS SPECIFIED. ALL PLATING/COATING TO BE APPLIED AFTER ANY MACHINING OPERATIONS. DATUMS AND DIMENSIONS APPLY TO PLATED/COATED PARTS ONLY. DATUMS ESTABLISHED BY ORIENTATION OF EQUATING TOLERANCES. SEPARATE POSITION CALLOUTS MAY BE CHAIN SEPARATELY. DIMENSIONS ARE NOT TO SCALE.
ALL DIMENSIONS ARE IN MILLIMETERS

(S) PROCESS SENSITIVE DIMENSION
REFERENCE
FORMULA OF CALCULATED TOLERANCE (Tol.) IS RELATED TO THE NUMBER OF DECIMAL PLACES IN THE NOMINAL LIMITS ON DRAWING

0.1 MAX
0.2 MAX
SHARP CORNER TOLERANCE

NUMERICAL RANGE (MM)	CHART 01							
FROM	>3	>6	>10	>30	>100	>200	>250	>300
TO	6	10	30	100	200	250	300	400
ALLOWANCE (TOLERANCE SPECIFIED)								
±0.15	±0.2	±0.25	±0.3	±0.4	±0.5	±0.6	±0.7	±0.8
ANGULAR TOLERANCE ±0								

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

MATERIAL	MMS75002 PBT BLK
DRAWING NAME	CONN 3 M M/P 150 BLK
DRAWING NUMBER	12064759
SIZE	A0
SCALE	5:1
FRAME NO	1 OF 1
SHEET NO	1 OF 1
STR	R
REV	04
REV NUM	AA

DELPHI

DELPHI PACKARD ELECTRIC SYSTEMS
WARREN, OH

	DATE
DR: APVD1 ANDY J. LE	24NOV05
APVD2 P.J. HESTON	30CT05
APVD3 S.A. NORLING	09NOV05
APVD4	
APVD5	

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI 10PM004