

MATERIAL SPECIFICATIONS

RECOMMENDED
BASE METAL - COA-210, GILDING, EXTRA SPRING TEMPER
PLATING - 0.005 ±0.0025 MM THK TIN

MINIMUMS
ELECTRICAL CONDUCTIVITY - ≥ 20% IACS ±20°C. USE OF A MATERIAL WITH CONDUCTIVITY < 20% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 407 MPa

PLATING - FOR LOW ENERGY (≤ 5 V) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.005 ±0.0025 MM THICK TIN. FOR MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.005 ±0.0025 MM THICK IS REQUIRED.

BLADE THICKNESS
UNPLATED = 0.813 ±0.025
TIN PLATED = 0.823 ±0.03

MATING BLADE INFORMATION
SCALE 8:1





SECTION A-A



SECTION B-B

NOTES:
1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN
ALL RADII 0.4
DRAFT IS 1° ON ALL OUTSIDE SURFACES
2. RECOMMENDED MATERIAL - GLASS FILLED NYLON OR POLYESTER.
3. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC DIVISION.

MATING CONNECTOR INFORMATION





NOTES
1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. WHEN PARTS ARE SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID FOREIGN MATTER.
3. SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN ESA-644 (WEATHER-PACK), ESA-710 (METRI-PACK), ESA-650 (UNDERHOOD MICRO-PACK), C-4006 (WORLD CONNECTOR), ETC. WHEN MATED TO MATING PART OR EQUIVALENT
4. FOR LEAD LENGTH CALCULATIONS, DISTANCE FROM MATING END OF CONNECTOR TO FRONT OF CABLE CORE IS 8.5 ±1.55.
○ 5. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

15324667	02	AA	15324668	- - - - - - - -	- - - - - - - -	12040756
12162834	04	AA	12162724	12070808/TAN	- - - - - - - -	12040756
12162833	02	AA	12162724	12040757/GREEN	- - - - - - - -	12040756
PART NO	REV	N/P	CONNECTOR	CABLE SEAL & COLOR		CONN SEAL

SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (▢) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	17
	LAST NO. USED	17

MISSING SYMBOLS
NO MISSING SYMBOL NUMBER

DWG STATUS DATE	STR	REL	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
09SEP02	R	06	-	-		12162834 - CONNECTOR SEAL WAS 15324919	29416	RIVERA	JR	
12SEP16	R	07	-	-		ALL PARTS - 1.5 WAS 1.5 ±1.3 AND ADDED APPLICATION DATA NOTE.	43411	APB	APB	ACM

APVD1 P. QUEQUERA		25SEP95
APVD2 R. RAMOS S.		26SEP95
APVD3 T. L. LEE, JR		12JAN96
APVD4		
APVD5		

SUBSTANCES OF CONCERN AND RECYCLED

MATERIAL	SEE DWG
FINISH	

DRAWING NAME: TAXI ASM CONN F M/P 150.2 SLD

DRAWING NUMBER: 12162835

SIZE	SCALE	TRACE NO	SHEET NO	TOT	REV	N/P
AD	4:1		1 OF 1	1	R	07 -

DELPHI
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE

COPYRIGHT 1996 DELPHI PACKARD ELECTRIC SYSTEMS, A DELPHI AUTOMOTIVE SYSTEMS LLC
ALL RIGHTS RESERVED.
PRINTED IN U.S.A.
THIS DRAWING IS THE EXCLUSIVE PROPRIETARY PROPERTY OF DELPHI PACKARD ELECTRIC SYSTEMS, A DELPHI AUTOMOTIVE SYSTEMS LLC BUSINESS AND IS NOT TO BE COPIED OR USED IN WHOLE OR IN PART FOR ANY PURPOSE WITHOUT EXPRESS AUTHORIZATION. IT IS PROVIDED ON A CONFIDENTIAL BASIS.

DATE
25SEP95
26SEP95
12JAN96

THIS DRAWING IS TO BE USED FOR REFERENCE ONLY. THE DRAWING THEREBY FOR SUBJECT PART NUMBER MAY NOT BE AVAILABLE FOR ORDERING.

PART NUMBERS THAT OR NOT HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT DELPHI SALES TO ASSURE AVAILABILITY OF PARTS.

DRAWING TYPE	PART DRAWING
STYLE	
RELEASE STATUS	DESIGN OWNER

UNLESS OTHERWISE SPECIFIED

DIMENSIONS	ARE IN MILLIMETERS WITH NON-CUMULATIVE TOLERANCES PER ASME Y14.5M-1994
TOLERANCING	PER ASME Y14.5M-1994
MATERIALS	AND FINISHES ARE AS SPECIFIED HEREIN
INTERPRET	DRAWING IN ACCORDANCE WITH ASME Y14.100
ALL DIMENSIONS	ARE IN MILLIMETERS

REFERENCE	
THIRD ANGLE PROJECTION	
DO NOT SCALE	
USE MATH DATA	

STANDARDIZED RADIUS (MM)										
FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

STANDARDIZED ANGLES (DEGREES)										
FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

FROM	0	30	45	60	75	100	150	200	250	300
TO	30	45	60	75	100	150	200	250	300	400

FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

FROM	0	30	45	60	75	100	150	200	250	300
TO	30	45	60	75	100	150	200	250	300	400

UNLESS OTHERWISE SPECIFIED
TOLERANCING PER ASME Y14.5M-1994
DIMENSIONS ARE IN MILLIMETERS
INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.100
ALL DRAWINGS ARE IN MILLIMETERS

PROCESS SENSITIVE DIMENSION
DIMENSIONS ESTABLISHED BY 3 DATUMS
DIMENSIONS ESTABLISHED BY 2 DATUMS
LIMITS ARE EQUAL BILATERAL

FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

FROM	0	30	45	60	75	100	150	200	250	300
TO	30	45	60	75	100	150	200	250	300	400

FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

FROM	0	30	45	60	75	100	150	200	250	300
TO	30	45	60	75	100	150	200	250	300	400

FROM	0.5	1.50	3.18	5.74	9.53	12.70	15.88	19.05	22.23	25.40
TO	1.25	2.75	4.75	7.95	11.10	14.30	17.50	20.60	23.80	26.90

FROM	0	30	45	60	75	100	150	200	250	300
TO	30	45	60	75	100	150	200	250	300	400