SYMBOL DEFINITION			MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL [ ] DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	3	NO MISSING SYMBOL NUMBER
	LAST NO. USED	3	

DWG STATUS DATE	STS	REC	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	APVD/APVD 2
09JN05	R	01	-	-		1531469 - WAS SEPARATE DWG; ADDED 1531958 - RELEASED	2588876	RH	RH	NLL
28APR06	R	02	-	-		ALL PARTS - 2.1MM WAS 2.8MM IN NOTE 3; REVISED CONNECTOR GRAPHICS TO LATEST MODELING STANDARDS	2800661	RH	RH	NLL
28MY10	R	03	-	-		SHT 1 OF 2 WAS SHT 1 OF 1	4109335	KHY	JAMMEA	



EXPLODED ASSEMBLY VIEW





RECOMMENDED SIDE FOR SECONDARY LOCK INSERTION



CONNECTOR - SEE CHART

TYPE 101
USCAR TYPE A







TYPE 106
USCAR TYPE F
SAME AS TYPE 101
EXCEPT AS SHOWN



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. CONNECTOR VALIDATED PER SAE/USCAR-2:
   TEMPERATURE CLASS 1, VIBRATION FOR COMPONENTS NOT COUPLED TO ENGINE.
   -SAE/USCAR-2 MAY 2004: 5.4.5 - SECONDARY LOCK DISENGAGE FORCE: 20N MIN
   -SAE/USCAR-2 MAY 2004: 5.4.2 - PRIMARY CONNECTOR LOCK DISENGAGE FORCE: 6.5N MIN
   -SAE/USCAR-2 MAY 2004: 5.4.5 - CPA DISENGAGE FORCE (LOCK TO PRE-SET): 35N MAX

3. MATING BLADE REQUIREMENTS ARE FOUND ON USCAR/EWCAP DRAWING #EWCAP-001 REV C SECTION "064-T001".

4. ASSEMBLY TO BE USED WITH APPROPRIATE DELPHI PACKARD ELECTRIC HOLDER DESIGN.

5. ASSEMBLY TO BE PROCESSED USING DELPHI PACKARD ELECTRIC SYSTEMS BEST PRACTICE METHODS AND/OR CONNECTOR ASSEMBLY INSTRUCTIONS, AND APPLICABLE REPAIR PROCEDURES.

6. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

VIEW SCALE DOES NOT REFLECT ACTUAL PART SIZE

PART NO	REV	N/P	STATUS	TYPE	CONNECTOR	CONNECTOR COLOR	USCAR TYPE
1531958	02	-		106	1531954	NATURAL	F
1531469	02	-		101	1531467	BLACK	A

ATMOSPHERICAL RANGE (MA)

FROM	0	250	750	1250	2100	3150	5250	7350	10500
TO	250	750	1250	2100	3150	5250	7350	10500	14000

ENVIRONMENTAL CONDITIONS SPECIFICATION
EWCAP-001 REV C | SAE/USCAR-2 REV 3 | ISO 16750-4 | OTHER

DRAWING NO. 1531959 REV 03

PART DRAWING		
DWG TYPE		
STYLE		
RELEASE DATE	SCREEN DWG	D

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS TO BE INTERPRETED WITH ASME Y14.5M-1994 AND ISO 8015:1985 GEOMETRIC DIMENSIONING AND TOLERANCING PRINCIPLES.
FEATURES NOT TO BE INSPECTED UNLESS OTHERWISE SPECIFIED.

ALL DIMENSIONS ARE IN MILLIMETERS

(N/A) PROCESS INSPECTION DIMENSION
DIMENSIONS (NO SPACE) WITH A 3 INDICATE CRITICAL TO FUNCTION (CTF) AS PER "CLEARANCE LIMITS ARE EQUAL/BILATERAL"

THIRD ANGLE PROJECTION | DO NOT SCALE | USE MATH DATA

DELPHI
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
WARREN, OH

DR	DATE
APVD1 ROBERT HURD	09JN05
APVD2 ROBERT HURD	09JN05
APVD3 NICOLE LIPTAK	15JN05
APVD4	
APVD5	

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI-A 1554900

MATERIAL
SEE DRAWING

DRAWING NAME
TAXI ASM CONN F MICRO HVT

DRAWING NUMBER
1531959

SIZE	SCALE	TRANS NO	SHEET NO	STS	REV	N/P
A0	5:1	1	1 OF 1	R	03	-