



- ## NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED, DIMENSIONS ARE TO FACE OF VIEW SHOWN AND DIMENSIONAL TOLERANCES ARE UNLESS OTHERWISE SPECIFIED.
2. DIMENSIONS ARE TO FACE UNLESS OTHERWISE SPECIFIED. OTHER DIMENSIONS NOT SHOWN, BUT REQUIRED FOR TOOLING, SHALL BE DETERMINED BY THE PRECISE TOOL PATH DATA. ALL RADIUS 0.4.
3. DIMENSIONS ARE IDENTICAL UNLESS OTHERWISE SPECIFIED. LOCKING FEATURES ARE IDENTICAL UNLESS OTHERWISE SPECIFIED.
4. TOOL CAVITY IDENTIFICATION SHOULD BE LOCATED AS CLOSE TO THE GATE AS POSSIBLE.
5. MATEL COATING CODE SHOULD BE 101649, 11, 61X10, 11 RAISED CHARACTERS AS SHOWN TO BE LOCATED ON AN EXTERIOR SURFACE.
6. SEALING CODE - UNSEALED.
7. 11, 61X10, 11 RAISED FINE LINE CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE AS SHOWN VISIBLE AT FINAL ASSEMBLY.
8. THIS PART ACCEPTS FOR THE COMPONENTS OR EQUIVALENT:
- CAVITIES A1 TO A3, J1 TO J3 TO ACCEPT 12052224 TERMINAL. H1 TO H3 TO ACCEPT 12052224 TERMINAL. LESS THAN 5.55 HIGH AND 7.5 HIGH.
- CAVITIES B1 TO B6, C1 TO C6, D1 TO D4 & F2 TO F4, 01 TO 06, H1 TO H3 TO ACCEPT 12052224 TERMINAL. LESS THAN 5.55 HIGH AND 7.5 HIGH. MAX INSULATION CRIMP MUST BE LESS THAN 0.32 HIGH AND 0.2 HIGH.
- CAVITIES D1,D5 & F1,F3 ACCEPT 15034711 TERMINAL. THICK 0.32 HIGH AND 5.15 WIDE.
- CAVITIES E1, E2 TO ACCEPT 15034711 TERMINAL. MAX INSULATION CRIMP MUST BE LESS THAN 0.32 HIGH AND 0.2 HIGH.
- SECONDARY TERMINAL LOCK 13682697.
- WIRE DRESS CORN
- LOT TYPE 1 13682696, .10C TYPE 1 13682628

7. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

7		6		5	
SYMBOL DEFINITION					
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ☐ DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.				TOTAL NO OF INSPECTIONS REQUIRED	
				LAST NO. USED	

MISSING SYMBOLS		ONE STATUS					ZONE		REVISION HISTORY		AUTH		DR		APR		P2	
		DATE	STG	REV	PLP	ONE												
7	NO MISSING SYMBOL NUMBER	26DEC7	R	01	-	-	-	-	CREATED DRAWING				HSP		KYL			
		27FE14	R	02	-	-	-	-	CREATED POW ATTRIBUTES				HSP		KYL			

13682771	13682689	1	01	-	-	M4629012 PBT GF20 1M HS - GRA LT	102	29,589
13682770	13682686	1	01	-	-	M4629002 PBT GF20 1M HS - BLK	101	29,589
ASM P/N	CONNECTOR P/N	STG	REV	N/P	STATUS	MATERIAL SPECIFICATION AND COLOR	TYPE	VOLUME

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15	Q16	Q17	Q18	Q19	Q20	Q21	Q22	Q23	Q24	Q25	Q26	Q27	Q28	Q29	Q30	Q31	Q32	Q33	Q34	Q35	Q36	Q37	Q38	Q39	Q40	Q41	Q42	Q43	Q44	Q45	Q46	Q47	Q48	Q49	Q50	Q51	Q52	Q53	Q54	Q55	Q56	Q57	Q58	Q59	Q60	Q61	Q62	Q63	Q64	Q65	Q66	Q67	Q68	Q69	Q70	Q71	Q72	Q73	Q74	Q75	Q76	Q77	Q78	Q79	Q80	Q81	Q82	Q83	Q84	Q85	Q86	Q87	Q88	Q89	Q90	Q91	Q92	Q93	Q94	Q95	Q96	Q97	Q98	Q99	Q100
10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560	570	580	590	600	610	620	630	640	650	660	670	680	690	700	710	720	730	740	750	760	770	780	790	800	810	820	830	840	850	860	870	880	890	900	910	920	930	940	950	960	970	980	990	1000

[illegible][illegible]