THIS DRAWING AND DESIGN HEREON CONSTITUTES A PROPRIETARY DESIGN OF PACKARD ELECTRIC DIVISION AND IS NOT TO BE DUPLICATED OR REPRODUCED WITHOUT AUTHORITY OF PACKARD ELECTRIC DIVISION.

DO NOT SCALE

PART NO. 1206 6571

PACKARD ELECTRIC DIVISION
GENERAL MOTORS CORPORATION
WARREN, OHIO

DATE	SYM	REVISION RECORD	AUTHORITY	DR	CK
14MY87	A	PART NO. WAS PE08828I AND RELEASED	870005	FM	FH
10OC91	B	MATL WAS NYLON 6 - BLACK	144950	TM	TM



MATING TERMINAL INFORMATION

SCALE 4:1

RECOMMENDED MATERIAL:
P-1546 (CA 210) - EXTRA SPRING TEMPER - TIN PLATED BRASS
PLATING THICKNESS: 0.003-0.005 MM
TENSILE STRENGTH: 430-480 MPA
MATERIAL SHOULD HAVE AN ELECTRICAL CONDUCTIVITY ≥ 20% IACS AT 68°F.
USE OF A MATERIAL WITH A CONDUCTIVITY <20% IACS AT 68°F SHOULD BE APPROVED BY PACKARD ELECTRIC.



SECTION A-A









NOTES —
1. CAVITIES TO ACCEPT 12015828 TERMINAL OR EQUIVALENT.
2. CONNECTOR TO ACCEPT 12066572 T.P.A. OR EQUIVALENT.
3. MATING COMPONENT DETAILS SHOWN ABOVE.
4. CONNECTOR TO ACCEPT 12052834 C.P.A. LOCK OR EQUIVALENT.





MATING SHROUD DETAIL

SCALE 4:1

SECTION B-B

RECOMMENDED MATERIAL:

NYLON 6 OR A GLASS FILLED POLYESTER

NOTES —
1. 1° DRAFT ON ALL OUTSIDE SURFACES, UNLESS OTHERWISE SPECIFIED.
2. DIMENSIONS ARE TO FACE OF VIEW SHOWN, UNLESS OTHERWISE INDICATED.
3. ALL RADII 0.40, UNLESS OTHERWISE SPECIFIED.

PED/INTERGRAPH MICROSTATION
THIRD ANGLE PROJECTION
FILE SPEC: ****USER****
DGN=SPECIFICATION*********
*****DTM=******
METRIC
DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
CODE NO. 6901
TOLERANCE UNLESS OTHERWISE SPECIFIED
DECIMALS ANGULAR ±2°
ONE PLACE ±0.3
TWO PLACE ±0.25
Q.C.
DWG. DATE 08JA87
SCALE NONE
DR. M.C. Jackson 17FE87
EST. NO.
CK. DATE
REFERENCE NO.
APPR. DATE
APPR. DATE
(B) MATERIAL SPEC. IM HS NYLON 66 - BLACK
NAME CONN, 4F M/P 480
PART NO. 1206 6571
OUTLINE DRAWING
SIZE D
PACKARD ELECTRIC