

Technical drawing of a Delphi 12-pin connector assembly. The drawing includes several views: a top view showing a 12-pin configuration with dimensions (12) and (12.1); a side view showing a 12-pin configuration with dimensions (12) and (12.1); a front view showing a 12-pin configuration with dimensions (12) and (12.1); a detail view of the connector housing with dimensions (12) and (12.1); and a side view of the connector housing with dimensions (12) and (12.1). The drawing also includes a note indicating that the dimensions are to the face of the view shown and are automatically rounded by computer for inspection.

NOTES

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
DIMENSIONS ARE TO FACE OF VIEW SHOWN AND
AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION
(SEE MATH MODEL FOR PRECISE DIMENSIONS). - FOR ALL
OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL
BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
- MATERIAL RECYCLING CODE: 3PA66C PER SAE J1344. (12-31X10.1) RA
CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE.
OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE.
- MATING COMPONENTS OR EQUIVALENTS:
CONNECTOR (712485)
MAX CABLE O.D. MUST BE LESS THAN 2.43.
- (12-31X10.1) RAISED DELPHI CORPORATE BRAND TO BE LOCATED ON AN
EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY.
OPTIONAL CONSTRUCTION TO BE "RISP" OR NO LOGO.